Product data sheet
Characteristics

QO2251042
Mini CB, QO, 25 A, 2P, 120/240 V, 10 kA, Plug in, Shunt Trip

Price** : 256.00 USD



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	25 A
Voltage Rating	120/240 V AC 120 V AC 48 V DC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate
Options	Shunt trip 12/24 V AC/DC

Complementary

Inturrupt Rating	10 kA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz 5 kA 48 V DC
Number of Panel Spaces	3
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening torque	44.25 lbf.in (5 N.m) 0.02…0.04 in² (10…25 mm²) AWG 8...AWG 2)
Height	76.20 mm (3 in)
Depth	73.91 mm (2.91 in)
Width	57.15 mm (2.25 in)

Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	00004-QO,QOT 10-30A 1P;10-60A 2P
Discount Schedule	DE2A
Package weight(Lbs)	14.88 oz (421.841 g)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed

Contractual warranty

Warranty	18 months