QPD2194

300 W, 48 V, 1.8-2.2 GHz GaN RF Power Transistor



2 Lead NI400 Package

Product Description


The QPD2194 is a discrete GaN on SiC HEMT which operates from 1.8-2.2 GHz. The device is a single stage pre-matched power amplifier transistor.

The QPD2194 can be used in Doherty architecture for the final stage of a base station power amplifier for macrocell high efficiency systems.

QPD2194 can deliver P_{SAT} of 371 W at +48 V operation.

Lead-free and ROHS compliant.

Functional Block Diagram



Product Features

- Operating Frequency Range: 1.8-2.2 GHz
- Operating Drain Voltage: +48 V
- Maximum Output Power (P_{SAT}): 371 W
- Maximum Drain Efficiency: 78.8%
- Efficiency-Tuned P3dB Gain: 18.0 dB
- 2-lead, earless, ceramic flange NI400 package

Applications

- W-CDMA / LTE
- Macrocell Base Station, B3-B1
- Active Antenna

Ordering Information

Part No.	ECCN	Description
QPD2194S2	EAR99	Box (2 Samples Each)
QPD2194SQ	EAR99	Tray (25 Samples)
QPD2194SR	EAR99	Reel (100 Samples)
QPD2194PCB4B01	EAR99	1.805-2.17 GHz Eval. Board

Absolute Maximum Ratings

Parameter	Value / Range
Gate Current (I_G)	−48 to 48 mA
Drain Voltage (V_D)	+55 V
Peak RF Input Power	44 dBm
VSWR Mismatch, P1dB Pulse (10 % duty cycle, 100 µ width), T = 25 °C	10:1
Storage Temperature	−65 to +150°C

Operation of this device outside the parameter ranges given above may cause permanent damage.

Recommended Operating

Parameter	Min	Typ	Max	Units
Operating Temperature	−40	–	–	°C
Gate Voltage (V_G)	–	−2.7	–	V
Drain Voltage (V_D)	–	48	–	V
Quiescent Current (I_{DQ})	–	600	–	mA
T_{CH} for >10^6 hours MTTF	–	–	250	°C

Electrical performance is measured under conditions noted in the electrical specifications table. Specifications are not guaranteed over all recommended operating conditions.

RF Characterization

Parameter	Conditions	Min	Typ	Max	Units
Frequency Range		1805	–	2170	MHz
Quiescent Current		–	600	–	mA
Linear Gain		–	19.1	–	dB
P3dB		–	55.0	–	dBm
Drain Efficiency	P3dB	–	60.0	–	%


Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, Pulsed CW (10% duty cycle, 100 µs width) on Class AB single-ended EVB at 1880 MHz

Thermal and Reliability Information


Parameter	Test Conditions	Value	Units
Carrier Amplifier Thermal Resistance at Average Power (θ_{JC})	T_{CASE} = 85°C, T_{CH} = 152°C, CW: P_{DISS} = 60 W, P_{OUT} = 90 W	1.12	°C/W

Notes:
1. Thermal resistance measured to package backside.
2. Based on expected carrier amplifier efficiency of Doherty.
3. P_{OUT} assumes 20% peaking amplifier contribution of total average Doherty rated power.

Median Lifetime




Single-Ended Evaluation Board Layout





Bill of Materials


Reference Des.	Value	Description	Manuf.	Part Number
C1, C2, C3, C4	33 pF	Capacitor, 33 pF, 5%, 250 V	ATC	ATC800A330JT
C5	1.2 oF	Capacitor, 1.2 pF, ±0.1 pF, 250 V	ATC	ATC800A1R2BT250X
C6	1.9 pF	Capacitor, 1.9 pF, ±0.1 pF, 250 V	ATC	ATC800A1R9BT250X
C7	2.2 pF	Capacitor, 2.2 pF, ±0.1 pF, 250 V	ATC	ATC800A2R2BT250X
C8	0.8 pF	Capacitor, 0.8 pF, ±0.1 pF, 250 V	ATC	ATC800A0R8BT250X
C9, C10, C11, C15	4.7 µF	Capacitor, 4.7 µF, 10%, 100 V, X7R	Murata	GRM55ER72A475KA01L
C12	1 µF	Capacitor, 1 µF, 10%, 100 V, X7R	Murata	GRM32NR72A104KA01L
C13	100 µF	Capacitor, 100 µF, ±20%, 50 V, electrolytic	Panasonic	EEE-1HA101UAP
C14	220 µF	Capacitor, 220 µF, 20%, 100 V, electrolytic	Cornell	AFK227M2AR44T-F
R1	10 Ω	Resistor, 10 Ω, 1%, 1/4 W, 1206	Panasonic	ERJ-8ENF10R0V


Single-Ended Evaluation Board Performance Plots
















Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, on Class AB single-ended EVB

Single-Ended Evaluation Board Performance Plots





Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, on Class AB single-ended EVB

RF Characterization – Power-Tuned Load Pull Performance

Frequency (MHz)	Source Impedance	Load Impedance	Gain @ P3dB (dB)	P3dB (dBm)	Drain Efficiency (%)
1800	6.21 – j1.70	6.15 – j5.81	15.1	55.4	54.0
1840	2.31 – j5.94	6.15 – j5.82	15.9	55.7	57.0
1880	4.21 – j2.56	6.00 – j4.30	16.4	55.7	62.5
2110	4.06 – j5.02	6.52 – j2.92	16.4	55.6	66.6
2140	4.24 – j5.12	8.50 – j2.10	15.7	55.6	59.4
2170	1.55 – j2.71	8.00 – j2.10	16.1	55.6	62.2

Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, Pulsed (10% duty cycle, 100 µs width)


RF Characterization – Efficiency-Tuned Load Pull Performance

Frequency (MHz)	Source Impedance	Load Impedance	Gain @ P3dB (dB)	P3dB (dBm)	Drain Efficiency (%)
1800	6.21 – j1.70	2.50 – j1.70	16.8	53.6	70.9
1840	2.31 – j5.94	2.92 – j2.22	17.6	54.3	73.3
1880	4.21 – j2.56	2.53 – j2.80	18.0	54.1	78.8
2110	4.06 – j5.02	2.14 – j3.38	17.6	52.6	78.4
2140	4.24 – j5.12	3.30 – j3.90	17.5	53.8	75.7
2170	1.55 – j2.71	2.23 – j4.27	18.0	52.2	77.7


Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, Pulsed (10% duty cycle, 100 µs width)

Load Pull Plots


Load Pull at 1.8 GHz



Load Pull at 1.84 GHz




Load Pull at 1.88 GHz




Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, Pulsed (10% duty cycle, 100 µs width)

Load Pull Plots


Load Pull at 2.11 GHz



Load Pull at 2.14 GHz




Load Pull at 2.17 GHz



Test conditions unless otherwise noted: V_D = +48 V, I_{DQ} = 600 mA, T = 25°C, Pulsed (10% duty cycle, 100 µs width)

Pin Configuration




Pin Description

Pin No.	Label	Description
1	RF IN, VG	RF Input, Gate Bias
2	RF OUT, VD	RF Output, Drain Bias
3 (Backside Paddle)	RF/DC GND	RF/DC Ground


Package Marking and Dimensions

Marking: Qorvo Logo
Part Number and Package Version – QPD2194
Date Code – YYWW
Production Lot Number – MXXX
Serial Number – ZZZ



Notes:
1. All dimensions are in inches. Angles are in degrees.
2. Exposed metallization is NiAu plated.


Tape and Reel Information – Carrier and Cover Tape Dimensions



Feature	Measure	Symbol	Size (in)	Size (mm)
Cavity	Length	A0	0.417	10.60
	Width	B0	0.419	10.65
	Depth	K0	0.181	4.60
	Pitch	P1	0.630	16
Centerline Distance	Cavity to Perforation – Length Direction	P2	0.079	2.00
	Cavity to Perforation – Width Direction	F	0.559	14.20
Cover Tape	Width	C	1.004	25.50
Carrier Tape	Width	W	1.260	32


Tape and Reel Information – Reel Dimensions

Standard T/R size = 100 pieces on a 13” reel.



Feature	Measure	Symbol	Size (in)	Size (mm)
Flange	Diameter	A	12.992	330.0
	Thickness	W2	1.504	38.2
	Space Between Flange	W1	1.291	32.8
Hub	Outer Diameter	N	4.016	102.0
	Arbor Hole Diameter	C	0.512	13.0
	Key Slit Width	B	0.079	2.0
	Key Slit Diameter	D	0.787	20.0

Tape and Reel Information – Tape Length and Label Placement



Notes:
1. Empty part cavities at the trailing and leading ends are sealed with cover tape. See EIA 481-1-A.
2. Labels are placed on the flange opposite the sprockets in the carrier tape.

Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1B	JEDEC Standard JESD22 A114
ESD – Charged Device Model (CDM)	Class C3	JEDEC Standard JESD22-C101F
MSL – 260°C Convection Reflow	Level 3	JEDEC standard IPC/JEDEC J-STD-020.



Caution!
ESD-Sensitive Device

Solderability

Compatible with both lead-free (260 °C maximum reflow temperature) and tin/lead (245 °C maximum reflow temperature) soldering processes.

The use of no-clean solder to avoid washing after soldering is recommended.

Contact plating: NiAu

RoHS Compliance

This product is compliant with the 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment), as amended by Directive 2015/863/EU. This product also has the following attributes:

- Lead Free
- Antimony Free
- TBBP-A ($C_{15}H_{12}Br_4O_2$) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about Qorvo:

Web: www.qorvo.com **Tel:** +1.972.994.8465
Email: info-sales@qorvo.com **Fax:** +1.972.994.8504

For technical questions and application information:

Email: BTSApplications@qorvo.com

Important Notice

The information contained herein is believed to be reliable. Qorvo makes no warranties regarding the information contained herein. Qorvo assumes no responsibility or liability whatsoever for any of the information contained herein. Qorvo assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.