
Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272
www.pwrx.com

Super Fast Recovery Diode Modules
140 Amperes/600 Volts





Outline Drawing and Circuit Diagram

Dimensions	Millimeters
A	93.5
B	80
C	30
D	26
E	40.5
F	23
G	16.5
H	13

Dimensions	Millimeters
J	12
K	M5
L	7.5
M	25.4
N	4
P	19
Q	6.5 Dia.

Description:

Powerex Super Fast Recovery Dual Diode Modules are designed for use in applications requiring fast switching. The modules are isolated for easy mounting with other components on common heatsinks.

Features:

- ☐ Super Fast Recovery Time
- ☐ RoHS Compliant
- ☐ Isolated Mounting
- ☐ Metal Baseplate
- ☐ Low Thermal Impedance
- ☐ 2500V Isolating Voltage

Applications:

- ☐ Free Wheeling
- ☐ Welding and Plasma Cutting Machine

Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272 www.pwrx.com

QR_0620R30
Super Fast Recovery Dual Diode Modules
140 Amperes/600 Volts

Absolute Maximum Ratings, T_j = 25 °C unless otherwise specified

Ratings	Symbol	QRD0620R30 QRC0620R30 QRF0620R30 QRJ0620R30	Units
Repetitive Peak Reverse Blocking Voltage	V_{RRM}	600	Volts
Non-Repetitive Peak Reverse Blocking Voltage	V_{RSM}	V_{RRM} + 100	Volts
DC Current, T_C = 80°C (Resistive load)	$I_{F(DC)}$	140	Amperes
Peak Half Cycle Non-repetitive Surge Current (t = 8.3mS, 100% V_{RRM} Reapplied)	I_{FSM}	TBD	Amperes
I^2t for Fusing for One Cycle (t = 8.3mS, 100% V_{RRM} Reapplied)	I^2t	TBD	A^2sec
Operating Junction Temperature	T_j	-40 to 150	°C
Storage Temperature	T_{stg}	-40 to 125	°C
Maximum Mounting Torque, M6 Mounting Screw	—	26	in-lb
Maximum Mounting Torque, M5 Terminal Screw	—	17	in-lb
Module Weight (Typical)	—	150	Grams
V Isolation (60 Hz, Circuit to Base, All Terminals Shorted, t = 60 sec)	V_{RMS}	2500	Volts

Electrical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Reverse Leakage Current	I_{RRM}	Rated V_{RRM}	—	—	1.0	mA
On-State Voltage	V_{FM}	I_F = 100A	—	1.6	2.3	Volts
		I_F = 140A	—	1.8	2.5	Volts
Reverse Recovery Time	t_{rr}	I_f = 100A, di/dt = TBD	—	—	120	ns
Reverse Recovery Charge	Q_{rr}	I_f = 100A, di/dt = TBD	—	4.2	—	µC

Thermal and Mechanical Characteristics, T_j = 25 °C unless otherwise specified


Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case*	$R_{th(j-c)}$ Q	Per Diode	—	—	0.205	°C/W
Contact Thermal Resistance, Case to Sink (Lubricated)*	$R_{th(c-s)}$	Per Module	—	—	0.075	°C/W

*T_C, T_f measured point is just under the chip.


Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272 www.pwrx.com

QR_0620R30
Super Fast Recovery Dual Diode Modules
140 Amperes/600 Volts


ON-STATE CHARACTERISTICS (TYPICAL)




TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS




REVERSE RECOVERY CHARACTERISTICS (TYPICAL)




REVERSE RECOVERY SWITCHING LOSS (TYPICAL)




MAXIMUM ON-STATE POWER DISSIPATION (SINUSOIDAL WAVEFORM)



MAXIMUM ALLOWABLE CASE TEMPERATURE (SINUSOIDAL WAVEFORM)



MAXIMUM ON-STATE POWER DISSIPATION (RECTANGULAR WAVEFORM)



MAXIMUM ALLOWABLE CASE TEMPERATURE (RECTANGULAR WAVEFORM)

