

Features

Regulated Converters

- 40W 2" x 2" Package (50.8x11.40x50.8mm)
- 1.6kVDC Isolation
- Wide Input 2:1
- Regulated Output
- UL94V-0 Package Material
- Continuous Short Circuit Protection
- Vout Trim and ON/OFF Control Function
- Efficiency to 87%

Selection Guide

Part Number	Input Voltage	Output Voltage	Output Current	Efficiency
2" x 2"	(VDC)	(VDC)	(mA)	(%)
REC40-xx05SRWB/H	9-18, 18-36, 36-75	5	8000	85/87/88
REC40-xx12SRWB/H	9-18, 18-36, 36-75	12	3333	85/86/87
REC40-xx15SRWB/H	9-18, 18-36, 36-75	15	2666	85/86/87
REC40-xx24SRWB/H	9-18, 18-36, 36-75	24	1666	85/86/87
REC40-xx05DRWB/H	9-18, 18-36, 36-75	±5	±3500	82/83/84
REC40-xx12DRWB/H	9-18, 18-36, 36-75	±12	±1666	85/86/87
REC40-xx15DRWB/H	9-18, 18-36, 36-75	±15	±1320	85/86/87
REC40-xx0512TRWB/H	9-18, 18-36, 36-75	5/±12	5000/±600	85/86/87
REC40-xx0515TRWB/H	9-18, 18-36, 36-75	5/±15	5000/±500	85/86/87

2:1

xx = 9-18Vin = 12

xx = 18-36Vin = 24

xx = 36-75Vin = 48

* add suffix "CTRL" for optional Remote ON/OFF-Control

Specifications (Core Operating Area)

Input Voltage Range	2:1	
Input Filter	π type	
Output Voltage Accuracy	±2% max.	
Line Voltage Regulation	Single & Dual	±0.5% max.
	Triple Output	±1%/±5%
Load Voltage Regulation (10% to 100% full load)	Single Output	±1% max.
	Dual Output	±2% max.
	Triple Output	±3%/±5%
Minimum Load	Single/Dual Output	0%
	Triple Output	10%
Ripple	Single Output	±1% max.
	All Others	<0.2% Vout +20mVp-p max.
Noise	Single Output	100mV min., ±1% max.
	All Others	<0.5% Vout +50mVp-p max.
Trim	±10%	
Operating Frequency	REC40-12xx	200kHz typ.
	REC40-1205	250kHz typ.
	REC40-24xx/48xx	400kHz typ.
Over Power Protection	Works over 120% of rating and recovers automatically	
Over Voltage Protection	Zener diode clamp	
Short Circuit Protection	Hiccup, auto-recovery	
Efficiency at Full Load	see table	

Continued on next page

ECONOLINE


DC/DC-Converter

REC40-S_D_TRWB/H Series

40 Watt

2" x 2"


Single, Dual & Triple Output



Designed to meet EN-60950-1

RECOM

Derating-Graph (Ambient Temperature)




REC40-S_D_TRWB/H Series

Specifications (Core Operating Area)



Remote On/Off	DC-DC ON	open or 3.7V>Vr>5V	
	DC-DC OFF	short to 0V or 0V>Vr>3.7V	
Remote Off input current	Nominal Vin	5mA max.	
Remote pin drive current	Vr=0V	-1.25mA max.	
Isolation Voltage	(tested for 1 second)	1600VDC min.	
Rated Working Voltage	(long term isolation)	see Application Notes	
Isolation Capacitance		1000pF	
Isolation Resistance		100 MΩ min.	
Operating Temperature Range (Natural convection,with derating)		-25°C to +70°C (see Graph)	
Storage Temperature Range		-55°C to +105°C	
Case Temperature		+100°C max.	
Temperature Coefficient		±0.02%/°C	
Relative Humidity		95% RH	
Case Material	Nickel-Plated Copper with Non-Conductive Base, Six-side Shielded		
Cooling Method		Natural convection	
Package Weight		70g	
MTBF (+25°C)	Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F	>550 x 10 ³ hours
(+50°C)		using MIL-HDBK 217F	187 x 10 ³ hours

Noise Measurement



Package Style and Pinning (mm) 2" x 2", Wide Input 2:1

2" x 2" PIN Package



Pin Connections

Pin #	Single	Dual	Triple
1	+Vin	+Vin	+Vin
2	-Vin	-Vin	-Vin
4	No Pin/CTRL	No Pin/CTRL	No Pin/CTRL
5	NC	+Vout	+Vout
6	+Vout	Com	+5Vout
7	-Vout	-Vout	Com
8	Trim	Trim	-Vout

XX.X $\pm$ 0.5 mm
XX.XX $\pm$ 0.25 mm

