Application


- Low-loss SAW component
- Low amplitude ripple
- Sharp rejections at both out-bands
- Usable passband 1.0 MHz



Features

- **RoHS** compatible
- Package size 11.0x4.5x4.1mm^3
- Package Code F11-SMD
- **E**lectrostatic **S**ensitive **D**evice(**ESD)**

Package Dimensions (Unit: mm)



Pin Configuration


Pin No.	Description
1	Input
4	Output
2,3	Case Ground

Marking Description

RF	**R**	Manufacturer
	F	SAW Filter
1011	Part Number	
●	Pin 1	
YYWW	Year Code & Week Code	

*Fig：If the products produced in 06th week of 2015,
The year code & week code is 1506.

Test Circuit（Bottom View）



Performance

Maximum Rating

Item		Value	Unit
DC Voltage	V_{DC}	3	V
Operation Temperature	T	-40 ~ +85	℃
Storage Temperature	T_{stg}	-55 ~ +125	℃
RF Power Dissipation	P	15	dBm


Electronic Characteristics

Test Temperature: 25℃±2℃
Terminating source impedance: 300Ω
Terminating load impedance: 300Ω


Item		Minimum	Typical	Maximum	Unit
Center Frequency	fc		110.00		MHz
Insertion Loss(min)	IL		3.5	3.8	dB
Insertion Loss 109.424-110.576MHz	IL		4.4	5.0	dB
Amplitude Ripple (p-p) 109.424-110.576MHz	△α		0.9	1.2	dB
Group Delay Ripple 109.424-110.576MHz			200.0	500.0	ns
Absolute Attenuation	α				
95.00-104.816MHz		48.0	52.0		dB
104.816-106.544MHz		40.0	45.0		dB
106.544-108.272MHz		35.0	40.0		dB
111.728-113.456MHz		25.0	28.0		dB
113.456-115.184MHz		28.0	32.0		dB
Input VSWR 109.424-110.576MHz			2.0:1	2.2:1	/
Output VSWR 109.424-110.576MHz			2.0:1	2.2:1	/

Frequency Characteristics


Frequency Response




Frequency Response（wideband）




Delay Ripple & S11 VSWR




Phase Linearity & S22 VSWR



S11 Smith Chart




S22 Smith Chart



Reliability（The SAW components shall remain electrical performance after tests）

No.	Test item	Test condition
1	Temperature Storage	(1) Temperature: 85℃±2℃ , Duration: 250h , Recovery time: 2h±0.5h (2) Temperature: –55℃±3℃ , Duration: 250h ,Recovery time: 2h±0.5h
2	Humidity Test	Conditions: 60℃±2℃ , 90~95% RH Duration: 250h
3	Thermal Shock	Heat cycle conditions: TA=-55℃±3℃, TB=85℃±2℃, t1=t2=30min, Switch time: ≤3min, Cycle time: 100 times, Recovery time: 2h±0.5h.
4	Vibration Fatigue	Frequency of vibration: 10~55Hz Amplitude:1.5mm Directions: X,Y and Z Duration: 2h
5	Drop Test	Cycle time: 10 times Height: 1.0m
6	Solder Ability Test	Temperature: 245℃±5℃ Duration: 3.0s--5.0s Depth: DIP--2/3 , SMD--1/5
7	Resistance to Soldering Heat	(1)Thickness of PCB:1mm , Solder condition: 260℃±5℃ , Duration: 10±1s (2)Temperature of Soldering Iron: 350℃±10℃ , Duration: 3~4s , Recovery time : 2 ± 0.5h

Recommended Reflow Soldering Diagram



Reflow cycles:3 cycles max.

Notes

1. As a result of the particularity of inner structure of SAW products, it easy to be breakdown by electrostatic, so we should pay attention to **ESD protect** in the test.
2. **Static voltage** between signal load and ground may cause deterioration and destruction of the component. Please avoid static voltage.
3. **Ultrasonic cleaning** may cause deterioration and destruction of the component. Please avoid ultrasonic cleaning.
4. Only leads of component may **be soldered**. Please avoid soldering another part of component.
5. There is a close relationship between the device's performance and **matching network**. The specifications of this device are based on the test circuit shown above. L and C values may change depending on board layout. Values shown are intended as a guide only.