RFMD
rfmd.com

RF2192

3V 900MHz LINEAR POWER AMPLIFIER

RoHS Compliant & Pb-Free Product
Package Style: QFN, 16-Pin, 4 x 4




Features

- Single 3V Supply
- 29dBm Linear Output Power
- 37% Linear Efficiency
- Low Power Mode
- 45 mA idle current
- 47% Peak Efficiency 31dBm Output

Applications

- 3V CDMA/AMPS Cellular Handsets
- 3V JCDMA Cellular Handsets
- 3V CDMA2000 Cellular Handsets
- 3V TDMA/GAIT Cellular Handsets
- 3V CDMA 450MHz Band Handsets
- Portable Battery-Powered Equipment



Functional Block Diagram

Product Description

The RF2192 is a high-power, high-efficiency linear amplifier IC targeting 3V handheld systems. The device is manufactured on an advanced Gallium Arsenide Heterojunction Bipolar Transistor (HBT) process, and has been designed for use as the final RF amplifier in dual-mode 3V CDMA/AMPS and CDMA2000 handheld digital cellular equipment, spread-spectrum systems, and other applications in the 800MHz to 960MHz band. The RF2192 has a low power mode to extend battery life under low output power conditions. The device is packaged in a 16-pin, 4mmx4mm QFN.

Ordering Information

RF2192	3V 900MHz Linear Power Amplifier
RF2192PCBA-41X	Fully Assembled Evaluation Board

Optimum Technology Matching® Applied

☑ GaAs HBT	☐ SiGe BiCMOS	☐ GaAs pHEMT	☐ GaN HEMT
☐ GaAs MESFET	☐ Si BiCMOS	☐ Si CMOS	☐ RF MEMS
☐ InGaP HBT	☐ SiGe HBT	☐ Si BJT	

RF MICRO DEVICES®, RFMD®, Optimum Technology Matching®, Enabling Wireless Connectivity™, PowerStar®, POLARIS™ TOTAL RADIO™ and UltimateBlue™ are trademarks of RFMD, LLC. BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed for use by RFMD. All other trade names, trademarks and registered trademarks are the property of their respective owners. ©2006, RF Micro Devices, Inc.

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

RFMD
rfmd.com

Absolute Maximum Ratings

Parameter	Rating	Unit
Supply Voltage (RF off)	+8.0	V_{DC}
Supply Voltage ($P_{OUT} \leq 31$dBm)	+5.2	V_{DC}
Mode Voltage (V_{MODE})	+4.2	V_{DC}
Control Voltage (V_{REG})	+3.0	V_{DC}
Input RF Power	+10	dBm
Operating Case Temperature	-30 to +110	°C
Storage Temperature	-40 to +150	°C

Caution! ESD sensitive device.

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional operation of the device under Absolute Maximum Rating conditions is not implied.

RoHS status based on EUDirective2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("RFMD") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of RFMD. RFMD reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.

Parameter	Specification			Unit	Chondition
	Min.	Typ.	Max.		
Usable Frequency Range	400		960	MHz	
High Power State- US-CDMA (V_{MODE} Low)					Case T=25°C, V_{CC}=3.4V, V_{REG}= 2.85V, V_{MODE}=0V to 0.5V, Freq=824MHz to 849MHz (unless otherwise specified)
Frequency Range	824		849	MHz	
Linear Gain	27	30		dB	
Second Harmonic		-33		dBc	
Third Harmonic		<-60		dBc	
Maximum Linear Output Power (CDMA Modulation)	29			dBm	
Total Linear Efficiency		37		%	P_{OUT}=29dBm
Adjacent Channel Power Rejection		-48	-44	dBc	ACPR@885kHz
		-58	-56	dBc	ACPR@1980kHz
Input VSWR		2:1			
Output VSWR			10:1		No damage.
			6:1		No oscillations. >-70dBc
Noise Power		-133		dBm/Hz	At 45MHz offset
Low Power State- US-CDMA (V_{MODE} High)					Case T=25 °C, V_{CC}=3.4V, V_{REG}=2.85V, V_{MODE}=1.8V to 3V, Freq=824MHz to 849MHz (unless otherwise specified)
Frequency Range	824		849	MHz	
Linear Gain	19	22		dB	
Second Harmonic		-33		dBc	
Third Harmonic		<-60		dBc	
Maximum Linear Output Power (CDMA Modulation)	16	20		dBm	
Max I_{CC}		150		mA	P_{OUT}=+16dBm (all currents included)
Adjacent Channel Power Rejection		-48	-46	dBc	ACPR@885kHz
		<-60	-58	dBc	ACPR@1980kHz
Input VSWR		2:1			
Output VSWR			10:1		No damage.
			6:1		No oscillations. >-70dBc



7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

Parameter	Specification			Unit	Condition
	Min.	Typ.	Max.		
High Power State CDMA 2000 1x (V_{MODE} LOW)					Case T=25°C, V_{CC}=3.4V, V_{REG}=2.85V. V_{MODE}=0V to 0.5V, Freq=824MHz to 849MHz (unless otherwise specified)
Frequency Range	824		849	MHz	
Linear Gain		29		dB	
Pilot+DCCH 9600					
Maximum Linear Output Power (CDMA 2000 Modulation)	26.5			dBm	2.5dB Backoff included in IS98D CCDF 1% 5.4dB Peak Average Ratio at CCDF 1%
Adjacent Channel Power Rejection		-47		dBc	ACPR@885kHz
		<-60		dBc	ACPR@1.98MHz
Pilot+FCH 9600+SCHO 9600					
Maximum Linear Output Power (CDMA 2000 Modulation)	29			dBm	4.5dB Peak Average Ratio at CCDF 1%
Adjacent Channel Power Rejection		-47		dBc	ACPR@885kHz
		<-60		dBc	ACPR@1.98MHz
Low Power State CDMA 2000 1x (V_{MODE} HIGH)					Case T=25°C, V_{CC}=3.4V, V_{REG}=2.85V. V_{MODE}=1.8V to 3V, Freq=824MHz to 849MHz
Frequency Range	824		849	MHz	
Linear Gain		22		dB	
Pilot+DCCH 9600					
Maximum Linear Output Power (CDMA 2000 Modulation)	16	20		dBm	5.4dB Peak to Average Ratio at CCDF 1%
Adjacent Channel Power Rejection		-48		dBc	ACPR@885kHz
		<-85		dBc	ACPR@1.98MHz
Efficiency		15		%	P_{OUT}=20dBm
Pilot+FCH 9600+SCHO 9600					
Maximum Linear Output Power (CDMA 2000 Modulation)	16	20		dBm	4.5dB Peak to Average Ratio at CCDF 1%
Adjacent Channel Power Rejection		<-50		dBc	ACPR@885kHz
		<-65		dBc	ACPR@1.98MHz
FM Mode					Case T=25°C, V_{CC}=3.4V, V_{REG}=2.85V, V_{MODE}=0V to 0.5V, Freq=824MHz to 849MHz (unless otherwise specified)
Frequency Range	824		849	MHz	
Gain		30		dB	
Second Harmonic		-33		dBc	
Third Harmonic		<-60		dBc	
Max CW Output Power	31	32		dBm	
Total Efficiency (AMPS mode)		47		%	P_{OUT}=31dBm (room temperature)
Input VSWR		2:1			
Output VSWR			10:1		No damage.
			6:1		No oscillations. >-70dBc


Note: DCCH: Dedicated Control Channel
FCH: Fundamental Channel
CCDF: Complementary Cumulative Distribution Function

Parameter	Specification			Unit	Condition
	Min.	Typ.	Max.		
High Power State-CDMA450 (V_{MODE} Low)					Case T=25°C, V_{CC}=3.4V, V_{REG}=2.85V, V_{MODE}=0V to 0.5V, Freq=452MHz to 458MHz (unless otherwise specified)
Frequency Range	452		458	MHz	
Linear Gain		31		dB	
Second Harmonic		30		dBc	
Third Harmonic		-60		dBc	
Maximum Linear Output Power (CDMA Modulation)	29			dBm	
Total Linear Efficiency		35		%	P_{OUT}=29dBm
Adjacent Channel Power Rejection		-49		dBc	ACPR @ 885kHz
		-56		dBc	ACPR @ 1980kHz
Input VSWR		2:1			
Output VSWR			10:1		No damage.
			6:1		No oscillations. > -70dBc
Low Power State-CDMA450 (V_{MODE} High)					Case T=25°C, V_{CC}=3.4V, V_{REG}=2.85V, V_{MODE}=2.85V, Freq=452MHz to 458MHz (unless otherwise specified)
Frequency Range	452		458	MHz	
Linear Gain		23		dB	
Maximum Linear Output Power (CDMA Modulation)	16			dBm	
Max I_{CC}		160		mA	P_{OUT}=+16dBm (all currents included)
Adjacent Channel Power Rejection		-52		dBc	ACPR @ 885kHz
		-70		dBc	ACPR @ 1980kHz
Input VSWR		2:1			
Output VSWR			10:1		No damage.
			6:1		No oscillations. > -70dBc
DC Supply					
Supply Voltage	3.0	3.4	4.2	V	The maximum power out for V_{CC}=3.0V is 28dBm.
Quiescent Current		160		mA	V_{MODE}=Low
		45	70	mA	V_{MODE}=High
V_{REG} Current			10	mA	
V_{MODE} Current			1	mA	
Turn On/Off Time			<40	µs	Time between V_{REG} turned on and PA reaching full power. Turn on/off time can be reduced by lowering the bypass capacitor value on the V_{REG} line.
Total Current (Power Down)			10	µA	V_{REG}=Low
V_{REG} "Low" Voltage	0		0.5	V	
V_{REG} "High" Voltage	2.75	2.85	2.95	V	
V_{MODE} "Low" Voltage	0		0.5	V	
V_{MODE} "High" Voltage	1.8	2.85	3.0	V	

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

Pin	Function	Description	Interface Schematic
1	GND	Ground connection.	
2	GND	Ground connection.	
3	GND	Ground connection.	
4	RF IN	RF input. An external 100pF series capacitor is required as a DC block. In addition, shunt inductor and series capacitor are required to provide 2:1VSWR.	
5	VREG1	Power Down control for first stage. Regulated voltage supply for amplifier bias. In Power Down mode, both V_{REG} and V_{MODE} need to be LOW (<0.5V).	
6	VMODE	For nominal operation (High Power Mode), V_{MODE} is set LOW. When set HIGH, the driver and final stage are dynamically scaled to reduce the device size and as a result to reduce the idle current.	
7	VREG2	Power Down control for the second stage. Regulated voltage supply for amplifier bias. In Power Down mode, both V_{REG} and V_{MODE} need to be LOW (<0.5V).	
8	BIAS GND	Bias circuitry ground. See application schematic.	
9	GND	Ground connection.	
10	RF OUT	RF output and power supply for final stage. This is the unmatched collector output of the second stage. A DC block is required following the matching components. The biasing may be provided via a parallel L-C set for resonance at the operating frequency of 824MHz to 849MHz. It is important to select an inductor with very low DC resistance with a 1A current rating. Alternatively, shunt microstrip techniques are also applicable and provide very low DC resistance. Low frequency bypassing is required for stability.	
11	RF OUT	Same as pin 10.	See pin 10.
12	RF OUT	Same as pin 10.	
13	2FO	Harmonic trap. This pin connects to the RF output but is used for providing a low impedance to the second harmonic of the operating frequency. An inductor or transmission line resonating with an on chip capacitor at 2fo is required at this pin.	
14	VCC BIAS	Power supply for bias circuitry. A 100pF high frequency bypass capacitor is recommended.	
15	VCC1	Power supply for first stage.	
16	VCC1	Same as Pin 15.	
Pkg Base	GND	Ground connection. The backside of the package should be soldered to a top side ground pad which is connected to the ground plane with multiple vias. The pad should have a short thermal path to the ground plane.	

Package Drawing




Dimensions in mm.
Shaded pin is lead 1.

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

Evaluation Board Schematic

US-CDMA




* L1 is a High Q inductor (i.e., Coilcraft 0805HQ-series).
**C1 and C14 are High Q capacitors
(i.e., Johanson C-series).

Board	C30 (pF)	C1 (pF)	L1 (nH)	C14 (pF)
CDMA (US)	100	9.1	20	9.1

Transmission Line Length	TL_1	TL_2	TL_3	TL_5
CDMA (US)	15 mils	350 mils	105 mils	85 mils

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

Application Schematic
CDMA-450MHz Band



* L1 is a High Q inductor (i.e., Coilcraft 0805HQ-series).
**C1, C100, C14, and C140 are High Q capacitors (i.e., Johanson C-series).


Board	C100 (pF)	C140 (pF)	C1 (pF)	L1 (nH)	C14 (pF)
CDMA (450 MHz)	15	13	15	20	13

Transmission Line Length	TL_1	TL_2	TL_6	TL_4	TL_5
	15 mils	125 mils	220 mils	L=40 mils	L=75 mils

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

Evaluation Board Layout - US-CDMA
2.0” x 2.0”

Board Thickness 0.031”, Board Material FR-4, Multi-Layer, Ground Plane at 0.015”



7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

PCB Design Requirements

PCB Surface Finish

The PCB surface finish used for RFMD's qualification process is electroless nickel, immersion gold. Typical thickness is 3μinch to 8μinch gold over 180μinch nickel.

PCB Land Pattern Recommendation

PCB land patterns are based on IPC-SM-782 standards when possible. The pad pattern shown has been developed and tested for optimized assembly at RFMD; however, it may require some modifications to address company specific assembly processes. The PCB land pattern has been developed to accommodate lead and package tolerances.

PCB Metal Land Pattern




Figure 1. PCB Metal Land Pattern (Top View)

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.

PCB Solder Mask Pattern

Liquid Photo-Imageable (LPI) solder mask is recommended. The solder mask footprint will match what is shown for the PCB Metal Land Pattern with a 3mil expansion to accommodate solder mask registration clearance around all pads. The center-grounding pad shall also have a solder mask clearance. Expansion of the pads to create solder mask clearance can be provided in the master data or requested from the PCB fabrication supplier.




Figure 2. PCB Solder Mask (Top View)

Thermal Pad and Via Design

The PCB metal land pattern has been designed with a thermal pad that matches the exposed die paddle size on the bottom of the device.

Thermal vias are required in the PCB layout to effectively conduct heat away from the package. The via pattern has been designed to address thermal, power dissipation and electrical requirements of the device as well as accommodating routing strategies.

The via pattern used for the RFMD qualification is based on thru-hole vias with 0.203mm to 0.330mm finished hole size on a 0.5mm to 1.2mm grid pattern with 0.025mm plating on via walls. If micro vias are used in a design, it is suggested that the quantity of vias be increased by a 4:1 ratio to achieve similar results.

7628 Thorndike Road, Greensboro, NC 27409-9421 · For sales or technical support, contact RFMD at (+1) 336-678-5570 or sales-support@rfmd.com.