SMAF Plastic-Encapsulate Diodes

Fast Recovery Rectifier

Features

- I_O 1A
- VRRM 50V-1000V
- High surge current capability
- Glass passivated chip
- Polarity: Color band denotes cathode


Applications

- Rectifier

Marking

- RS1AF-RS1MF ： RS1A-RS1M

SMAF



Limiting Values (Absolute Maximum Rating)

Item	Symbo	nit	Conditions	RS1						
				AF	BF	DF	GF	JF	KF	MF
Repetitive Peak Reverse Voltage	V_{RRM}	V		50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V		35	70	140	280	420	560	700
Average Forward Current	$I_{F(AV)}$	A	0Hz Half-sine wave, Resistance oad, Ta=90℃	1						
Surge(Non-repetitive)Forward Current	I_{FSM}	A	60Hz Half-sine wave,1 cycle, a=25℃	30						
Junction Temperature	T_J	℃		-55 ~ +150						
Storage Temperature	T_{STG}	℃		-55 ~ +150						

Downloaded from alldatasheet.com

Electrical Characteristics (T_a 25℃ Unless otherwise specified）

Item	Symbol	Unit	Test Condition		RS1						
					AF	BF	DF	GF	JF	KF	MF
Peak Forward Voltage	V_{FM}	V	I_{FM}=1.0A		1.3						
Peak Reverse Current	I_{RRM1}	μA	$V_{RM}=V_{RRM}$	T_a=25℃	5						
	I_{RRM2}			T_a=125℃	50						
Reverse Recovery time	t_{rr}	ns	I_F=0.5A I_R=1A I_{RR}=0.25A		150				250	500	
Thermal Resistance(Typical)	$R_{\theta J-A}$	℃/W	Between junction and ambient		105[1)]						
	$R_{\theta J-L}$		Between junction and terminal		32[1)]						

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT





FIG.3: TYPICAL FORWARD CHARACTERISTICS



Downloaded from alldatasheet.com

FIG.4：TYPICAL REVERSE CHARACTERISTICS






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




SMAF Package Outline Dimensions



Dimensions in inches and (millimeters)

Downloaded from alldatasheet.com

SMAF Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

JSHD reserve the right to make modifications,enhancements, improvements, corrections or other changes without further notice to any product herein .JSHD does not assume any liability arising out of the application or use of any product described herein.




FIG:CONFIGURATION OF AXIAL TAPING

Downloaded from alldatasheet.com

ITEM	SYMBOL	SMAF mm(inch)
Carrier width	A	2.83+0.1(0.112+0.004)
Carrier length	B	4.90+0.1(0.193+0.004)
Carrier depth	C	1.45+0.1(0.057+0.004)
Sprocket hole	d	1.55+0.05(0.061+0.002)
Reel outside diameter	D	280/178+2.0(11/7.0+0.079)
Reel inner diameter	D1	8.0+0.2(0.315+0.008)
Feed hole diameter	D2	13+0.5(0.512+0.020)
Stroket hole position	E	1.75+0.1(0.069+0.004)
Punch hole position	F	5.5+0.05(0.217+0.002)
Punch hole pitch	P	4.0+0.1(0.157+0.004)
Sprocket hole pitch	P0	4.0+0.1(0.157+0.004)
Embossment center	P1	2.0+0.1(0.079+0.004)
Totall tape thickness	T	0.23-0.29(0.009-0.011)
Tape width	W	12.0+0.1(0.472+0.004)
Reel width	W1	16.8+2.0(0.661+0.079)

NOTE:Devices are packde in accordance with EIA standard RS-481-A and specification given above.