
RV1490D VCXO

`Tiger' SMD Voltage Control Crystal Oscillator Series



High Performance Discrete Voltage Control Crystal Oscillator.

Product description

This discrete VCXO offers ultra low RMS phase jitter and phase noise, high linearity pull range and high frequency stability in an industry standard 14 mm x 9 mm SMD package.

Applications

- Basestation
- Communications
- Ethernet
- DSL/ADSL
- Other
- SONET/SDH
- WiMAX/WLAN

Features

- Low Jitter
- LVPECL output

Specifications

New

1.0 SPECIFICATION REFERENCES

Line	Parameter	Description
1.1	Model Series	RV1490D VCXO
1.2	RoHS Compliant	Yes
1.3	Custom P#	
1.4	Package Type	P6, P4, M6 or M4 - select only one

2.0 FREQUENCY CHARACTERISTIC

Line	Parameter	Test Condition	Value	Unit
2.1	Frequency Range		10 to 125	MHz
2.2	Operating Temperature Range	(Note 1)	-40 to 85	°C
2.3	Frequency Stability	Including temperature range, Supply variation, Load variation and 15 years Aging	±15 to 50	ppm

3.0 POWER SUPPLY

Line	Parameter	Test Condition	Value	Unit
3.1	Supply Voltage	With a tolerance of ±10%	2.97 to 5.5	V
3.2	Supply Current	(Note 2)	10 to 120	mA

4.0 CONTROL VOLTAGE (VCO)

Line	Parameter	Test Condition	Value	Unit
4.1	Absolute Pulling Range		±	ppm
4.2	Pulling Range	Frequency shift from minimum to maximum control voltage (Note 3)	±40 to 250	ppm
4.3	Control Voltage	Vcc ÷ 2	0 to 3.3	V
4.4	Linearity		10 max	%
4.5	Slope	Positive only	±10 to 100	ppm/V
4.6	Modulation BW		0.3 to 100	kHz
4.7	Input Impedance		10 to 2000	kΩ

5.0 OUTPUT CHARACTERISTICS - PECL/LVPECL ONLY

Line	Parameter	Test Condition	Value	Unit
5.1	Output	PECL/LVPECL		
5.2	Duty Cycle	@ VCC -1.3V	40 to 60	%
5.3	Output Load	With VCC -2V @ 50Ω		
5.4	Rise time /fall time	80%/20% (Note 4)	0.5 to 3	ns
5.5	Logic `1' on Pad 2	Tristate GND (Note 5)		
5.6	Logic `0' on Pad 2	Enable (VCC or open) (Note 5)		
5.7	RMS Phase Jitter	Integrated 12 kHz to 20 MHz. Typical @ 77.76 MHz (Note 6)	0.5 max	ps
5.8	RMS Period Jitter	Typical @ 77.76 MHz (Note 6)	3 max	ps
5.9	Sub-harmonics		-30 max	dBc

6.0 OUTPUT CHARACTERISTICS - CMOS/LVCMOS ONLY

Line	Parameter	Test Condition	Value	Unit
6.1	Output	CMOS/LVCMOS		
6.2	Duty Cycle	@ 50% VCC	40 to 60	%
6.3	Output Load		15 to 50	pF
6.4	Rise time / fall time	90%/10% (Note 4)	0.5 to 3	ns
6.5	Logic `0' on Pad 2	Tristate GND (Note 4)		
6.6	Logic `1' on Pad 2	Enable (VCC or open) (Note 5)		
6.7	RMS Phase Jitter	Integrated 12 kHz to 20 MHz. Typical @ 77.76 MHz (Note 6)	0.5 max	ps
6.8	RMS Period Jitter	Typical @ 77.76 MHz (Note 6)	3 max	ps
6.9	Sub-harmonics		-30 max	dBc

7.0 OUTPUT CHARACTERISTICS - LVDS ONLY UPTO 3.3V

Line	Parameter	Test Condition	Value	Unit
7.1	Output	LVDS		
7.2	Duty Cycle	Measured at 1.25 V	40 to 60	%
7.3	Output Load	RL - 100 Ω / CL = 10 pF		
7.4	Rise time / fall time	RL - 100 Ω / CL = 10 pF (Note 4)	0.5 to 3	ns
7.5	Logic `0' on Pad 2	Tristate GND (Note 5)		
7.6	Logic `1' on Pad 2	Enable (VCC or open) (Note 5)		
7.7	RMS Phase Jitter	Integrated 12 kHz to 20 MHz. Typical @ 77.76 MHz (Note 6)	0.5 max	ps
7.8	RMS Period Jitter	Typical @ 77.76 MHz (Note 6)	3 max	ps
7.9	Sub-harmonics		-40 max	dBc

8.0 SSB PHASE NOISE

Line	Parameter	Test Condition	Value	Unit
8.1	SSB Phase Noise power density @ 10 Hz offset	Value for a 24.576 MHz VCXO @ 25°C	-78	dBc/Hz
8.2	SSB Phase Noise power density @ 100 Hz offset	Value for a 24.576 MHz VCXO @ 25°C	-102	dBc/Hz
8.3	SSB Phase Noise power density @ 1 kHz offset	Value for a 24.576 MHz VCXO @ 25°C	-128	dBc/Hz
8.4	SSB Phase Noise power density @ 10 kHz offset	Value for a 24.576 MHz VCXO @ 25°C	-150	dBc/Hz
8.5	SSB Phase Noise power density @ 100 kHz offset	Value for a 24.576 MHz VCXO @ 25°C	-155	dBc/Hz

New

9.0 SSB PHASE NOISE

Line	Parameter	Test Condition	Value	Unit
9.1	SSB Phase Noise power density @ 10 Hz offset	Value for a 77.76 MHz VCXO @ 25°C	-75	dBc/Hz
9.2	SSB Phase Noise power density @ 100 Hz offset	Value for a 77.76 MHz VCXO @ 25°C	-100	dBc/Hz
9.3	SSB Phase Noise power density @ 1 kHz offset	Value for a 77.76 MHz VCXO @ 25°C	-125	dBc/Hz
9.4	SSB Phase Noise power density @ 10 kHz offset	Value for a 77.76 MHz VCXO @ 25°C	-150	dBc/Hz
9.5	SSB Phase Noise power density @ 100 kHz offset	Value for a 77.76 MHz VCXO @ 25°C	-155	dBc/Hz

10.0 ENVIRONMENTAL SPECIFICATION

Line	Parameter	Description
10.1	SMD	Product suitable for Pb-free convection reflow soldering, compliant with JEDEC standard. J-STD-020, Level 1.
10.2	Storage Temperature Range	-55 to 125°C
10.3	Sealing	Non-hermatic package
10.4	Shock	981ms-²(100gn) acceleration for 6ms duration,3 shocks in each direction along 3 mutually perpendicular axis. IEC 60068-2-27 Test Ea.
10.5	Vibration	10-60Hz 0.75mm displacements, 60-500Hz 98.1ms-² (10gn) acceleration. 30 minutes in each of three mutually perpendicular planes at 1 octave per minute. IEC 60068-2-6 Test Fc Procedure B4
10.6	Marking	Resistant to all common solvents
10.7	RoHS	Parts are fully compliant with the European Union Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment. Note: The RoHS compliant parts are suitable for assembly using both Lead-free solders and Tin/Lead solders.

New

11.0 MANUFACTURING INFORMATION


Line	Parameter	Description
11.1	Packaging Description	Tape and Reel as shown
11.2	Reflow	Solder reflow process as per attached profile

12.0 SPECIFICATION NOTES

Line	Parameter	Description
12.1	Note 1	The operating temperature range needs to be specified.
12.2	Note 2	Output current depends on the frequency selected and the output characteristic chosen
12.3	Note 3	Select the exact tuning range required. The values listed are maximum normally available and may require some trade-off in frequency stability. Standard options are ±50ppm, ± 75ppm, ±100ppm and ±150ppm.
12.4	Note 4	The exact value will be frequency dependant
12.5	Note 5	Enable high or low is available as an option
12.6	Note 6	The jitter values will vary depending on the frequency selected

Drawing Name: RS/RV1490 Plastic Model Drawing

MODEL OUTLINE (P6 & P4)




TOP VIEW


PIN CONNECTIONS

P6		
PIN	VCXO & XO (LVPECL/LVDS)	VCXO (LV/HCMOS/Sinewave)
1	VCO (VCXO only) E/D or NC (XO only)	VCO
2	E/D or NC	E/D or NC
3	GND	GND
4	OUTPUT	OUTPUT
5	$\overline{\text{OUTPUT}}$	NC
6	VCC	VCC


P4	
PIN	VCXO & XO (LV/HCMOS/Sinewave)
1	VCO (VCXO only) E/D or NC (XO only)
2	GND
3	OUTPUT
4	VCC




SIDE VIEW (6 PAD)



SIDE VIEW (4 PAD)




BOTTOM VIEW (6 PAD)




BOTTOM VIEW (4 PAD)

RECOMMENDED PAD LAYOUT - P6



RECOMMENDED PAD LAYOUT - P4




New

TITLE: RV/RS1490 PLASTIC MODEL DRAWING	FILENAME: CAT519	Tolerance:	
RELATED DRAWINGS:	REVISION: B	XX	=
	DATE: 12-Sep-11	X.X	=±0.2
	SCALE: 2 : 1	X.XX	=±0.10
	Millimetres	X.XXX	=±0.05
		X°	=
		Hole	=

©2009 Rakon Limited

Drawing Name: RS/RV1490 Metal Model Drawing

MODEL OUTLINE (M6 & M4)




TOP VIEW


PIN CONNECTIONS

M6		
PIN	VCXO & XO (LVPECL/LVDS)	VCXO (LV/HCMOS)
1	VCO (VCXO only) E/D or NC (XO only)	VCO
2	E/D or NC	E/D or NC
3	GND	GND
4	OUTPUT	OUTPUT
5	$\overline{\text{OUTPUT}}$	NC
6	VCC	VCC


M4	
PIN	VCXO & XO (LV/HCMOS)
1	VCO (VCXO only) E/D or NC (XO only)
2	GND
3	OUTPUT
4	VCC




SIDE VIEW (6 PAD)



SIDE VIEW (4 PAD)




BOTTOM VIEW (6 PAD)




BOTTOM VIEW (4 PAD)

RECOMMENDED PAD LAYOUT - M6



RECOMMENDED PAD LAYOUT -M4



New

TITLE: RV/RS1490 METAL MODEL DRAWING

RELATED DRAWINGS:

FILENAME: CAT525

REVISION: A

DATE: 16-Sep-09

SCALE: 2 : 1


Millimetres [inch]

Tolerance:
XX =±0.5
X.X =±0.2
X.XX =±0.10
X.XXX =±0.05
X° =±1.0°
Hole =±0.10


©2009 Rakon Limited

Drawing Name: RS/RV 1490 Series Marking

GENERAL MARKING



MARKING EXAMPLE




TITLE: RS/RV 1490 SERIES MARKING	FILENAME: CAT524
RELATED DRAWINGS:	REVISION: A
	DATE: 16-Sep-09
	SCALE: NTS
	Millimetres

©2009 Rakon Limited


Drawing Name: RS/RV1490 Series Test Circuit

HCMOS TEST CIRCUIT :




C_1 = 10nF
C_L = 15pF (Inclusive of jigging and equipment capacitance)

LVPECL TEST CIRCUIT :



$C_1 = C_2$ = 10nF
$R_1 = R_2$ = 50Ω

LVDS TEST CIRCUIT :




C_1 = 10nF
R_1 = 100Ω

TITLE: RV/RS1490 SERIES TEST CIRCUIT	FILENAME: CAT521
RELATED DRAWINGS:	REVISION: A
	DATE: 16-Sep-09
	SCALE: NTS
	Millimetres [inch]


©2009 Rakon Limited

Drawing Name: RS/RV1490 Series Tape & Reel

TAPE DETAIL (SCALE 2 : 1)



REEL DETAIL (SCALE 1 : 5)




NOTE: Ø330mm REEL'S STANDARD PACKING QUANTITY IS 500 OSCILLATORS PER REEL.

TITLE: RV/RS1490 SERIES TAPE & REEL	FILENAME: CAT522	Tolerance:
RELATED DRAWINGS:	REVISION: A	XX =±0.5
	DATE: 16-Sep-09	X.X =±0.2
	SCALE: See above	X.XX =±0.10
	Millimetres [inch]	X.XXX =±0.05
		X° =±1.0°
		Hole =±0.10

©2009 Rakon Limited

Drawing Name: RF-CAT523



NOTE:
The product has been tested to withstand the Reflow Profile shown. The Reflow Profile used to solder Rakon VCXO/XO is determined by the solder paste manufacturer's specification. It is recommended that the Reflow Profile used does not exceed the one shown above.

TITLE: RV/RS1490 SERIES Pb-FREE REFLOW	FILENAME: CAT523
RELATED DRAWINGS:	REVISION: A
	DATE: 16-Sep-09
	SCALE: NTS
	Millimetres [inch]

©2009 Rakon Limited

Specification History

Current Version : 1.01

Version	User	Change	Note	Date