
AC-DC Power Supplies

RWS300B-24/DIN

Sales Region	Worldwide
Series	RWS-B
Status	Production
Feature	DIN rail installation compatible
Option	DIN rail mountable
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	88% Typ.
Rated Output Voltage[DC]	24V
Output Voltage Range[DC]	21.6 to 27.6V
Maximum Output Current	12.5A
Maximum Output Power	300W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	50mm Nom.
Height(H)	114.8mm Nom.
Depth(D)	221.8mm Nom.
Weight	1100g Typ.

Other	
Operating Temp. Range	-20 to 70°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 CSA C22.2 No.107.1-01 EN60950-1 UL508
Safety Standard(Conformed)	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.