



Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311

Phone: (818) 701-4933  
Fax: (818) 701-4939

## S2A THRU S2M

## 2 Amp Silicon Rectifier 50 to 1000 Volts

### Features

- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- For Surface Mount Applications
- Low Thermal Resistance
- Easy Pick And Place
- High Temp Soldering: 260°C for 10 Seconds At Terminals
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

### Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 16°C/W Junction To Lead

| MCC Catalog Number | Device Marking | Maximum Recurrent Peak Reverse Voltage | Maximum RMS Voltage | Maximum DC Blocking Voltage |
|--------------------|----------------|----------------------------------------|---------------------|-----------------------------|
| S2A                | S2A            | 50V                                    | 35V                 | 50V                         |
| S2B                | S2B            | 100V                                   | 70V                 | 100V                        |
| S2D                | S2D            | 200V                                   | 140V                | 200V                        |
| S2G                | S2G            | 400V                                   | 280V                | 400V                        |
| S2J                | S2J            | 600V                                   | 420V                | 600V                        |
| S2K                | S2K            | 800V                                   | 560V                | 800V                        |
| S2M                | S2M            | 1000V                                  | 700V                | 1000V                       |


### Electrical Characteristics @ 25°C Unless Otherwise Specified

|                                                         |             |              |                                                               |
|---------------------------------------------------------|-------------|--------------|---------------------------------------------------------------|
| Average Forward current                                 | $I_{F(AV)}$ | 2.0A         | $T_J = 75^\circ\text{C}$                                      |
| Peak Forward Surge Current                              | $I_{FSM}$   | 50A          | 8.3ms, half sine, $T_J = 150^\circ\text{C}$                   |
| Maximum Instantaneous Forward Voltage                   | $V_F$       | 1.15V        | $I_{FM} = 2.0\text{A}; T_J = 25^\circ\text{C}^*$              |
| Maximum DC Reverse Current At Rated DC Blocking Voltage | $I_R$       | 10μA<br>50μA | $T_J = 25^\circ\text{C}$<br>$T_J = 125^\circ\text{C}$         |
| Maximum Reverse Recovery Time                           | $T_{rr}$    | 2.0μs        | $I_F = 0.5\text{A}, I_R = 1.0\text{A}, I_{rr} = 0.25\text{A}$ |
| Typical Junction Capacitance                            | $C_J$       | 30pF         | Measured at 1.0MHz, $V_R = 4.0\text{V}$                       |

\*Pulse test: Pulse width 300 μsec, Duty cycle 2%


Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

### DO-214AA (HSMB) (Round Lead)




| DIM | INCHES |      | MM   |      | NOTE |
|-----|--------|------|------|------|------|
|     | MIN    | MAX  | MIN  | MAX  |      |
| A   | .078   | .116 | 1.98 | 2.95 |      |
| B   | .075   | .089 | 1.90 | 2.25 |      |
| C   | .002   | .008 | .05  | .20  |      |
| D   | ----   | .02  | ---- | .51  |      |
| E   | .035   | .055 | .90  | 1.40 |      |
| F   | .065   | .091 | 1.65 | 2.32 |      |
| G   | .205   | .224 | 5.21 | 5.69 |      |
| H   | .160   | .180 | 4.06 | 4.57 |      |
| J   | .130   | .155 | 3.30 | 3.94 |      |

### SUGGESTED SOLDER PAD LAYOUT




# S2A thru S2M

Figure 1  
Typical Forward Characteristics




Instantaneous Forward Current - Amperes *versus*  
Instantaneous Forward Voltage - Volts

Figure 2  
Forward Derating Curve




Average Forward Rectified Current - Amperes *versus*  
Ambient Temperature - °C

Figure 3  
Junction Capacitance




Junction Capacitance - pF *versus*  
Reverse Junction Potential (Applied V + 0.7 Volts) - Volts

## S2A thru S2M



Peak Forward Surge Current - Amperes *versus*  
Number Of Cycles At 60Hz - Cycles



Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel |

\*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

\*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

\*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.