S9013

NPN Silicon Epitaxial Planar Transistor


FEATURES

High Collector Current.(I_C= 500mA).

Complementary To S9012.

Excellent H_{FE} Linearity.

Power dissipation.(P_C=300mW).



SOT-23

APPLICATIONS

High Collector Current.

MAXIMUM RATING at Ta=25℃ unless otherwise specified

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	25	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current -Continuous	500	mA
P_C	Collector Dissipation	300	mW
T_j,T_{stg}	Junction and Storage Temperature	-55 to +150	℃

JSMICRO Semiconductor

ELECTRICAL CHARACTERISTICS at Ta=25℃ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=100μA,I_E=0	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=0.1mA,I_B=0	25			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=100μA,I_C=0	5			V
Collector cut-off current	I_{CBO}	V_{CB}=40V,I_E=0			0.1	μA
Collector cut-off current	I_{CEO}	V_{CE}=20V,I_B=0			0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V,I_C=0			0.1	μA
DC current gain	h_{FE}	V_{CE}=1V,I_C=50mA	120		400	
		V_{CE}=1V,I_C=500mA	40			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=500mA, I_B= 50mA			0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=500mA, I_B= 50mA			1.2	V
Transition frequency	f_T	V_{CE}=6V, I_C= 20mA f=30MHz	150			MHz

CLASSIFICATION OF $h_{FE(1)}$

Rank	L	H	J
Range	120-200	200-350	300-400

JSMICRO Semiconductor

TYPICAL CHARACTERISTICS at Ta=25℃ unless otherwise specified




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Base-Emitter Saturation Voltage Collector-Emitter Saturation Voltage





Figure 4. Current Gain Bandwidth Product

JSMICRO Semiconductor


PACKAGE OUTLINE

Plastic surface mounted package SOT-23



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60
All Dimensions in mm		

SOLDERING FOOTPRINT



Unit : mm

PACKAGE INFORMATION

Device	Package	Shipping
S9013	SOT-23	3000/Tape&Reel

JSMICRO Semiconductor