Ordering number : ENA8375B

SB1003M3

Schottky Barrier Diode
30V, 1A, Low IR, Single MCPH3

ON Semiconductor®
http://onsemi.com

Applications
- High frequency rectification (switching regulators, converters, choppers)

Features
- Low switching noise
- Low leakage current and high reliability due to highly reliable planar structure
- Ultrasmall package permitting applied sets to be small and slim (Mounting height 0.85mm)
- Halogen free compliance


Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Repetitive Peak Reverse Voltage	V_{RRM}		30	V
Nonrepetitive Peak Reverse Surge Voltage	V_{RSM}		35	V
Average Output Current	I_O		1.0	A
Surge Forward Current	I_{FSM}	50Hz sine wave, 1 cycle	10	A
Junction Temperature	Tj		−55 to +125	°C
Storage Temperature	Tstg		−55 to +125	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Package Dimensions
unit : mm (typ)
7019A-001



Product & Package Information
- Package : MCPH3
- JEITA, JEDEC : SC-70, SOT-323
- Minimum Packing Quantity : 3,000 pcs./reel


Packing Type : TL



Marking



Electrical Connection




ORDERING INFORMATION
See detailed ordering and shipping information on page 2 of this data sheet.

Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Reverse Voltage	V_R	I_R=0.5mA	30			V
Forward Voltage	V_F1	I_F=0.7A		0.45	0.50	V
	V_F2	I_F=1.0A		0.48	0.53	V
Reverse Current	I_R	V_R=16V			15	μA
Interterminal Capacitance	C	V_R=10V, f=1MHz		27		pF
Reverse Recovery Time	t_{rr}	I_F=I_R=100mA, See specified Test Circuit.			10	ns
Thermal Resistance	Rth(j-a)1	When mounted in Cu-foiled area of 0.72mm^2×0.03mm on glass epoxy substrate		94.7		°C / W
	Rth(j-a)2	When mounted on ceramic substrate (500mm^2×0.8mm)		67.7		°C / W


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


t_{rr} Test Circuit





Ordering Information


Device	Package	Shipping	memo
SB1003M3-TL-E	MCPH3	3,000pcs./reel	Pb-Free
SB1003M3-TL-W	MCPH3	3,000pcs./reel	Pb-Free and Halogen Free


IF – VF
Forward Current, IF – A
Forward Voltage, VF – V
Ta=125°C
100°C
75°C
50°C
25°C
0°C
–25°C
IT09553


IR – VR
Reverse Current, IR – µA
Reverse Voltage, VR – V
Ta=125°C
100°C
75°C
50°C
25°C
0°C
–25°C
IT09554



PF(AV) – IO
Average Forward Power Dissipation, PF(AV) – W
Average Output Current, IO – A
Rectangular wave
θ
360°
Sine wave
180°
360°
(1)
(2)(4)(3)
(1)Rectangular wave θ=60°
(2)Rectangular wave θ=120°
(3)Rectangular wave θ=180°
(4)Sine wave θ=180°
IT09555


C – VR
Interterminal Capacitance, C – pF
Reverse Voltage, VR – V
IT09556



IFSM – t
Surge Forward Current, IFSM(Peak) – A
Current waveform 50Hz sine wave
IS
20ms
t
Time, t – s
ID00435

Outline Drawing

SB1003M3-TL-E, SB1003M3-TL-W



Land Pattern Example



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.