




## Product Description

Sirenza Microdevices' SBB-2089Z is a high performance InGaP HBT MMIC amplifier utilizing a Darlington configuration with an active bias network. The active bias network provides stable current over temperature and process Beta variations. Designed to run directly from a 5V supply, the SBB-2089Z does not require a dropping resistor as compared to typical Darlington amplifiers. The SBB-2089Z product is designed for high linearity 5V gain block applications that require small size and minimal external components. It is internally matched to 50 ohms.


The matte tin finish on Sirenza's lead-free package utilizes a post annealing process to mitigate tin whisker formation and is RoHS compliant per EU Directive 2002/95. This package is also manufactured with green molding compounds that contain no antimony trioxide nor halogenated fire retardants.

Gain & Return Loss vs. Frequency (w/ App. Ckt.)



## SBB-2089Z

50 - 850 MHz, Cascadable Active Bias  
InGaP HBT MMIC Amplifier



## Product Features

- OIP3 = 42.8 dBm @ 240MHz
- P1dB = 20.8 dBm @ 500MHz
- Single Fixed 5V Supply
- Robust 1000V ESD, Class 1C
- Patented Thermal Design & Bias Circuit
- Low Thermal Resistance
- MSL 1 moisture rating

## Applications

- Receiver IF Amplifier
- Cellular, PCS, GSM, UMTS
- Wireless Data, Satellite Terminals


| Symbol                                                                                                                                                                                                                      | Parameters                                                          | Units | Frequency                    | Min.             | Typ.           | Max.             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|-------|------------------------------|------------------|----------------|------------------|
| S <sub>21</sub>                                                                                                                                                                                                             | Small Signal Gain                                                   | dB    | 70 MHz<br>240 MHz<br>400 MHz | <br>18.5<br>18.5 | 20<br>20<br>20 | <br>21.5<br>21.5 |
| P <sub>1dB</sub>                                                                                                                                                                                                            | Output Power at 1dB Compression                                     | dBm   | 70 MHz<br>240 MHz<br>400 MHz | <br><br>18.5     | 20<br>20<br>21 |                  |
| IP <sub>3</sub>                                                                                                                                                                                                             | Third Order Intercept Point                                         | dBm   | 70 MHz<br>240 MHz<br>400 MHz | <br><br>39       | 41<br>43<br>41 |                  |
| Bandwidth                                                                                                                                                                                                                   | S <sub>11</sub> , S <sub>22</sub> : Minimum 10dB Return Loss (typ.) | MHz   |                              |                  | 50 - 850       |                  |
| IRL                                                                                                                                                                                                                         | Input Return Loss                                                   | dB    | 70 -500MHz                   | 15               | 20             |                  |
| ORL                                                                                                                                                                                                                         | Output Return Loss                                                  | dB    | 70 -500MHz                   | 11               | 14             |                  |
| S <sub>12</sub>                                                                                                                                                                                                             | Reverse Isolation                                                   | dB    | 70 -500MHz                   |                  | 22             |                  |
| NF                                                                                                                                                                                                                          | Noise Figure                                                        | dB    | 500 MHz                      |                  | 2.7            | 3.7              |
| V <sub>D</sub>                                                                                                                                                                                                              | Device Operating Voltage                                            | V     |                              |                  | 5              | 5.3              |
| I <sub>D</sub>                                                                                                                                                                                                              | Device Operating Current                                            | mA    |                              | 82               | 90             | 98               |
| R <sub>TH</sub> , j-l                                                                                                                                                                                                       | Thermal Resistance (junction - lead)                                | °C/W  |                              |                  | 48.8           |                  |
| <b>Test Conditions:</b> V <sub>D</sub> = 5V I <sub>D</sub> = 90mA Typ. OIP <sub>3</sub> Tone Spacing = 1MHz, Pout per tone = 0 dBm<br>T <sub>L</sub> = 25°C Z <sub>S</sub> = Z <sub>L</sub> = 50 Ohms Tested with Bias Tees |                                                                     |       |                              |                  |                |                  |

The information provided herein is believed to be reliable at press time. Sirenza Microdevices assumes no responsibility for inaccuracies or omissions. Sirenza Microdevices assumes no responsibility for the use of this information, and all such information shall be entirely at the user's own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any Sirenza Microdevices product for use in life-support devices and/or systems. Copyright 2001 Sirenza Microdevices, Inc.. All worldwide rights reserved.



**Typical RF Performance at Key Operating Frequencies (With Application Circuit)**

| Symbol    | Parameter                          | Unit | Frequency (MHz) |     |     |     |     |     |     |
|-----------|------------------------------------|------|-----------------|-----|-----|-----|-----|-----|-----|
|           |                                    |      | 50              | 70  | 100 | 240 | 400 | 500 | 850 |
| $S_{21}$  | Small Signal Gain                  | dB   | 20              | 20  | 20  | 20  | 20  | 20  | 20  |
| $OIP_3$   | Output Third Order Intercept Point | dBm  | 40              | 40  | 41  | 42  | 41  | 40  | 35  |
| $P_{1dB}$ | Output Power at 1dB Compression    | dBm  | 20              | 20  | 20  | 20  | 20  | 20  | 19  |
| IRL       | Input Return Loss                  | dB   | 15              | 18  | 19  | 20  | 20  | 19  | 16  |
| ORL       | Output Return Loss                 | dB   | 21              | 23  | 24  | 27  | 34  | 30  | 14  |
| $S_{12}$  | Reverse Isolation                  | dB   | 22              | 22  | 22  | 22  | 22  | 22  | 22  |
| NF        | Noise Figure                       | dB   | 3.1             | 2.9 | 2.7 | 2.6 | 2.7 | 2.8 | 2.9 |





**Test Conditions:**  $V_{CC} = 5V$   $I_D = 90mA$  Typ.  $OIP_3$  Tone Spacing = 1MHz,  $P_{out}$  per tone = 0 dBm  
 $T_L = 25^\circ C$   $Z_S = Z_L = 50$  Ohms




*Data on Charts taken with App. Ckt.*







**S-Parameters over Temperature (Bias Tee)**




**Device Current over Temperature (Bias Tee)**




**Application Circuit S-Parameters over Temperature**



**Device Current over Temperature (w/App. Ckt.)**




### Application Schematic



### Application Circuit Element Values

| Reference Designator | Frequency (MHz)<br>50 to 850 |
|----------------------|------------------------------|
| $C_B$                | 8200pF                       |
| $L_C$                | 1200nH LS Coilcraft          |
| $L_S$                | 2.7nH Toko                   |

### Evaluation Board Layout



### Absolute Maximum Ratings

| Parameter                       | Absolute Limit |
|---------------------------------|----------------|
| Ma. Dvice Current ( $I_D$ )     | 110 mA         |
| Max Device Voltage ( $V_D$ )    | 5.5 V          |
| Max. RF Input Power             | +12 dBm        |
| Max. Operating Dissipated Power | 0.61 W         |
| Max. Junction Temp. ( $T_J$ )   | +150°C         |
| Operating Temp. Range ( $T_L$ ) | -40°C to +85°C |
| Max. Storage Temp.              | +150°C         |

Operation of this device beyond any one of these limits may cause permanent damage. For reliable continuous operation, the device voltage and current must not exceed the maximum operating values specified in the table on page one.

Bias Conditions should also satisfy the following expression:

$$I_D V_D < (T_J - T_L) / R_{TH}, \text{ j-l } T_L = T_{LEAD}$$

### Mounting Instructions

1. Solder the copper pad on the backside of the device package to the ground plane.
2. Use a large ground pad area with many plated through-holes as shown.
3. We recommend 1 or 2 ounce copper. Measurement for this datasheet were made on a 31 mil thick FR-4 board with 1 ounce copper on both sides.




### ESD Class 1C

Appropriate precautions in handling, packaging and testing devices must be observed.

**MSL (Moisture Sensitivity Level) Rating: Level 1**

### Suggested PCB Pad Layout

Dimensions in inches [millimeters]




### Nominal Package Dimensions


Dimensions in inches (millimeters)

Refer to package drawing posted at [www.sirenza.com](http://www.sirenza.com) for tolerances


#### Bottom View



#### Side View



#### Package Marking



### Part Number Ordering Information

| Part Number | Reel Size | Devices / Reel |
|-------------|-----------|----------------|
| SBB-2089Z   | 7"        | 1000           |

| Pin # | Function    | Description                                                                                                                     |
|-------|-------------|---------------------------------------------------------------------------------------------------------------------------------|
| 1     | RF IN       | RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.             |
| 2, 4  | GND         | Connection to ground. Use via holes for best performance to reduce lead inductance as close to ground leads as possible         |
| 3     | RF OUT/BIAS | RF output and bias pin. DC voltage is present on this pin, therefore a DC blocking capacitor is necessary for proper operation. |