SOLID STATE DEVICES, INC

14849 Firestone Boulevard · La Mirada,CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424

PRELIMINARY

SDR936/61 thru SDR939/61


Designer's Data Sheet

30 AMP 600-900 VOLTS 80 nsec ULTRA FAST RECTIFIER

FEATURES:

- Soft Recovery Diode
- Ultrafast Recovery: 80 nsec Maximum
- Available with faster recovery
- High Surge Rating
- Low Reverse Leakage Current
- Low Junction Capacitance
- Hermetically Sealed Package
- Gold Eutectic Die Attach available
- Ultrasonic Aluminum Wire Bonds
- TX, TXV and Space Level Screening Available

TO-61



MAXIMUM RATINGS

RATING	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse and DC Blocking Voltage			
SDR936/61	V_{RRM}	600	**Volts**
SDR937/61	V_{RWM}	700	
SDR938/61		800	
SDR939/61	V_R	900	
Average Rectified Forward Current (Resistive Load, 60Hz, Sine Wave, TA=25°C)	I_O	30	**Amps**
Peak Surge Current (8.3 ms Pulse, Half Sine Wave, TA=25°C)	I_{FSM}	450	**Amps**
Operating and storage temperature	**Top & Tstg**	-65 to +200	**°C**
Maximum Thermal Resistance Junction to Case	$R_{\theta JC}$	1.3	**°C/W**

SDR936/61 thru SDR939/61

PRELIMINARY

SOLID STATE DEVICES, INC


14849 Firestone Boulevard · La Mirada,CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424

ELECTRICAL CHARACTERISTICS

CHARACTERISTICS	SYMBOL	MAXIMUM	UNIT
Instantaneous Forward Voltage Drop (IF = 15 Adc, TA=25°C, 300ms Pulse) (IF = 30 Adc, TA=25°C, 300ms Pulse)	VF	1.25 1.40	Vdc
Instantaneous Forward Voltage Drop (IF = 30 Adc, TA= - 55°C, 300ms Pulse) (IF = 30 Adc, TA=100°C, 300ms Pulse)	VF	1.35 1.15	Vdc
Reverse Leakage Current (Rated VR, TA=25°C, 300ms pulse minimum)	IR	100	µA
Reverse Leakage Current (Rated VR, TA=100°C, 300ms pulse minimum)	IR	10	mA
Junction Capacitance (VR = 10 Vdc, TA=25°C, f= 1 MHz)	CJ	100	pf
Reverse Recovery Time (IF=500mA, IR=1 A, IRR=250mA, TA=25°C)	trr	80	nsec

CASE OUTLINE: TO-61
PIN OUT:

PIN 1: CATHODE
PIN 3: ANODE



TYPICAL OPERATING CURVES

TA=25°C Unless otherwise specified

