
Small Signal Fast Switching Diode

General Description

Dual general-purpose switching diodes, fabricated in planar technology, and packaged in small SOT-23F surface mounted device (SMD) packages.



SOT-23F

Features and Benefits

- Silicon epitaxial planar diode
- High switching speed: trr≤4ns
- Low forward drop voltage and low leakage current
- Full lead (Pb)-free device and RoHS compliant device
- Available in “Green” device


Applications

- Ultra high speed switching application

Ordering Information

Part Number	Marking Code	Package	Packaging
SDS2836F	CA2 □	SOT-23F	Tape & Reel



Marking Information



CA2 = Specific Device Code

□ = Year & Week Code Marking

Pinning Information

Pin	Description	Simplified Outline	Graphic Symbol
1	Cathode (Diode 1)		
2	Cathode (Diode 2)		
3	Common Anode		

Absolute Maximum Ratings (T_{amb}=25℃, Unless otherwise specified)

Characteristic	Symbol	Ratings	Unit
Maximum repetitive peak reverse voltage	V_{RM}	85	V
Continuous reverse voltage	V_R	80	V
Maximum average forward rectified current	I_O	100	mA
Forward current (DC)	I_F	100	mA
Maximum repetitive peak forward current	I_{FM}	300	mA
Non-repetitive peak forward surge current(t=10ms)	I_{FSM}	2	A
Power dissipation [1]	P_D	150	mW

[1] Device mounted on FR-4 board with recommended pad layout.

Thermal Characteristics (T_{amb}=25℃, Unless otherwise specified)

Characteristic	Symbol	Ratings	Unit
Thermal resistance, junction to ambient [1]	$R_{th(j-a)}$	830	°C/W
Operating junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55 ~ 150	°C

[1] Device mounted on FR-4 board with recommended pad layout.

Electrical Characteristics (T_{amb}=25℃, Unless otherwise specified)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward voltage [2]	$V_{F(1)}$	I_F=1mA	-	0.6	-	V
	$V_{F(2)}$	I_F=10mA	-	0.7	-	V
	$V_{F(3)}$	I_F=100mA	-	0.9	1.2	V
Reverse leakage current [3]	I_R	V_R=80V	-	-	0.5	uA
Total capacitance	C_T	V_R=0V, f=1㎒	-	2.2	4.0	pF
Reverse recovery time	t_{rr}	I_F=10mA (Fig. 5)	-	1.6	4.0	ns

[2] Pulse test: $t_P \leq 380\mu s$, Duty cycle≤2%

[3] Pulse test: $t_P \leq 5ms$, Duty cycle≤2%

Rating and Characteristic Curves

Fig. 1) Typical Forward Characteristics




Fig. 2) Typical Reverse Characteristics




Fig. 3) Typical Total Capacitance Characteristics




Fig. 4) Reverse Recovery Time vs. Forward Current






Fig. 5) Reverse recovery time equivalent test circuit




Package Outline Dimensions



SYMBOL	MILLIMETER(mm)			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	0.80	0.90	1.00	
A1	0.00	–	0.10	
b	0.35	0.40	0.45	
c	0.10	0.15	0.20	
D	2.80	2.90	3.00	
E	2.30	2.40	2.50	
E1	1.50	1.60	1.70	
e	0.95BSC			
e1	1.80	1.90	2.00	
L	0.48	0.58	0.68	
L1	0.30	–	0.50	

※ Recommend PCB solder land (Unit : mm)



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.