N-Channel MOSFET

Features

- Low R_{DS}(on) (0.023 Ω)@V_{GS}=10V
- Low Gate Charge (Typical 39nC)
- Low Crss (Typical 110pF)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Maximum Junction Temperature Range (175°C)



General Description

This Power MOSFET is produced using SemiWell's advanced planar stripe, DMOS technology. This latest technology has been especially designed to minimize on-state resistance, have a low gate charge with superior switching performance, and rugged avalanche characteristics. This Power MOSFET is well suited for synchronous DC-DC Converters and Power Management in portable and battery operated products.



Absolute Maximum Ratings

Symbol	Parameter		Value	Units
V_{DSS}	Drain to Source Voltage		60	V
I_D	Continuous Drain Current(@T_C = 25°C)		50	A
	Continuous Drain Current(@T_C = 100°C)		35.2	A
I_{DM}	Drain Current Pulsed	(Note 1)	200	A
V_{GS}	Gate to Source Voltage		±20	V
E_{AS}	Single Pulsed Avalanche Energy	(Note 2)	470	mJ
E_{AR}	Repetitive Avalanche Energy	(Note 1)	13	mJ
I_{AR}	Avalnche Current	(Note 1)	50	A
dv/dt	Peak Diode Recovery dv/dt	(Note 3)	7	V/ns
P_D	Total Power Dissipation(@T_C = 25 °C)		130	W
	Derating Factor above 25 °C		0.87	W/°C
T_{STG}, T_J	Operating Junction Temperature & Storage Temperature		- 55 ~ 175	°C
T_L	Maximum Lead Temperature for soldering purpose, 1/8 from Case for 5 seconds.		300	°C

Thermal Characteristics

Symbol	Parameter	Value			Units
		Min.	Typ.	Max.	
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	-	-	1.15	°C/W
$R_{\theta CS}$	Thermal Resistance, Case to Sink	-	0.5	-	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	-	-	62.5	°C/W

Copyright@SemiWell Semiconductor Co., Ltd., All rights reserved.

Electrical Characteristics (T_C = 25 °C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250uA	60	-	-	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature coefficient	I_D = 250uA, referenced to 25 °C	-	0.06	-	V/°C
I_{DSS}	Drain-Source Leakage Current	V_{DS} = 60V, V_{GS} = 0V	-	-	1	uA
		V_{DS} = 48V, T_C = 150 °C	-	-	10	uA
I_{GSS}	Gate-Source Leakage, Forward	V_{GS} = 20V, V_{DS} = 0V	-	-	100	nA
	Gate-source Leakage, Reverse	V_{GS} = -20V, V_{DS} = 0V	-	-	-100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250uA	2.0	-	4.0	V
$R_{DS(ON)}$	Static Drain-Source On-state Resistance	V_{GS} =10 V, I_D = 25A	-	0.018	0.023	Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{GS} =0 V, V_{DS} =25V, f = 1MHz	-	880	1140	pF
C_{oss}	Output Capacitance		-	430	560	
C_{rss}	Reverse Transfer Capacitance		-	110	140	
Dynamic Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD} =30V, I_D =25A, R_G =50Ω ※ **see fig. 13.** (Note 4, 5)	-	60	130	ns
t_r	Rise Time		-	185	380	
$t_{d(off)}$	Turn-off Delay Time		-	75	160	
t_f	Fall Time		-	60	130	
Q_g	Total Gate Charge	V_{DS} =48V, V_{GS} =10V, I_D =50A ※ **see fig. 12.** (Note 4, 5)	-	39	45	nC
Q_{gs}	Gate-Source Charge		-	9.5	-	
Q_{gd}	Gate-Drain Charge(Miller Charge)		-	13	-	

Source-Drain Diode Ratings and Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit.
I_S	Continuous Source Current	Integral Reverse p-n Junction Diode in the MOSFET	-	-	50	A
I_{SM}	Pulsed Source Current		-	-	200	
V_{SD}	Diode Forward Voltage	I_S =50A, V_{GS} =0V	-	-	1.5	V
t_{rr}	Reverse Recovery Time	I_S=50A,V_{GS}=0V,dI_F/dt=100A/us	-	54	-	ns
Q_{rr}	Reverse Recovery Charge		-	81	-	nC

※ NOTES

1. Repeativity rating : pulse width limited by junction temperature, δ <1%
2. L = 220uH, I_{AS} =50A, V_{DD} = 25V, R_G = 0Ω , Starting T_J = 25°C
3. ISD ≤ 50A, di/dt ≤ 300A/us, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C
4. Pulse Test : Pulse Width ≤ 300us, Duty Cycle ≤ 2%
5. Essentially independent of operating temperature.

Fig 1. On-State Characteristics



Fig 2. Transfer Characteristics



Fig 3. On Resistance Variation vs. Drain Current and Gate Voltage



Fig 4. On State Current vs. Allowable Case Temperature



Fig 5. Capacitance Characteristics



Fig 6. Gate Charge Characteristics



Fig 7. Breakdown Voltage Variation vs. Junction Temperature



Fig 8. On-Resistance Variation vs. Junction Temperature



Fig 9. Maximum Safe Operating Area



Fig 10. Maximum Drain Current vs. Case Temperature



Fig 11. Transient Thermal Response Curve



Fig. 12. Gate Charge Test Circuit & Waveforms



Fig 13. Switching Time Test Circuit & Waveforms



Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms



Fig. 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms



TO-220 Package Dimension

Dim.	mm			Inch		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.7		10.1	0.382		0.398
B	6.3		6.7	0.248		0.264
C	9.0		9.47	0.354		0.373
D	12.8		13.3	0.504		0.524
E	1.2		1.4	0.047		0.055
F		1.7			0.067	
G		2.5			0.098	
H	3.0		3.4	0.118		0.134
I	1.25		1.4	0.049		0.055
J	2.4		2.7	0.094		0.106
K	5.0		5.15	0.197		0.203
L	2.2		2.6	0.087		0.102
M	1.25		1.55	0.049		0.061
N	0.45		0.6	0.018		0.024
O	0.6		1.0	0.024		0.039
∅		3.6			0.142	

