N-Channel 30-V (D-S) MOSFET


PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)[a]	Q_g (Typ)
30	0.270 @ V_{GS} = 4.5 V	0.90	1.1
	0.385 @ V_{GS} = 2.5 V	0.75	

FEATURES


- TrenchFET® Power MOSFET
- 100% R_g Tested


Pb-free
RoHS COMPLIANT

SC-70 (3-LEADS)



Top View





Ordering Information: Si1304BDL–T1–E3

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	± 12	
Continuous Drain Current (T_J = 150°C)	T_C = 25°C	I_D	0.90	A
	T_C = 70°C		0.71	
	T_A = 25°C		0.85[b, c]	
	T_A = 70°C		0.68[b, c]	
Pulsed Drain Current		I_{DM}	4	
Continuous Source-Drain Diode Current	T_C = 25°C	I_S	0.31	
	T_A = 25°C		0.28[b, c]	
Maximum Power Dissipation	T_C = 25°C	P_D	0.37	W
	T_C = 70°C		0.24	
	T_A = 25°C		0.34[b, c]	
	T_A = 70°C		0.22[b, c]	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	–55 to 150	°C

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient[b, d]	t ≤ 5 sec	R_{thJA}	315	375	°C/W
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	285	340	

Notes:
a. Based on T_C = 25°C.
b. Surface mounted on 1" x 1" FR4 board.
c. t = 5 sec
d. Maximum under steady state conditions is 360 °C/W.

SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	V_{GS} = 0 V, I_D = 250 μA	30			V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	I_D = 250 μA		27.3		mV/°C
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$			3		
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 μA	0.6		1.3	V
Gate-Source Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±12 V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 30 V, V_{GS} = 0 V			1	μA
		V_{DS} = 30 V, V_{GS} = 0 V, T_J = 70°C			5	
On-State Drain Current[a]	$I_{D(on)}$	V_{DS} ≥ 5 V, V_{GS} = 4.5 V	4			A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = 4.5 V, I_D = 0.9		0.216	0.270	Ω
		V_{GS} =2.5 V, I_D = 0.75		0.308	0.385	
Forward Transconductance[a]	g_{fs}	V_{DS} = 15 V, I_D = 0.9		2		S
Dynamic[b]						
Input Capacitance	C_{iss}	V_{DS} = 15 V, V_{GS} = 0 V, f = 1 MHz		100		pF
Output Capacitance	C_{oss}			30		
Reverse Transfer Capacitance	C_{rss}			20		
Total Gate Charge	Q_g	V_{DS} = 15 V, V_{GS} = 4.5 V, I_D = 0.9		1.8	2.7	nC
		V_{DS} = 15 V, V_{GS} = 2.5 V, I_D= 0.9		1.1	1.7	
Gate-Source Charge	Q_{gs}			0.4		
Gate-Drain Charge	Q_{gd}			0.6		
Gate Resistance	R_g	f = 1 MHz		1.5	2.3	Ω
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 15 V, R_L = 22 Ω I_D ≅ 0.68 A, V_{GEN} = 4.5 V, R_g = 1 Ω		10	15	ns
Rise Time	t_r			30	45	
Turn-Off Delay Time	$t_{d(off)}$			5	25	
Fall Time	t_f			10	15	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	T_C = 25°C			0.31	A
Pulse Diode Forward Current[a]	I_{SM}				4	
Body Diode Voltage	V_{SD}	I_S = 0.28 A		0.8	1.2	V
Body Diode Reverse Recovery Time	t_{rr}	I_F = 0.28 A, di/dt = 100 A/μs, T_J = 25°C		50	75	ns
Body Diode Reverse Recovery Charge	Q_{rr}			105	160	nC
Reverse Recovery Fall Time	t_a			34		ns
Reverse Recovery Rise Time	t_b			16		


Notes

a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics curves vs. Temp




On-Resistance vs. Drain Current




Capacitance



Q_g–Gate Charge




On-Resistance vs. Junction Temperature




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Forward Diode Voltage vs. Temp




$r_{DS(on)}$ vs VGS vs Temperature




Threshold Voltage



Single Pulse Power, Junction-to-Ambient




Safe Operating Area



*V_{GS} > minimum V_{GS} at which $r_{DS(on)}$ is specified

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

Current De-Rating*





Power, De-Rating



*The power dissipation P_D is based on $T_{J(max)}$ = 150°C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see http://www.vishay.com/ppg?73480.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.