

SIL40C2 Series

4.5-13.8 Vin Single Output

March 15, 2006


DC-DC CONVERTERS

C Class Non-isolated

1

NEW Product

- **40 A current rating**
- **Input voltage range: 4.5-13.8 V**
- **Output voltage: 0.6-5 V**
- **Industry leading value**
 - **Cost optimized design**
- **Excellent transient response**
- **Output enable**
- **Output voltage adjustability**
 - **Pathway for future upgrades**
 - **Supports silicon voltage migration**
 - **Resulting in reduced design-in and qual time**
- **RoHS compliant**



The SIL40C2 series is a new high density open frame non-isolated converter for space sensitive applications. This model has a wide input range (4.5-13.8 Vdc) and offers a wide 0.6-5 V output voltage range with 40 A load capability. An external resistor adjusts the output voltage from its pre-set value of 0.6 V to any value up to the 5 V maximum. Typical efficiencies for the models are 91% for the 12 V input version. The SIL40C2 series offers remote ON/OFF and over-current protection as standard.

UL US
2 YEAR WARRANTY



All specifications are typical at nominal input, full load at 25 °C unless otherwise stated

SPECIFICATIONS

OUTPUT SPECIFICATIONS

Output voltage	(See Note 5)	0.6-5 V
Output setpoint accuracy	0.1% trim resistors	±1.0%
Line regulation	Low line to high line	±0.2%
Load regulation	Full load to min. load	±0.5%
Min/max load		0 A/40 A
Overshoot	At turn-on	0.5% max.
Undershoot	At turn-off	100 mV max.
Ripple and noise 5 Hz to 20 MHz	(See Note 1) Vin = 5 V, Vout = 2.5 V	25 mV
Transient response	(See Notes 1, 2)	150 mV max. deviation 30 µs recovery within regulation band

INPUT SPECIFICATIONS

Input voltage range		4.5-13.8 Vdc
Input current	Minimum load Remote OFF	50 mA 5 mA
Input current (max.)	(See Note 3)	25 A @ Io max.
Start-up time	Remote ON/OFF	3 ms

GENERAL SPECIFICATIONS

Efficiency	Vin=5 V, Vo=2.5 V, Io=20 A	94% Typ.
Switching frequency	Fixed	500 kHz
Approvals and standards (pending)		EN60950 UL/cUL60950
Material flammability		UL94V-0
Weight		17 g/0.06 oz.
MTBF	12 V @ 40 °C 100% load Bellcore 332	6,749,409 hours
Coplanarity		150 µm

ENVIRONMENTAL SPECIFICATIONS

Thermal performance (See Note 5)	Operating ambient, temperature Non-operating	0 °C to +70 °C -40 °C to +125 °C
-------------------------------------	--	-------------------------------------

PROTECTION

Short-circuit	Hiccup, non-latching
Over voltage	Hiccup, non-latching

RECOMMENDED SYSTEM CAPACITANCE

Input capacitance	(See Note 6)	0 µF
Output capacitance	(See Note 7)	0 µF

International Safety Standard Approvals



UL/cUL CAN/CSA 22.2 No. E139421
UL60950 File No. TBD



TÜV Product Service (EN60950) Certificate No. TBD
CB report and certificate to IEC60950

SIL40C2 Series

4.5-13.8 Vin Single Output

March 15, 2006

DC-DC CONVERTERS

C Class Non-isolated

2

For the most current data and application support visit www.artesyn.com/powergroup/products.htm

NEW Product

OUTPUT POWER (MAX.)	INPUT VOLTAGE	OVP	OUTPUT VOLTAGE	OUTPUT CURRENT (MIN.)	OUTPUT CURRENT (MAX.)	EFFICIENCY (TYP.)	REGULATION		MODEL NUMBER ^(8, 9)
							LINE	LOAD	
200 W	4.5-13.8 Vdc	N/A	0.6-5 Vdc	0 A	40 A	94%	±0.2%	±0.5%	SIL40C2-00SADJ-VJ

Part Number System with Options

SIL40C2-00SADJ-VJ

Product Family

SIL = Single In Line
SMT = Surface Mount

Rated Output Current

06 = 6 A
15 = 15 A
20 = 20 A
30 = 30 A
40 = 40 A

Performance

C = Cost Optimized

Generation

Blank = Standard Part
2 = Increased Current Density

RoHS Compliance ⁽⁸⁾

J = Pb-free (RoHS 6/6 compliant)

Mounting Option

V = Vertical
H = Horizontal

Output Voltage

Single Adjustable Output

Input Voltage

00 = 4.5-13.8 V

Output Voltage Adjustment of the SIL40C2 Series

The ultra-wide output voltage trim range offers major advantages to users who select the SIL40C2. It is no longer necessary to purchase a variety of modules in order to cover different output voltages. The output voltage can be trimmed in a range of 0.6-5 V. When the SIL40C2 converter leaves the factory the output has been adjusted to the default voltage of 0.6 V.

Notes

- 1 Measured as per recommended system capacitance.
- 2 $di/dt = 10 \text{ A}/\mu\text{s}$, $V_{in} = \text{Nom}$, $T_c = 25^\circ\text{C}$, load change = 0.75 I_o to full I_o and full I_o to 0.75.
- 3 External input fusing is recommended.
- 4 Additional part numbers may be available with different output voltages.
- 5 Airflow dependent, 100 LFM minimum required.
- 6 No capacitor needed for ripple current capability.
- 7 No capacitor needed for stability.
- 8 TSE RoHS 5/6 (non PB-free) compliant versions are also available on special request, please contact your local sales representative for details.
- 9 NOTICE: Some models may not support all options. Please contact your local Artesyn representative or use the on-line model number search tool at <http://www.artesyn.com/powergroup/products.htm> to find a suitable alternative.




Figure 1: Standard Application Drawing

SIL40C2 Series

4.5-13.8 Vin Single Output

March 15, 2006

DC-DC CONVERTERS

C Class Non-isolated

3

For the most current data and application support visit www.artesyn.com/powergroup/products.htm

NEW Product

PIN CONNECTIONS	
PIN NO.	FUNCTION
1	Vout
2	Vout
3	Vout
4	Trim
5	Enable
6	Power Good
7	Ground
8	Ground
9	(+) Sense
10	Vin
11	Vin
12	*Mech Support
13	*Mech Support

* Horizontal and SMT version only




Figure 2: Vertical Mount Mechanical Drawing




Figure 3: Horizontal Mount Mechanical Drawing

SIL40C2 Series

4.5-13.8 Vin Single Output

March 15, 2006

DC-DC CONVERTERS

C Class Non-isolated

4

For the most current data and application support visit www.artesyn.com/powergroup/products.htm

NEW Product

PIN CONNECTIONS	
PIN NO.	FUNCTION
1	Vout
2	Vout
3	Vout
4	Trim
5	Enable
6	Power Good
7	Ground
8	Ground
9	(+) Sense
10	Vin
11	Vin
12	*Mech Support
13	*Mech Support

* Horizontal and SMT version only




Figure 4: Surface Mount Mechanical Drawing