



## SNx4HC273 Octal D-Type Flip-Flops With Clear

### 1 Features

- Wide Operating Voltage Range of 2 V to 6 V
- Outputs Can Drive Up to 10 LSTTL Loads
- Low Power Consumption, 80- $\mu$ A Maximum  $I_{CC}$
- Typical  $t_{pd} = 12$  ns
- $\pm 4$ -mA Output Drive at 5 V
- Low Input Current of 1- $\mu$ A Maximum
- Contain Eight Flip-Flops With Single-Rail Outputs
- Direct Clear Input
- Individual Data Input to Each Flip-Flop
- On Products Compliant to MIL-PRF-38535, All Parameters Are Tested Unless Otherwise Noted. On All Other Products, Production Processing Does Not Necessarily Include Testing of All Parameters.

### 2 Applications

- Buffer or Storage Registers
- Shift Registers
- Pattern Generators

### 3 Description

The SNx4HC273 devices are positive-edge-triggered D-type flip-flops with a direct active low clear (CLR) input.


Information at the data (D) inputs meeting the setup time requirements is transferred to the Q outputs on the positive-going edge of the clock (CLK) pulse. Clock triggering occurs at a particular voltage level and is not related directly to the transition time of the positive-going pulse. When CLK is at either the high or low level, the D input has no effect at the output.

**Device Information<sup>(1)</sup>**

| PART NUMBER | PACKAGE (PINS) | BODY SIZE (NOM)           |
|-------------|----------------|---------------------------|
| SN54HC273J  | CDIP (20)      | 24.20 mm $\times$ 6.92 mm |
| SN54HC273W  | CFP (20)       | 13.09 mm $\times$ 6.92 mm |
| SN54HC273FK | LCCC (20)      | 8.89 mm $\times$ 8.89 mm  |
| SN74HC273D  | SOIC (20)      | 12.80 mm $\times$ 7.50 mm |
| SN74HC273DB | SSOP (20)      | 7.20 mm $\times$ 5.30 mm  |
| SN74HC273NS | SO (20)        | 12.60 mm $\times$ 5.30 mm |
| SN74HC273N  | PDIP (20)      | 24.33 mm $\times$ 6.35 mm |
| SN74HC273PW | TSSOP (20)     | 6.50 mm $\times$ 4.40 mm  |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

**Logic Diagram, Each Flip-Flop (Positive Logic)**



Copyright © 2016, Texas Instruments Incorporated



## Table of Contents

|                                                  |           |                                                                  |           |
|--------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                          | <b>1</b>  | <b>8 Detailed Description</b> .....                              | <b>11</b> |
| <b>2 Applications</b> .....                      | <b>1</b>  | 8.1 Overview .....                                               | 11        |
| <b>3 Description</b> .....                       | <b>1</b>  | 8.2 Functional Block Diagram .....                               | 11        |
| <b>4 Revision History</b> .....                  | <b>2</b>  | 8.3 Feature Description .....                                    | 11        |
| <b>5 Pin Configuration and Functions</b> .....   | <b>3</b>  | 8.4 Device Functional Modes .....                                | 11        |
| <b>6 Specifications</b> .....                    | <b>4</b>  | <b>9 Application and Implementation</b> .....                    | <b>12</b> |
| 6.1 Absolute Maximum Ratings .....               | 4         | 9.1 Application Information .....                                | 12        |
| 6.2 ESD Ratings – SN74HC273 .....                | 4         | 9.2 Typical Application .....                                    | 12        |
| 6.3 Recommended Operating Conditions .....       | 4         | <b>10 Power Supply Recommendations</b> .....                     | <b>13</b> |
| 6.4 Thermal Information .....                    | 5         | <b>11 Layout</b> .....                                           | <b>13</b> |
| 6.5 Electrical Characteristics .....             | 5         | 11.1 Layout Guidelines .....                                     | 13        |
| 6.6 Electrical Characteristics – SN54HC273 ..... | 5         | 11.2 Layout Example .....                                        | 13        |
| 6.7 Electrical Characteristics – SN74HC273 ..... | 6         | <b>12 Device and Documentation Support</b> .....                 | <b>14</b> |
| 6.8 Timing Requirements .....                    | 6         | 12.1 Documentation Support .....                                 | 14        |
| 6.9 Timing Requirements – SN54HC273 .....        | 7         | 12.2 Related Links .....                                         | 14        |
| 6.10 Timing Requirements – SN74HC273 .....       | 7         | 12.3 Receiving Notification of Documentation Updates .....       | 14        |
| 6.11 Switching Characteristics .....             | 8         | 12.4 Community Resources .....                                   | 14        |
| 6.12 Switching Characteristics – SN54HC273 ..... | 8         | 12.5 Trademarks .....                                            | 14        |
| 6.13 Switching Characteristics – SN74HC273 ..... | 8         | 12.6 Electrostatic Discharge Caution .....                       | 14        |
| 6.14 Operating Characteristics .....             | 9         | 12.7 Glossary .....                                              | 14        |
| 6.15 Typical Characteristics .....               | 9         | <b>13 Mechanical, Packaging, and Orderable Information</b> ..... | <b>14</b> |
| <b>7 Parameter Measurement Information</b> ..... | <b>10</b> |                                                                  |           |


## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


| Changes from Revision D (August 2003) to Revision E                                                                                                                                                                                                                                                                                                                                  | Page |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| • Added <i>Device Information</i> table, <i>ESD Ratings</i> table, <i>Feature Description</i> section, <i>Device Functional Modes</i> , <i>Application and Implementation</i> section, <i>Power Supply Recommendations</i> section, <i>Layout</i> section, <i>Device and Documentation Support</i> section, and <i>Mechanical, Packaging, and Orderable Information</i> section..... | 1    |
| • Removed <i>Ordering Information</i> table, see POA at the end of the data sheet.....                                                                                                                                                                                                                                                                                               | 1    |
| • Added Military Disclaimer to <i>Features</i> .....                                                                                                                                                                                                                                                                                                                                 | 1    |
| • Changed $R_{\theta JA}$ for DB package from 70°C/W : to 90.3°C/W .....                                                                                                                                                                                                                                                                                                             | 5    |
| • Changed $R_{\theta JA}$ for DW package from 58°C/W : to 77.4°C/W .....                                                                                                                                                                                                                                                                                                             | 5    |
| • Changed $R_{\theta JA}$ for N package from 69°C/W : to 45.1°C/W.....                                                                                                                                                                                                                                                                                                               | 5    |
| • Changed $R_{\theta JA}$ for NS package from 60°C/W : to 72.6°C/W .....                                                                                                                                                                                                                                                                                                             | 5    |
| • Changed $R_{\theta JA}$ for PW package from 83°C/W : to 98.3°C/W .....                                                                                                                                                                                                                                                                                                             | 5    |

## 5 Pin Configuration and Functions

**J, W, DB, DW N, NS, or PW Package  
CDIP, CFP, SSOP, SOIC, SO, PDIP, or TSSOP  
Top View**



**FK Package  
20-Pin LCCC  
Top View**



### Pin Functions

| PIN |                 | I/O | DESCRIPTION            |
|-----|-----------------|-----|------------------------|
| NO. | NAME            |     |                        |
| 1   | CLR             | I   | Active low clear input |
| 2   | 1Q              | O   | Output 1               |
| 3   | 1D              | I   | Input 1                |
| 4   | 2D              | I   | Input 2                |
| 5   | 2Q              | O   | Output 2               |
| 6   | 3Q              | O   | Output 3               |
| 7   | 3D              | I   | Input 3                |
| 8   | 4D              | I   | Input 4                |
| 9   | 4Q              | O   | Output 4               |
| 10  | GND             | —   | Ground                 |
| 11  | CLK             | I   | Clock input            |
| 12  | 5Q              | O   | Output 5               |
| 13  | 5D              | I   | Input 5                |
| 14  | 6D              | I   | Input 6                |
| 15  | 6Q              | O   | Output 6               |
| 16  | 7Q              | O   | Output 7               |
| 17  | 7D              | I   | Input 7                |
| 18  | 8D              | I   | Input 8                |
| 19  | 8Q              | O   | Output 8               |
| 20  | V <sub>CC</sub> | —   | Power                  |

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                  |                                                   |                                                        | MIN  | MAX | UNIT |
|------------------|---------------------------------------------------|--------------------------------------------------------|------|-----|------|
| V <sub>CC</sub>  | Supply voltage                                    |                                                        | –0.5 | 7   | V    |
| I <sub>IK</sub>  | Input clamp current <sup>(2)</sup>                | V <sub>I</sub> < 0 or V <sub>I</sub> > V <sub>CC</sub> |      | ±20 | mA   |
| I <sub>OK</sub>  | Output clamp current <sup>(2)</sup>               | V <sub>O</sub> < 0 or V <sub>O</sub> > V <sub>CC</sub> |      | ±20 | mA   |
| I <sub>O</sub>   | Continuous output current                         | V <sub>O</sub> = 0 to V <sub>CC</sub>                  |      | ±25 | mA   |
|                  | Continuous current through V <sub>CC</sub> or GND |                                                        |      | ±50 | mA   |
| T <sub>J</sub>   | Junction temperature                              |                                                        |      | 150 | °C   |
| T <sub>stg</sub> | Storage temperature                               |                                                        | –65  | 150 | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

### 6.2 ESD Ratings – SN74HC273

|                    |                         |                                                                                | VALUE | UNIT |
|--------------------|-------------------------|--------------------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 | V    |
|                    |                         | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±500  |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible with the necessary precautions.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible with the necessary precautions.

### 6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                 |                                     |                         | MIN  | NOM | MAX             | UNIT |
|-----------------|-------------------------------------|-------------------------|------|-----|-----------------|------|
| V <sub>CC</sub> | Supply voltage                      |                         | 2    | 5   | 6               | V    |
| V <sub>IH</sub> | High-level input voltage            | V <sub>CC</sub> = 2 V   | 1.5  |     |                 | V    |
|                 |                                     | V <sub>CC</sub> = 4.5 V | 3.15 |     |                 |      |
|                 |                                     | V <sub>CC</sub> = 6 V   | 4.2  |     |                 |      |
| V <sub>IL</sub> | Low-level input voltage             | V <sub>CC</sub> = 2 V   |      |     | 0.5             | V    |
|                 |                                     | V <sub>CC</sub> = 4.5 V |      |     | 1.35            |      |
|                 |                                     | V <sub>CC</sub> = 6 V   |      |     | 1.8             |      |
| V <sub>I</sub>  | Input voltage                       |                         | 0    |     | V <sub>CC</sub> | V    |
| V <sub>O</sub>  | Output voltage                      |                         | 0    |     | V <sub>CC</sub> | V    |
| Δt/Δv           | Input transition rise and fall time | V <sub>CC</sub> = 2 V   |      |     | 1000            | ns   |
|                 |                                     | V <sub>CC</sub> = 4.5 V |      |     | 500             |      |
|                 |                                     | V <sub>CC</sub> = 6 V   |      |     | 400             |      |
| T <sub>A</sub>  | Operating free-air temperature      | SN54HC273               | –55  |     | 125             | °C   |
|                 |                                     | SN74HC273               | –40  |     | 85              |      |

- (1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, [Implications of Slow or Floating CMOS Inputs](#).

## 6.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                                       | SN74HC273    |              |             |            |               | UNIT |
|-------------------------------|-------------------------------------------------------|--------------|--------------|-------------|------------|---------------|------|
|                               |                                                       | DB<br>(SSOP) | DW<br>(SOIC) | N<br>(PDIP) | NS<br>(SO) | PW<br>(TSSOP) |      |
|                               |                                                       | 20 PINS      | 20 PINS      | 20 PINS     | 20 PINS    | 20 PINS       |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance <sup>(2)</sup> | 90.3         | 77.4         | 45.1        | 72.6       | 98.3          | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance             | 51.7         | 42.8         | 31.1        | 38.9       | 33.3          | °C/W |
| $R_{\theta JB}$               | Junction-to-board thermal resistance                  | 45.5         | 45.2         | 26          | 40.1       | 49.3          | °C/W |
| $\psi_{JT}$                   | Junction-to-top characterization parameter            | 17.7         | 16.7         | 16.6        | 15.7       | 2             | °C/W |
| $\psi_{JB}$                   | Junction-to-board characterization parameter          | 45.1         | 44.7         | 25.9        | 39.7       | 48.7          | °C/W |

(1) For more information about traditional and new thermal metrics, see [Semiconductor and IC Package Thermal Metrics](#).

(2) The package thermal impedance is calculated in accordance with JESD 51-7.

## 6.5 Electrical Characteristics

$T_A = 25^\circ\text{C}$  (unless otherwise noted)

| PARAMETER | TEST CONDITIONS                                             |                                                  | MIN                      | TYP       | MAX       | UNIT          |
|-----------|-------------------------------------------------------------|--------------------------------------------------|--------------------------|-----------|-----------|---------------|
| $V_{OH}$  | $V_i = V_{IH} \text{ or } V_{IL}$                           | $I_{OH} = -20 \mu\text{A}$                       | $V_{CC} = 2 \text{ V}$   | 1.9       | 1.998     | V             |
|           |                                                             | $I_{OH} = -4 \text{ mA}, V_{CC} = 4.5 \text{ V}$ | $V_{CC} = 4.5 \text{ V}$ | 4.4       | 4.499     |               |
|           |                                                             |                                                  | $V_{CC} = 6 \text{ V}$   | 5.9       | 5.999     |               |
|           |                                                             |                                                  |                          | 3.98      | 4.3       |               |
|           |                                                             | $I_{OH} = -5.2 \text{ mA}, V_{CC} = 6 \text{ V}$ |                          | 5.48      | 5.8       |               |
| $V_{OL}$  | $V_i = V_{IH} \text{ or } V_{IL}$                           | $I_{OL} = 20 \mu\text{A}$                        | $V_{CC} = 2 \text{ V}$   | 0.002     | 0.1       | V             |
|           |                                                             | $I_{OL} = 4 \text{ mA}, V_{CC} = 4.5 \text{ V}$  | $V_{CC} = 4.5 \text{ V}$ | 0.001     | 0.1       |               |
|           |                                                             |                                                  | $V_{CC} = 6 \text{ V}$   | 0.001     | 0.1       |               |
|           |                                                             |                                                  |                          | 0.17      | 0.26      |               |
|           |                                                             | $I_{OL} = 5.2 \text{ mA}, V_{CC} = 6 \text{ V}$  |                          | 0.15      | 0.26      |               |
| $I_i$     | $V_i = V_{CC} \text{ or } 0, V_{CC} = 6 \text{ V}$          |                                                  |                          | $\pm 0.1$ | $\pm 100$ | nA            |
| $I_{CC}$  | $V_i = V_{CC} \text{ or } 0, I_o = 0, V_{CC} = 6 \text{ V}$ |                                                  |                          |           | 8         | $\mu\text{A}$ |
| $C_i$     | $V_{CC} = 2 \text{ V to } 6 \text{ V}$                      |                                                  |                          | 3         | 10        | pF            |

## 6.6 Electrical Characteristics – SN54HC273

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS                                             |                                                  | MIN                      | TYP | MAX        | UNIT          |
|-----------|-------------------------------------------------------------|--------------------------------------------------|--------------------------|-----|------------|---------------|
| $V_{OH}$  | $V_i = V_{IH} \text{ or } V_{IL}$                           | $I_{OH} = -20 \mu\text{A}$                       | $V_{CC} = 2 \text{ V}$   | 1.9 |            | V             |
|           |                                                             | $I_{OH} = -4 \text{ mA}, V_{CC} = 4.5 \text{ V}$ | $V_{CC} = 4.5 \text{ V}$ | 4.4 |            |               |
|           |                                                             |                                                  | $V_{CC} = 6 \text{ V}$   | 5.9 |            |               |
|           |                                                             |                                                  |                          | 3.7 |            |               |
|           |                                                             | $I_{OH} = -5.2 \text{ mA}, V_{CC} = 6 \text{ V}$ |                          | 5.2 |            |               |
| $V_{OL}$  | $V_i = V_{IH} \text{ or } V_{IL}$                           | $I_{OL} = 20 \mu\text{A}$                        | $V_{CC} = 2 \text{ V}$   |     | 0.1        | V             |
|           |                                                             | $I_{OL} = 4 \text{ mA}, V_{CC} = 4.5 \text{ V}$  | $V_{CC} = 4.5 \text{ V}$ |     | 0.1        |               |
|           |                                                             |                                                  | $V_{CC} = 6 \text{ V}$   |     | 0.1        |               |
|           |                                                             |                                                  |                          |     | 0.4        |               |
|           |                                                             | $I_{OL} = 5.2 \text{ mA}, V_{CC} = 6 \text{ V}$  |                          |     | 0.4        |               |
| $I_i$     | $V_i = V_{CC} \text{ or } 0, V_{CC} = 6 \text{ V}$          |                                                  |                          |     | $\pm 1000$ | nA            |
| $I_{CC}$  | $V_i = V_{CC} \text{ or } 0, I_o = 0, V_{CC} = 6 \text{ V}$ |                                                  |                          |     | 160        | $\mu\text{A}$ |
| $C_i$     | $V_{CC} = 2 \text{ V to } 6 \text{ V}$                      |                                                  |                          |     | 10         | pF            |

**SN54HC273, SN74HC273**

SCLS136E – DECEMBER 1982 – REVISED JULY 2016

[www.ti.com](http://www.ti.com)

## 6.7 Electrical Characteristics – SN74HC273

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER       | TEST CONDITIONS                                                                  |                                                  |                         | MIN  | TYP | MAX   | UNIT |
|-----------------|----------------------------------------------------------------------------------|--------------------------------------------------|-------------------------|------|-----|-------|------|
| V <sub>OH</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OH</sub> = −20 μA                         | V <sub>CC</sub> = 2 V   | 1.9  |     |       | V    |
|                 |                                                                                  |                                                  | V <sub>CC</sub> = 4.5 V | 4.4  |     |       |      |
|                 |                                                                                  |                                                  | V <sub>CC</sub> = 6 V   | 5.9  |     |       |      |
|                 |                                                                                  | I <sub>OH</sub> = −4 mA, V <sub>CC</sub> = 4.5 V |                         | 3.84 |     |       |      |
|                 |                                                                                  | I <sub>OH</sub> = −5.2 mA, V <sub>CC</sub> = 6 V |                         | 5.34 |     |       |      |
| V <sub>OL</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OL</sub> = 20 μA                          | V <sub>CC</sub> = 2 V   |      |     | 0.1   | V    |
|                 |                                                                                  |                                                  | V <sub>CC</sub> = 4.5 V |      |     | 0.1   |      |
|                 |                                                                                  |                                                  | V <sub>CC</sub> = 6 V   |      |     | 0.1   |      |
|                 |                                                                                  | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 4.5 V  |                         |      |     | 0.33  |      |
|                 |                                                                                  | I <sub>OL</sub> = 5.2 mA, V <sub>CC</sub> = 6 V  |                         |      |     | 0.33  |      |
| I <sub>I</sub>  | V <sub>I</sub> = V <sub>CC</sub> or 0, V <sub>CC</sub> = 6 V                     |                                                  |                         |      |     | ±1000 | nA   |
| I <sub>CC</sub> | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0, V <sub>CC</sub> = 6 V |                                                  |                         |      |     | 80    | μA   |
| C <sub>i</sub>  | V <sub>CC</sub> = 2 V to 6 V                                                     |                                                  |                         |      |     | 10    | pF   |

## 6.8 Timing Requirements

 $T_A = 25^\circ\text{C}$  (unless otherwise noted)

|                    |                                      |                             |                          | MIN | MAX | UNIT |
|--------------------|--------------------------------------|-----------------------------|--------------------------|-----|-----|------|
| $f_{\text{clock}}$ | Clock frequency                      |                             | $V_{CC} = 2 \text{ V}$   |     | 5   | MHz  |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ |     | 27  |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   |     | 32  |      |
| $t_w$              | Pulse duration                       | $\overline{\text{CLR}}$ low | $V_{CC} = 2 \text{ V}$   | 80  |     | ns   |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ | 16  |     |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   | 14  |     |      |
|                    | CLK high or low                      |                             | $V_{CC} = 2 \text{ V}$   | 80  |     |      |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ | 16  |     |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   | 14  |     |      |
| $t_{\text{su}}$    | Setup time before CLK $\uparrow$     | Data                        | $V_{CC} = 2 \text{ V}$   | 100 |     | ns   |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ | 20  |     |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   | 17  |     |      |
|                    | $\overline{\text{CLR}}$ inactive     |                             | $V_{CC} = 2 \text{ V}$   | 100 |     |      |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ | 20  |     |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   | 17  |     |      |
| $t_h$              | Hold time, data after CLK $\uparrow$ |                             | $V_{CC} = 2 \text{ V}$   | 0   |     | ns   |
|                    |                                      |                             | $V_{CC} = 4.5 \text{ V}$ | 0   |     |      |
|                    |                                      |                             | $V_{CC} = 6 \text{ V}$   | 0   |     |      |

## 6.9 Timing Requirements – SN54HC273

over recommended operating free-air temperature range (unless otherwise noted)

|                    |                                      |                                 | MIN | MAX | UNIT |
|--------------------|--------------------------------------|---------------------------------|-----|-----|------|
| $f_{\text{clock}}$ | Clock frequency                      | $V_{\text{CC}} = 2 \text{ V}$   |     | 4   | MHz  |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ |     | 18  |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   |     | 21  |      |
| $t_w$              | $\overline{\text{CLR}}$ low          | $V_{\text{CC}} = 2 \text{ V}$   | 120 |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 24  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 20  |     |      |
|                    | CLK high or low                      | $V_{\text{CC}} = 2 \text{ V}$   | 120 |     |      |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 24  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 20  |     |      |
| $t_{\text{su}}$    | Data                                 | $V_{\text{CC}} = 2 \text{ V}$   | 150 |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 30  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 25  |     |      |
|                    | $\overline{\text{CLR}}$ inactive     | $V_{\text{CC}} = 2 \text{ V}$   | 150 |     |      |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 30  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 25  |     |      |
| $t_h$              | Hold time, data after CLK $\uparrow$ | $V_{\text{CC}} = 2 \text{ V}$   | 0   |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 0   |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 0   |     |      |

## 6.10 Timing Requirements – SN74HC273

over recommended operating free-air temperature range (unless otherwise noted)

|                    |                                      |                                 | MIN | MAX | UNIT |
|--------------------|--------------------------------------|---------------------------------|-----|-----|------|
| $f_{\text{clock}}$ | Clock frequency                      | $V_{\text{CC}} = 2 \text{ V}$   |     | 4   | MHz  |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ |     | 21  |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   |     | 25  |      |
| $t_w$              | $\overline{\text{CLR}}$ low          | $V_{\text{CC}} = 2 \text{ V}$   | 100 |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 20  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 17  |     |      |
|                    | CLK high or low                      | $V_{\text{CC}} = 2 \text{ V}$   | 100 |     |      |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 20  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 17  |     |      |
| $t_{\text{su}}$    | Data                                 | $V_{\text{CC}} = 2 \text{ V}$   | 125 |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 25  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 21  |     |      |
|                    | $\overline{\text{CLR}}$ inactive     | $V_{\text{CC}} = 2 \text{ V}$   | 125 |     |      |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 25  |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 21  |     |      |
| $t_h$              | Hold time, data after CLK $\uparrow$ | $V_{\text{CC}} = 2 \text{ V}$   | 0   |     | ns   |
|                    |                                      | $V_{\text{CC}} = 4.5 \text{ V}$ | 0   |     |      |
|                    |                                      | $V_{\text{CC}} = 6 \text{ V}$   | 0   |     |      |

**SN54HC273, SN74HC273**

SCLS136E – DECEMBER 1982 – REVISED JULY 2016

[www.ti.com](http://www.ti.com)

## 6.11 Switching Characteristics

 $T_A = 25^\circ\text{C}$  and  $C_L = 50\text{ pF}$  (unless otherwise noted; see [Figure 2](#))

| PARAMETER        | TEST CONDITIONS                                      | MIN                            | TYP | MAX | UNIT |
|------------------|------------------------------------------------------|--------------------------------|-----|-----|------|
| $f_{\text{max}}$ |                                                      | $V_{\text{CC}} = 2\text{ V}$   | 5   | 11  | MHz  |
|                  |                                                      | $V_{\text{CC}} = 4.5\text{ V}$ | 27  | 50  |      |
|                  |                                                      | $V_{\text{CC}} = 6\text{ V}$   | 32  | 60  |      |
| $t_{\text{PHL}}$ | From $\overline{\text{CLR}}$ (input) to any (output) | $V_{\text{CC}} = 2\text{ V}$   |     | 55  | ns   |
|                  |                                                      | $V_{\text{CC}} = 4.5\text{ V}$ |     | 15  |      |
|                  |                                                      | $V_{\text{CC}} = 6\text{ V}$   |     | 12  |      |
| $t_{\text{pd}}$  | From CLK (input) to any (output)                     | $V_{\text{CC}} = 2\text{ V}$   |     | 56  | ns   |
|                  |                                                      | $V_{\text{CC}} = 4.5\text{ V}$ |     | 15  |      |
|                  |                                                      | $V_{\text{CC}} = 6\text{ V}$   |     | 13  |      |
| $t_t$            | To any (output)                                      | $V_{\text{CC}} = 2\text{ V}$   |     | 38  | ns   |
|                  |                                                      | $V_{\text{CC}} = 4.5\text{ V}$ |     | 8   |      |
|                  |                                                      | $V_{\text{CC}} = 6\text{ V}$   |     | 6   |      |

## 6.12 Switching Characteristics – SN54HC273

over recommended operating free-air temperature range,  $C_L = 50\text{ pF}$  (unless otherwise noted; see [Figure 2](#))

| PARAMETER        | TEST CONDITIONS                                      |                         | MIN | MAX | UNIT |
|------------------|------------------------------------------------------|-------------------------|-----|-----|------|
| f <sub>max</sub> |                                                      | V <sub>CC</sub> = 2 V   | 4   | MHz |      |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 18  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 21  |     |      |
| t <sub>PHL</sub> | From $\overline{\text{CLR}}$ (input) to any (output) | V <sub>CC</sub> = 2 V   | 240 | ns  |      |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 48  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 41  |     |      |
| t <sub>pd</sub>  | From CLK (input) to any (output)                     | V <sub>CC</sub> = 2 V   | 240 | ns  |      |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 48  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 41  |     |      |
| t <sub>i</sub>   | To any (output)                                      | V <sub>CC</sub> = 2 V   | 110 | ns  |      |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 22  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 19  |     |      |

## 6.13 Switching Characteristics – SN74HC273

over recommended operating free-air temperature range,  $C_L = 50\text{ pF}$  (unless otherwise noted; see [Figure 2](#))

| PARAMETER        | TEST CONDITIONS                                      |                         | MIN | MAX | UNIT |
|------------------|------------------------------------------------------|-------------------------|-----|-----|------|
| f <sub>max</sub> |                                                      | V <sub>CC</sub> = 2 V   | 4   | 21  | MHz  |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 21  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 25  |     |      |
| t <sub>PHL</sub> | From $\overline{\text{CLR}}$ (input) to any (output) | V <sub>CC</sub> = 2 V   | 200 | 40  | ns   |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 40  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 34  |     |      |
| t <sub>pd</sub>  | From CLK (input) to any (output)                     | V <sub>CC</sub> = 2 V   | 200 | 40  | ns   |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 40  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 34  |     |      |
| t <sub>i</sub>   | To any (output)                                      | V <sub>CC</sub> = 2 V   | 95  | 19  | ns   |
|                  |                                                      | V <sub>CC</sub> = 4.5 V | 19  |     |      |
|                  |                                                      | V <sub>CC</sub> = 6 V   | 16  |     |      |

## 6.14 Operating Characteristics

$T_A = 25^\circ\text{C}$

| PARAMETER                                            | TEST CONDITIONS | TYP | UNIT |
|------------------------------------------------------|-----------------|-----|------|
| $C_{pd}$ Power dissipation capacitance per flip-flop | No load         | 35  | pF   |

## 6.15 Typical Characteristics





Figure 1. Max  $t_{pd}$  vs  $V_{CC}$

## 7 Parameter Measurement Information



- NOTES:
- $C_L$  includes probe and test-fixture capacitance.
  - Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1 \text{ MHz}$ ,  $Z_O = 50 \Omega$ ,  $t_r = 6 \text{ ns}$ ,  $t_f = 6 \text{ ns}$ .
  - For clock inputs,  $f_{max}$  is measured when the input duty cycle is 50%.
  - The outputs are measured one at a time with one input transition per measurement.
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .


**Figure 2. Load Circuit and Voltage Waveforms**

## 8 Detailed Description

### 8.1 Overview

The SNx4HC273 contains eight flip-flops with single-rail outputs with individual data input to each flip-flop. The outputs can drive up to 10 LSTTL loads. The device has direct active low clear input.

### 8.2 Functional Block Diagram



### 8.3 Feature Description

The SNx4HC273 has low power consumption with a maximum  $I_{CC}$  of 80  $\mu$ A.

The typical  $t_{pd}$  for the SNx4HC273 is 12 ns and the output drive is  $\pm 4$  mA at 5 V.

The SNx4HC273 also has very low input current, with the maximum set at 1  $\mu$ A.

### 8.4 Device Functional Modes

Table 1 lists the functional modes of the SNx4HC273.

**Table 1. Function Table (Each Flip-Flop)**

| INPUTS                  |            |   | OUTPUT<br>Q |
|-------------------------|------------|---|-------------|
| $\overline{\text{CLR}}$ | CLK        | D |             |
| L                       | X          | X | L           |
| H                       | $\uparrow$ | H | H           |
| H                       | $\uparrow$ | L | L           |
| H                       | L          | X | $Q_0$       |

## 9 Application and Implementation


### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 9.1 Application Information

The SNx4HC273 is octal D Flip flop with active low clear input. It has low input current and low power consumption. The D flip-flop can be used as a Toggle flip flop using an XOR gate at the input. The output toggles from the previous state whenever the T input is high.

### 9.2 Typical Application



Copyright © 2016, Texas Instruments Incorporated

#### 9.2.1 Design Requirements


This SNx4Hc273 device uses CMOS technology and has balanced output drive.

#### 9.2.2 Detailed Design Procedure

1. Recommended input conditions:
  - Rise time and fall time specifications: see ( $\Delta t/\Delta V$ ) in [Recommended Operating Conditions](#).
  - Specified high and low levels: see ( $V_{IH}$  and  $V_{IL}$ ) in [Recommended Operating Conditions](#).
  - Inputs are not overvoltage tolerant and must not be above any valid  $V_{CC}$  as per [Recommended Operating Conditions](#).
2. Absolute maximum output conditions:
  - Continuous output currents must not exceed ( $I_O$  max) per output and must not exceed total current (continuous current through  $V_{CC}$  or GND) for the part. These limits are located in the [Absolute Maximum Ratings](#).
  - Outputs must not be pulled above  $V_{CC}$ .

## Typical Application (continued)

### 9.2.3 Application Curve



**Figure 3. Max Transition Time vs V<sub>CC</sub>**

## 10 Power Supply Recommendations

The power supply can be any voltage between the minimum and maximum supply voltage rating located in [Recommended Operating Conditions](#).

Each V<sub>CC</sub> pin must have a good bypass capacitor to prevent power disturbance. For devices with a single supply, TI recommends a 0.1-μF capacitor. If there are multiple V<sub>CC</sub> pins, TI recommends a 0.01-μF or 0.022-μF capacitor for each power pin. It is ok to parallel multiple bypass capacitors to reject different frequencies of noise. 0.1-μF and 1-μF capacitors are commonly used in parallel. The bypass capacitor must be installed as close to the power pin as possible for best results.


## 11 Layout

### 11.1 Layout Guidelines

When using multiple bit logic devices inputs must not ever float. In many cases, functions or parts of functions of digital logic devices are unused; for example, when only two inputs of a triple-input AND gate are used or only 3 of the 4 buffer gates are used. Such input pins must not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. Specified below are the rules that must be observed under all circumstances:

- All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating.
- The logic level that must be applied to any particular unused input depends on the function of the device.
- Generally they are tied to GND or V<sub>CC</sub> whichever make more sense or is more convenient.

### 11.2 Layout Example



**Figure 4. SNx4HC273 Layout**

## 12 Device and Documentation Support

### 12.1 Documentation Support

#### 12.1.1 Related Documentation

For related documentation, see the following:

[Implications of Slow or Floating CMOS Inputs](#)

### 12.2 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

**Table 2. Related Links**

| PARTS     | PRODUCT FOLDER             | SAMPLE & BUY               | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|-----------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| SN54HC273 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| SN74HC273 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

### 12.3 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 12.4 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

**TI E2E™ Online Community** *TI's Engineer-to-Engineer (E2E) Community*. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

### 12.5 Trademarks

E2E is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

### 12.6 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 12.7 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical packaging and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser based versions of this data sheet, refer to the left hand navigation.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)            | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|------------------------------------|-------------------------|
| 5962-8409901VRA  | ACTIVE        | CDIP         | J                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | 5962-8409901VR<br>A<br>SNV54HC273J | <a href="#">Samples</a> |
| 5962-8409901VSA  | ACTIVE        | CFP          | W                  | 20   | 25             | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | 5962-8409901VS<br>A<br>SNV54HC273W | <a href="#">Samples</a> |
| 84099012A        | ACTIVE        | LCCC         | FK                 | 20   | 1              | TBD                        | POST-PLATE              | N / A for Pkg Type   | -55 to 125   | 84099012A<br>SNJ54HC<br>273FK      | <a href="#">Samples</a> |
| 8409901RA        | ACTIVE        | CDIP         | J                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | 8409901RA<br>SNJ54HC273J           | <a href="#">Samples</a> |
| 8409901SA        | ACTIVE        | CFP          | W                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | 8409901SA<br>SNJ54HC273W           | <a href="#">Samples</a> |
| JM38510/65601BRA | ACTIVE        | CDIP         | J                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65601BRA               | <a href="#">Samples</a> |
| JM38510/65601BSA | ACTIVE        | CFP          | W                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65601BSA               | <a href="#">Samples</a> |
| M38510/65601BRA  | ACTIVE        | CDIP         | J                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65601BRA               | <a href="#">Samples</a> |
| M38510/65601BSA  | ACTIVE        | CFP          | W                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65601BSA               | <a href="#">Samples</a> |
| SN54HC273J       | ACTIVE        | CDIP         | J                  | 20   | 1              | TBD                        | Call TI                 | N / A for Pkg Type   | -55 to 125   | SN54HC273J                         | <a href="#">Samples</a> |
| SN74HC273DBR     | ACTIVE        | SSOP         | DB                 | 20   | 2000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                              | <a href="#">Samples</a> |
| SN74HC273DW      | ACTIVE        | SOIC         | DW                 | 20   | 25             | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                              | <a href="#">Samples</a> |
| SN74HC273DWR     | ACTIVE        | SOIC         | DW                 | 20   | 2000           | Green (RoHS<br>& no Sb/Br) | NIPDAU   SN             | Level-1-260C-UNLIM   | -40 to 85    | HC273                              | <a href="#">Samples</a> |
| SN74HC273DWRE4   | ACTIVE        | SOIC         | DW                 | 20   | 2000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                              | <a href="#">Samples</a> |
| SN74HC273DWRG4   | ACTIVE        | SOIC         | DW                 | 20   | 2000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                              | <a href="#">Samples</a> |
| SN74HC273N       | ACTIVE        | PDIP         | N                  | 20   | 20             | Pb-Free<br>(RoHS)          | NIPDAU                  | N / A for Pkg Type   | -40 to 85    | SN74HC273N                         | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)         | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)       | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------------|-------------------------|
| SN74HC273NE4     | ACTIVE        | PDIP         | N               | 20   | 20          | Pb-Free (RoHS)          | NIPDAU                  | N / A for Pkg Type   | -40 to 85    | SN74HC273N                    | <a href="#">Samples</a> |
| SN74HC273NSR     | ACTIVE        | SO           | NS              | 20   | 2000        | Green (RoHS & no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                         | <a href="#">Samples</a> |
| SN74HC273PW      | ACTIVE        | TSSOP        | PW              | 20   | 70          | Green (RoHS & no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                         | <a href="#">Samples</a> |
| SN74HC273PWR     | ACTIVE        | TSSOP        | PW              | 20   | 2000        | Green (RoHS & no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                         | <a href="#">Samples</a> |
| SN74HC273PWRG4   | ACTIVE        | TSSOP        | PW              | 20   | 2000        | Green (RoHS & no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                         | <a href="#">Samples</a> |
| SN74HC273PWT     | ACTIVE        | TSSOP        | PW              | 20   | 250         | Green (RoHS & no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 85    | HC273                         | <a href="#">Samples</a> |
| SNJ54HC273FK     | ACTIVE        | LCCC         | FK              | 20   | 1           | TBD                     | POST-PLATE              | N / A for Pkg Type   | -55 to 125   | 84099012A<br>SNJ54HC<br>273FK | <a href="#">Samples</a> |
| SNJ54HC273J      | ACTIVE        | CDIP         | J               | 20   | 1           | TBD                     | Call TI                 | N / A for Pkg Type   | -55 to 125   | 8409901RA<br>SNJ54HC273J      | <a href="#">Samples</a> |
| SNJ54HC273W      | ACTIVE        | CFP          | W               | 20   | 1           | TBD                     | Call TI                 | N / A for Pkg Type   | -55 to 125   | 8409901SA<br>SNJ54HC273W      | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54HC273, SN54HC273-SP, SN74HC273 :**

- Catalog: [SN74HC273](#), [SN54HC273](#)
- Automotive: [SN74HC273-Q1](#), [SN74HC273-Q1](#)
- Military: [SN54HC273](#)
- Space: [SN54HC273-SP](#)

**NOTE: Qualified Version Definitions:**


- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Military - QML certified for Military and Defense Applications
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74HC273DBR   | SSOP         | DB              | 20   | 2000 | 330.0              | 16.4               | 8.2     | 7.5     | 2.5     | 12.0    | 16.0   | Q1            |
| SN74HC273DWR   | SOIC         | DW              | 20   | 2000 | 330.0              | 24.4               | 10.8    | 13.3    | 2.7     | 12.0    | 24.0   | Q1            |
| SN74HC273DWRG4 | SOIC         | DW              | 20   | 2000 | 330.0              | 24.4               | 10.8    | 13.3    | 2.7     | 12.0    | 24.0   | Q1            |
| SN74HC273NSR   | SO           | NS              | 20   | 2000 | 330.0              | 24.4               | 8.4     | 13.0    | 2.5     | 12.0    | 24.0   | Q1            |
| SN74HC273PWR   | TSSOP        | PW              | 20   | 2000 | 330.0              | 16.4               | 6.95    | 7.0     | 1.4     | 8.0     | 16.0   | Q1            |
| SN74HC273PWT   | TSSOP        | PW              | 20   | 250  | 330.0              | 16.4               | 6.95    | 7.1     | 1.6     | 8.0     | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74HC273DBR   | SSOP         | DB              | 20   | 2000 | 367.0       | 367.0      | 38.0        |
| SN74HC273DWR   | SOIC         | DW              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| SN74HC273DWRG4 | SOIC         | DW              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| SN74HC273NSR   | SO           | NS              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| SN74HC273PWR   | TSSOP        | PW              | 20   | 2000 | 367.0       | 367.0      | 38.0        |
| SN74HC273PWT   | TSSOP        | PW              | 20   | 250  | 367.0       | 367.0      | 38.0        |

W (R-GDFP-F20)

CERAMIC DUAL FLATPACK




## NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a ceramic lid using glass frit.
- D. Index point is provided on cap for terminal identification only.
- E. Falls within Mil-Std 1835 GDFP2-F20



FK (S-CQCC-N\*\*)

LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN





| NO. OF<br>TERMINALS<br>** | A                |                  | B                |                  |
|---------------------------|------------------|------------------|------------------|------------------|
|                           | MIN              | MAX              | MIN              | MAX              |
| 20                        | 0.342<br>(8,69)  | 0.358<br>(9,09)  | 0.307<br>(7,80)  | 0.358<br>(9,09)  |
| 28                        | 0.442<br>(11,23) | 0.458<br>(11,63) | 0.406<br>(10,31) | 0.458<br>(11,63) |
| 44                        | 0.640<br>(16,26) | 0.660<br>(16,76) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 52                        | 0.740<br>(18,78) | 0.761<br>(19,32) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 68                        | 0.938<br>(23,83) | 0.962<br>(24,43) | 0.850<br>(21,6)  | 0.858<br>(21,8)  |
| 84                        | 1.141<br>(28,99) | 1.165<br>(29,59) | 1.047<br>(26,6)  | 1.063<br>(27,0)  |



4040140/D 01/11

- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a metal lid.
  - Falls within JEDEC MS-004



4214851/B 08/2019

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-150.

# EXAMPLE BOARD LAYOUT



DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4214851/B 08/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4214851/B 08/2019

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



| DIM \ PINS ** | 14    | 16    | 20    | 24    |
|---------------|-------|-------|-------|-------|
| A MAX         | 10,50 | 10,50 | 12,90 | 15,30 |
| A MIN         | 9,90  | 9,90  | 12,30 | 14,70 |


4040062/C 03/03

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.


J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |




4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

PW (R-PDSO-G20)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G20)

PLASTIC SMALL OUTLINE




- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate design.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.


## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE




| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.



4220724/A 05/2016

## NOTES:


1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
5. Reference JEDEC registration MS-013.

# EXAMPLE BOARD LAYOUT



DW0020A

SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE  
SCALE:6X



SOLDER MASK DETAILS

4220724/A 05/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DW0020A

SOIC - 2.65 mm max height

SOIC



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:6X

4220724/A 05/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2020, Texas Instruments Incorporated