



LEADSUN
hv-semi.com

High Voltage Diode

SPF05-15
15kv 50mA 80nS

FEATURES


- Fast reverse recovery time
- SMA Package
- Tj:-40°C~+120°C
- ROHS compliant



Device Electrical Characteristics(Ta=25°C Unless otherwise noted)

Items	Symbol	Conditions	Value	Unit
Max. Repetitive Peak Reverse Voltage	V_{RRM}	$I_R=0.5\mu A$	15	KV
Average Forward Current max.	$I_{F(AV)}$	Ta=55°C	50	mA
Max. Forward Voltage Drop	V_{FM}	$I_F=I_{F(AV)}$	29	V
Max. Surge Current	I_{FSM}	10msec, half sine	5.0	A
Max. Reverse Current	I_{RM1}	$V_R=V_{RRM}$	0.5	μA
Max. High Temperature Reverse Current	I_{RM2}	Ta=100°C $V_R=V_{RRM}$	5	μA
Max. Reverse Recovery Time	trr	$I_F=20mA$, $I_R=40mA$ $I_{RR}=10mA$	80	nS
Max. Temperature Junction	T_J		120	°C
Storage Temperature Range	Tstg		-55to160	°C

Mechanical Data



LEADSUN ELECTRONICS

TEL: +86-412-2660889 FAX: +86-412-2663889
Email: leadsun@hv-semi.com Http: // www.hv-semi.com