



SR120 THRU SR1200

SCHOTTKY BARRIER RECTIFIERS

FEATURES

- High current capability
- High surge current capability
- Low forward voltage drop
- Exceeds environmental standards of MIL-S-19500/228
- For use in low voltage, high frequency inverters free wheeling, and porlarlity protection applications

MECHANICAL DATA

Case: Molded plastic, DO-41

Epoxy: UL 94V-O rate flame retardant


Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed

Polarity: Color band denotes cathode end

Mounting position: Any

Weight: 0.012ounce, 0.33gram

DO-41



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	SR120	SR140	SR150	SR160	SR180	SR1100	SR1500	SR1200	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	40	50	60	80	100	150	200	Volts
Maximum RMS Voltage	V _{RMS}	14	28	35	42	56	70	105	140	Volts
Maximum DC Blocking Voltage	V _{DC}	20	40	50	60	80	100	150	200	Volts
Maximum Average Forward Rectified Current 375"(9.5mm) Lead Length	I _(AV)	1.0								Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	30								Amp
Maximum Forward Voltage at 1.0A DC and 25	V _F	0.55		0.70		0.85		0.95		Volts
Maximum Reverse Current at T _A =25 at Rated DC Blocking Voltage T _A =100	I _R	0.5 10								mAmp
Typical Junction Capacitance (Note 1)	C _J	110								pF
Typical Thermal Resistance (Note 2)	R _{θJA}	50								/W
Operating Junction Temperature Range	T _J	-55 to +125		-55 to +150						
Storage Temperature Range	T _{stg}	-55 to +150								

NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- Thermal Resistance From Junction to Ambient 0 375"(9.5mm) lead length P.C.B. Mounted with 0.22x0.22" (5.5x5.5mm) copper pads





SR120 THRU SR1200 SCHOTTKY BARRIER RECTIFIERS

RATINGS AND CHARACTERISTIC CURVES

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD
CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD
SURGE CURRENT




FIG.5 - TYPICAL REVERSE
CHARACTERISTICS




FIG.4-TYPICAL JUNCTION CAPACITANCE

