



SCHOTTKY BARRIER RECTIFIER

SR2020 THRU SR20100

VOLTAGE RANGE

20 to 100 Volts

CURRENT


20.0 Ampere

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low forward voltage, high current capability
- High surge capacity
- For use in low voltage high frequency inverters, Free wheeling, and polarity protection applications

MECHANICAL DATA

- Case: TO-220AC molded plastic
- Terminals: Lead solderable per MIL-STD-202 Method 208
- Polarity: as marked
- Mounting position: Any
- Weight: 0.08ounce, 2.24 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	SR 2020	SR 2030	SR 2035	SR 2040	SR 2045	SR 2050	SR 2060	SR 2080	SR 20100	SR 20150	SR 20200	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum RMS Voltage		V _{RMS}	14	21	25	28	32	35	42	56	70	105	140	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum Average Forward Rectified Current At Tc=100℃		I _(AV)	20.0											Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)		I _{FSM}	150											Amps
Maximum Forward Voltage at 20.0A per element		V _F	0.65					0.75		0.85				Volts
Maximum DC Reverse Current at rated DC Blocking Voltage per element	T _C = 25℃	I _R	1.0											mA
	T _C = 100℃		100											
Typical Junction Capacitance(Note2)		C _J	700											pF
Typical Thermal Resistance (Note 1)		R _{θJC}	2.0											℃/W
Operating Storage Temperature Range		T _J T _{STG}	(-55 to +150)											℃

Notes:

- Thermal Resistance Junction to CASE
- Measured at $V_R=4\text{V}$ and $f=1\text{MHz}$



SCHOTTKY BARRIER RECTIFIER

SR2020 THRU SR20100

VOLTAGE RANGE 20 to 100 Volts
CURRENT 20.0 Amperes

RATING AND CHARACTERISTIC CURVES SR12020 THRU SR20100

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC




FIG.2-TYPICAL REVERSE CHARACTERISTICS




FIG.4-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.5-TYPICAL JUNCTION CAPACITANCE

