


表面安装肖特基二极管
反向电压 20 ---100 V
正向电流 3.0 A

Surface Mount Schottky Barrier Rectifier
Reverse Voltage 20 to 100 V
Forward Current 3.0 A



特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 高温焊接保证 High temperature soldering guaranteed:
260℃/10 秒, 0.375" (9.5mm)引线长度。
260℃/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线 and 管体皆符合RoHS标准 。
Lead and body according with RoHS standard

机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25℃ 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

	符号 Symbols	SS32A	SS34A	SS36A	SS310A	单位 Unit
最大峰值反向电压 Maximum repetitive peak reverse voltage	V_{RRM}	20	40	60	100	V
最大反向有效值电压 Maximum RMS voltage	$V_{R(RMS)}$	14	28	42	70	V
最大直流阻断电压 Maximum DC blocking voltage	V_{DC}	20	40	60	100	V
最大正向平均整流电流 Maximum average forward rectified current	I_{FM}	3.0				A
最大正向电压降 Maximum forward voltage	V_F	0.50		0.7	0.85	V
正向峰值浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I_{FSM}	80				A
最大反向漏电流 Maximum reverse current	I_R	0.5 10				mA
典型热阻 Typical thermal resistance	$R_{\theta JA}$	55				℃/W
典型结电容 Type junction capacitance	C_j	15				pF
工作结温 Operating junction	T_j	-55 --- +125		-55 --- +150		℃
存储温度 Storage temperature range	T_{STG}	-55 --- +150				℃

特性曲线 Characteristic Curves

