
SS32B THRU SS310B

肖特基二极管 Schottky Rectifier

■特征 Features

- I_o 3.0A
- V_{RRM} 20V-100V
- 耐正向浪涌电流能力高
  High surge current capability
- 封装：模压塑料
  Cases: Molded plastic

■外形尺寸和印记 Outline Dimensions and Mark



■用途 Applications

- 整流用 Rectifier

■极限值（绝对最大额定值）
Limiting Values (Absolute Maximum Rating)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Conditions	SS3						
				2B	3B	4B	5B	6B	9B	10B
反向重复峰值电压 Repetitive Peak Reverse Voltage	V_{RRM}	V		20	30	40	50	60	90	100
正向平均电流 Average Forward Current	$I_{F(AV)}$	A	正弦半波 60Hz，电阻负载，TL(Fig.1) 60HZ Half-sine wave, Resistance load, TL(Fig.1)	3.0						
正向（不重复）浪涌电流 Surge(Non-repetitive)Forward Current	I_{FSM}	A	正弦半波 60Hz，一个周期，Ta=25℃ 60Hz Half-sine wave ,1 cycle , Ta =25℃	100						
结温 Junction Temperature	T_J	℃		-55~+125			-55~+150			
储存温度 Storage Temperature	T_{STG}	℃		-55 ~ +150						

■电特性 （Ta=25℃ 除非另有规定）
Electrical Characteristics (T_a=25℃ Unless otherwise specified）

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition		SS3						
					2B	3B	4B	5B	6B	9B	10B
正向峰值电压 Peak Forward Voltage	V_F	V	I_F=3.0A		0.50			0.70		0.85	
反向漏电流 Peak Reverse Current	I_{RRM1}	mA	$V_{RM}=V_{RRM}$	Ta =25℃	0.5					0.1	
	I_{RRM2}			Ta =100℃	10			5.0			
热阻(典型) Thermal Resistance(Typical)	$R_{\theta J-A}$	℃/W	结和环境之间 Between junction and ambient		55[1)]						
	$R_{\theta J-L}$		结和终端之间 Between junction and terminal		17[1)]						

备注：Notes:

1) 热阻从结到环境及从结到引线，在电路板的0.6" x 0.6" (16毫米 x 16毫米)铜垫片区
Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■特性曲线（典型） Characteristics(Typical)

图1：正向电流降额曲线
FIG.1: FORWARD CURRENT DERATING CURVE




图2：最大正向浪涌冲击耐受力
FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




图3: 典型正向特性曲线
FIG.3: TYPICAL FORWARD CHARACTERISTICS




图4：典型反向特性曲线
FIG.4：TYPICAL REVERSE CHARACTERISTICS

