

Pb Free Plating Product



SS52 thru SS515

5.0 AMP. SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

Features


- ✧ For surface mounted application
- ✧ Metal to silicon rectifier, majority carrier conduction
- ✧ Low forward voltage drop
- ✧ Easy pick and place
- ✧ High surge current capability
- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-0
- ✧ Epitaxial construction
- ✧ High temperature soldering: 260°C / 10 seconds at terminals

Mechanical Data

- ✧ Case: Molded plastic
- ✧ Terminals: Pure tin plated, lead free.
- ✧ Polarity: Indicated by cathode band
- ✧ Packaging: 16mm tape per EIA STD RS-481
- ✧ Weight: 0.1 gram

SMC/DO-214AB

Unit: inch (mm)



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SS 52	SS 53	SS 54	SS 55	SS 56	SS 59	SS 510	SS 515	Units	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	90	100	150	V	
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	63	70	105	V	
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	90	100	150	V	
Maximum Average Forward Rectified Current at T _L (See Fig. 1)	I _(AV)	5.0								A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	120								A	
Maximum Instantaneous Forward Voltage @ 5.0A	V _F	0.55			0.75		0.85		0.95	V	
Maximum DC Reverse Current (Note 1) @ T _A =25 °C at Rated DC Blocking Voltage @ T _A =125 °C	I _R	0.5					0.3			mA	
		20			10		5.0			mA	
Typical Thermal Resistance (Note 2)	R _{θJL} R _{θJA}	17 55								°C/W	
Operating Temperature Range	T _J	-55 to +125			-55 to +150						°C
Storage Temperature Range	T _{STG}	-55 to +150								°C	

Notes: 1. Pulse Test with PW=300 usec, 1% Duty Cycle
2. Measured on P.C.Board with 0.6" x 0.6" (16mm x 16mm) Copper Pad Areas.

RATINGS AND CHARACTERISTIC CURVES (SS52 THRU SS515)

