# SS6P4C


Vishay General Semiconductor

# High Current Density Surface Mount Dual Common-Cathode Schottky Rectifier

eSMP™ Series




TO-277A (SMPC)




| PRIMARY CHARACTERISTICS | |
|---|---|
| $I_{F(AV)}$ | 2 x 3.0 A |
| $V_{RRM}$ | 40 V |
| $I_{FSM}$ | 70 A |
| $E_{AS}$ | 20 mJ |
| $V_F$ at $I_F$ = 3 A | 0.53 V |
| $T_J$ max. | 150 °C |

## FEATURES

- Very low profile - typical height of 1.1 mm
- Ideal for automated placement
- Low forward voltage drop, low power losses
- High efficiency
- Low thermal resistance
- Meets MSL level 1, per J-STD-020
- AEC-Q101 qualified
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- **Halogen-free according to IEC 61249-2-21 definition**

AUTOMOTIVE GRADE Available

RoHS COMPLIANT

HALOGEN FREE

## MECHANICAL DATA

**Case:** TO-277A (SMPC)
Molding compound meets UL 94 V-0 flammability rating
Base P/N-M3 - halogen-free, RoHS compliant, and commercial grade
Base P/NHM3 - halogen-free, RoHS compliant, and automotive grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102
M3 suffix meets JESD 201 class 1A whisker test, HM3 suffix meets JESD 201 class 2 whisker test

## TYPICAL APPLICATIONS

For use in low voltage high frequency inverters, freewheeling, DC/DC converters and polarity protection applications.

**MAXIMUM RATINGS** ($T_A$ = 25 °C unless otherwise noted)

| PARAMETER | | SYMBOL | SS6P4C | UNIT |
|---|---|---|---|---|
| Device marking code | | | S64C | |
| Maximum repetitive peak reverse voltage | | $V_{RRM}$ | 40 | V |
| Maximum average forward rectified current (fig. 1) | total devive | $I_{F(AV)}$ | 6.0 | A |
| | per diode | | 3.0 | |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load | | $I_{FSM}$ | 70 | A |
| Non-repetitive avalanche energy at 25 °C, $I_{AS}$ = 2 A per diode | | $E_{AS}$ | 20 | |
| Operating junction and storage temperature range | | $T_J$, $T_{STG}$ | - 55 to + 150 | °C |


For technical questions within your region, please contact one of the following:
DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# SS6P4C

Vishay General Semiconductor

| ELECTRICAL CHARACTERISTICS ($T_A$ = 25 °C unless otherwise noted) | | | | | | |
|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITIONS** | | **SYMBOL** | **TYP.** | **MAX.** | **UNIT** |
| Instantaneous forward voltage per diode | $I_F$ = 1.5 A | $T_A$ = 25 °C | $V_F$ (1) | 0.47 | - | V |
| | $I_F$ = 3.0 A | | | 0.57 | 0.65 | |
| | $I_F$ = 1.5 A | $T_A$ = 125 °C | | 0.40 | - | |
| | $I_F$ = 3.0 A | | | 0.53 | 0.60 | |
| Reverse current per diode | Rated $V_R$ | $T_A$ = 25 °C | $I_R$ (2) | 17 | 200 | µA |
| | | $T_A$ = 125 °C | | 6 | 20 | mA |
| Typical junction capacitance per diode | 4.0 V, 1 MHz | | $C_J$ | 100 | - | pF |

**Notes**

(1) Pulse test: 300 µs pulse width, 1 % duty cycle

(2) Pulse test: Pulse width ≤ 40 ms

| THERMAL CHARACTERISTICS ($T_A$ = 25 °C unless otherwise specified) | | | |
|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **SS6P4C** | **UNIT** |
| Typical thermal resistance per diode | $R_{\theta JA}$ (1) | 80 | °C/W |
| | $R_{\theta JL}$ | 4 | |

**Note**

(1) Units mounted on recommended PCB 1 oz. pad layout

| ORDERING INFORMATION (Example) | | | | |
|---|---|---|---|---|
| **PREFERRED P/N** | **UNIT WEIGHT (g)** | **PACKAGE CODE** | **BASE QUANTITY** | **DELIVERY MODE** |
| SS6P4C-M3/86A | 0.10 | 86A | 1500 | 7" diameter plastic tape and reel |
| SS6P4C-M3/87A | 0.10 | 87A | 6500 | 13" diameter plastic tape and reel |
| SS6P4CHM3/86A (1) | 0.10 | 86A | 1500 | 7" diameter plastic tape and reel |
| SS6P4CHM3/87A (1) | 0.10 | 87A | 6500 | 13" diameter plastic tape and reel |

**Note**

(1) Automotive grade



For technical questions within your region, please contact one of the following:
DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

Document Number: 89114
Revision: 10-May-11

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## RATINGS AND CHARACTERISTICS CURVES

($T_A$ = 25 °C unless otherwise noted)





Fig. 1 - Maximum Forward Current Derating Curve





Fig. 4 - Typical Reverse Leakage Characteristics Per Diode





Fig. 2 - Forward Power Loss Characteristics Per Diode





Fig. 5 - Typical Junction Capacitance Per Diode





Fig. 3 - Typical Instantaneous Forward Characteristics Per Diode




This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# SS6P4C

Vishay General Semiconductor

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

### TO-277A (SMPC)




Conform to JEDEC TO-277A



For technical questions within your region, please contact one of the following:
DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

Document Number: 89114
Revision: 10-May-11

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.