Elektronische Bauelemente

SSE90P06-08P

-90A , -60V , $R_{DS(ON)}$ 12mΩ

P-Channel Enhancement Mode MOSFET

RoHS Compliant Product

A suffix of "-C" specifies halogen and lead-free

DESCRIPTION

These miniature surface mount MOSFETs utilize a high cell density trench process to provide low $R_{DS(on)}$ and to ensure minimal power loss and heat dissipation.


FEATURES

- Low $R_{DS(on)}$ provides higher efficiency and extends battery life.
- Low thermal impedance copper leadframe TO-220P saves board space.
- Fast Switch Speed.
- High performance trench technology.


APPLICATION

DC-DC converters and power management in portable and battery-powered products such as computers, printers, PCMCIA cards, cellular and cordless telephones.

TO-220P



P-Channel



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	7.90	8.10	M	-	1.50
B	9.45	9.65	N	0.75	0.95
C	9.87	10.47	O	0.66	0.86
D	-	11.50	P	13.50	14.50
E	1.06	1.46	Q	2.44	3.44
F	2.60	3.00	R	3.50	3.70
G	6.30	6.70	S	1.15	1.45
H	8.35	8.75	T	4.30	4.70
I	14.7	15.3	U	-	2.7
J	1.60 Typ.		V	1.89	3.09
K	1.10	1.30	W	0.40	0.60
L	1.17	1.37	X	2.60	3.60

ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise specified)

Parameter		Symbol	Ratings	Unit
Drain-Source Voltage		V_{DS}	-60	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current [1]	T_C=25°C	I_D	-90	A
Pulsed Drain Current [2]		I_{DM}	-390	A
Continuous Source Current (Diode Conduction) [1]		I_S	-110	A
Power Dissipation [1]	T_C=25°C	P_D	300	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~175	°C
Thermal Resistance Rating				
Maximum Junction to Ambient [1]		$R_{\theta JA}$	62.5	°C / W
Maximum Junction to Case		$R_{\theta JC}$	0.5	

Notes:

1 Package Limited.

2 Pulse width limited by maximum junction temperature.

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Teat Conditions
Static						
Gate-Threshold Voltage	$V_{GS(th)}$	-1	-	-	V	V_{DS}=V_{GS}, I_D= -250μA
Gate-Body Leakage	I_{GSS}	-	-	±100	nA	V_{DS}=0, V_{GS}= -20V
Zero Gate Voltage Drain Current	I_{DSS}	-	-	-1	μA	V_{DS}= -48V, V_{GS}=0
		-	-	-25		V_{DS}= -48V, V_{GS}=0, T_J=55°C
On-State Drain Current [1]	$I_{D(on)}$	-120	-	-	A	V_{DS}= -5V, V_{GS}= -10V
Drain-Source On-Resistance [1]	$R_{DS(ON)}$	-	-	12	mΩ	V_{GS}= -10V, I_D= -2A
		-	-	14		V_{GS}= -4.5V, I_D= -2A
Forward Transconductance [1]	g_{fs}	-	30	-	S	V_{DS}= -15V, I_D= -2A
Diode Forward Voltage	V_{SD}	-	-1.1	-	V	I_S= -2A, V_{GS}=0
Dynamic [2]						
Total Gate Charge	Q_g	-	100	-	nC	V_{DS}= -15V, V_{GS}= -4.5V, I_D= -2A
Gate-Source Charge	Q_{gs}	-	30	-		
Gate-Drain Charge	Q_{gd}	-	40	-		
Turn-on Delay Time	$T_{d(on)}$	-	20	-	nS	V_{DD}= -25V, V_{GEN}= -10V, R_L=25Ω, I_D= -34A
Rise Time	T_r	-	20	-		
Turn-off Delay Time	$T_{d(off)}$	-	300	-		
Fall Time	T_f	-	100	-		

Notes:
1 Pulse test：PW ≦ 300 μs duty cycle ≦ 2%.
2 Guaranteed by design, not subject to production testing.