



SSM3K333R

Preliminary

Power MOSFET

6A, 30V N-CHANNEL POWER MOSFET

DESCRIPTION



The UTC **SSM3K333R** is an N-channel power MOSFET using UTC's advanced technology to provide customers with a minimum on-state resistance and superior switching performance.

The UTC **SSM3K333R** is usually used in power management switching applications.

FEATURES

- * $R_{DS(ON)} < 42m\Omega$ @ $V_{GS}=4.5V$
- * $R_{DS(ON)} < 28m\Omega$ @ $V_{GS}=10V$
- * High switching speed
- * Low gate charge (Typ.=3.4nC)
- * Low C_{RSS} (Typ.=28pF)

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
SSM3K333RL-AE3-R	SSM3K333RG-AE3-R	SOT-23	S	G	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

SSM3K333RL-AE3-R	(1)Packing Type (2)Package Type (3)Lead Free	(1) R: Tape Reel (2) AE3: SOT-23 (3) G: Halogen Free, L: Lead Free
------------------	--	--

MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	30	V
Gate-Source Voltage		V_{GSS}	± 20	V
Drain Current	Continuous	I_D (Note 2)	6	A
	Pulsed	I_{DM} (Note 2)	12	A
Power Dissipation		P_D (Note 3)	1	W
	$t=10\text{s}$		2	W
Channel Temperature		T_{CH}	150	$^\circ\text{C}$
Storage Temperature		T_{STG}	$-55\sim+150$	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. The channel temperature should not exceed 150°C during use.

3. Mounted on a FR4 board.(25.4mm×25.4mm×1.6mm, Cu Pad: 645mm²)



■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$I_D=10\text{mA}$, $V_{GS}=0\text{V}$	30			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=30\text{V}$, $V_{GS}=0\text{V}$			1	μA
Gate-Source Leakage Current	Forward	I_{GSS}	$V_{GS}=+20\text{V}$, $V_{DS}=0\text{V}$			+100	nA
	Reverse		$V_{GS}=-20\text{V}$, $V_{DS}=0\text{V}$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}$, $I_D=0.1\text{mA}$	1.3		2.5	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=4.5\text{V}$, $I_D=3\text{A}$ (Note 2)		25.7	42	m Ω
			$V_{GS}=10\text{V}$, $I_D=5\text{A}$ (Note 2)		18.7	28	m Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	$V_{GS}=0\text{V}$, $V_{DS}=15\text{V}$, $f=1.0\text{MHz}$		436		pF
Output Capacitance		C_{OSS}			77		pF
Reverse Transfer Capacitance		C_{RSS}			28		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	$V_{GS}=4.5\text{V}$, $V_{DD}=15\text{V}$, $I_D=6\text{A}$		3.4		nC
Gate to Source Charge		Q_{GS}			1.8		nC
Gate to Drain Charge		Q_{GD}			1.0		nC
Turn-ON Delay Time		$t_{D(ON)}$	$V_{DD}=15\text{V}$, $I_D=3\text{A}$, $V_{GS}=0\sim 4.5\text{V}$,		12		ns
Turn-OFF Delay Time		$t_{D(OFF)}$	$R_G=10\Omega$		9		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Drain-Source Diode Forward Voltage		V_{SD}	$I_{SD}=6\text{A}$, $V_{GS}=0\text{V}$		0.85	1.2	V

Notes: 1. The channel temperature should not exceed 150°C during use.

2. Pulse test

■ TEST CIRCUITS AND WAVEFORMS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.