

SpiceLED™

Like spice, its diminutive size is a stark contrast to its standout performance in terms of brightness, durability and reliability. Despite being the smallest in size yet the SpiceLED™ packs a powerful performance and is a highly reliable design device. Its versatility enables its application in automotive appliances, key-pad illumination, hand-held devices such as PDAs, notebooks, compact back-lighting applications, consumer appliances, office equipment, audio and video equipment.



Features:

- > High brightness surface mount LED.
- > Super wide viewing angle of 160°.
- > Equivalent to 0603 package outline. Copper lead-frame construction.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.



Applications:

- > Automotive: interior applications, eg: switches, telematics, climate control system, dashboard, etc.
- > Consumer Appliances: LCD illumination as in PDAs, LCD TV.
- > Communication: indicator and backlight in mobilephone.
- > Industrial: white goods (eg: Oven, microwave, etc.).



Optical Characteristics at Tj=25°C

Part Ordering Number	Color	Viewing Angle°	Luminous Intensity @ 2mA IV (mcd)	
			Min.	Typ. Max.
SSS-CLD-HJ2-1-I2	Super Red, 632 nm	160	2.80	4.50 7.20
SSO-CLD-JK2-1-I2	Orange, 605 nm	160	4.50	7.20 11.20
SSY-CLD-JK2-1-I2	Yellow, 587 nm	160	4.50	7.20 11.20

NOTE

1. All part number above comes in a quantity of 3000 units per reel.
2. Other luminous intensity groups are also available upon request
3. Luminous intensity is measured with an accuracy of $\pm 11\%$.
4. Wavelength binning is carried for all units as per the wavelength-binning table. Only one wavelength group is allowed for each reel.

Electrical Characteristics at Tj=25°C

Part Number	Min. (V)	Vf @ If = 2mA		Vr @ Ir = 10uA Min. (V)
		Typ. (V)	Max. (V)	
SSx-CLD	1.6	1.8	2.4	5

Forward voltage, Vf is measured with an accuracy of ± 0.1 V.

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	30	mA
Peak pulse current; (tp $\leq$ 10 μ s, Duty cycle = 0.1)	100	mA
Reverse voltage; Ir _{max} = 10 μ A	5	V
ESD threshold (HBM)	2000	V
LED junction temperature	110	°C
Operating temperature	-40 ... +100	°C
Storage temperature	-40 ... +100	°C
Power dissipation (at room temperature)	40	mW
Thermal resistance		
- Junction / ambient, R _{th JA}	450	K/W
- Junction / solder point, R _{th JS}	250	K/W
(Mounting on FR4 PCB, pad size $\geq$ 16 mm ² per pad)		

Characteristics

	Symbol	Part Number	Value	Unit
Temperature coefficient of λ_{dom} (typ) $I_F = 2\text{mA}; 0^\circ\text{C} \leq T \leq 85^\circ\text{C}$	$TC_{\lambda_{\text{dom}}} \text{ (typ)}$	SSS-CLD	0.04	nm / K
		SSO-CLD	0.08	
		SSY-CLD	0.09	
Temperature coefficient of V_F (typ) $I_F = 2\text{mA}; 0^\circ\text{C} \leq T \leq 85^\circ\text{C}$	TC_V	SSS-CLD	-2.4	mV / K
		SSO-CLD	-2.4	
		SSY-CLD	-3.3	
Temperature coefficient of I_V (typ) $I_F = 2\text{mA}; 0^\circ\text{C} \leq T \leq 85^\circ\text{C}$	TC_{I_V}	SSS-CLD	-0.55	% / K
		SSO-CLD	-0.65	
		SSY-CLD	-1.05	

Wavelength Grouping at Tj=25°C

Color	Group	Wavelength distribution (nm)
SSS; Super Red	Full	625 - 640
SSO; Orange	Full	600 - 612
	W	600 - 603
	X	603 - 606
	Y	606 - 609
	Z	609 - 612
SSY; Yellow	Full	582 - 594
	W	582 - 585
	X	585 - 588
	X	588 - 591
	Y	591 - 594


Dominant wavelength is measured with an accuracy of $\pm 1\text{nm}$.

Luminous Intensity Group at Tj=25°C


Brightness Group	Luminous Intensity IV (mcd)
H1	2.80 ... 3.55
H2	3.55 ... 4.50
J1	4.50 ... 5.60
J2	5.60 ... 7.20
K1	7.20 ... 9.00
K2	9.00 ... 11.20

Luminous intensity is measured with an accuracy of $\pm 11\%$.


Relative Intensity vs Forward Current




Forward Current Vs Forward Voltage




Maximum Current Vs Ambient Temperature




Relative Intensity vs Wavelength



Radiation Pattern



SpiceLED™ • AlInGaP S-Spice : SSx-CLD-I2 Package Outlines




Material

Material	
Lead-frame	Cu Alloy With NiPdAu Plating
Package	High Temperature Resistant Epoxy Resin


Note: product is Pb free

Recommended Solder Pad

Solder pad.




Recommended Solder-pad




Alternative Solder-pad
 Compatible to ChipLED 0603

Note: Component is based on a new package platform, which features “Bottom Only Terminations”. Solder joints are only formed at the bottom of the component and solder fillet will not be observable as the sides of the component.




Taping and orientation


- Reels come in quantity of 3000 units.
- Reel diameter is 180 mm.




Packaging Specification



Packaging Specification




	Average 1pc SpiceLED	1 completed bag (3000pcs)
Weight (gram)	0.001	140 ± 10



For SpiceLED™

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box	Quantity / Box (pcs)
Small	300 x 250 x 250	0.58	15 reels MAX	45,000 MAX
Large	416 x 516 x 476	1.74	96 reels MAX	288,000 MAX

Recommended Pb-free Soldering Profile



Revision History

Page	Subjects	Date of Modification
-	New Format	10 Mar 2006
4	Add Relative Intensity vs Forward Current Graph	24 Jun 2008
2	Update DC Forward Current --> 30mA	10 Sep 2009
-	Update Company Name	29 Mar 2010
3	Add Luminous Intensity Group Add Thermal Resistance	23 Aug 2011
7	Update Carrier Tape	13 Feb 2014
3	Add Characteristics	24 Nov 2014

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

About Us

DOMINANT Opto Technologies is a dynamic Malaysian Corporation that is among the world's leading SMT LED Manufacturers. An excellence – driven organization, it offers a comprehensive product range for diverse industries and applications. Featuring an internationally certified quality assurance acclaim, DOMINANT's extra bright LEDs are perfectly suited for various lighting applications in the automotive, consumer and communications as well as industrial sectors. With extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing, research and testing capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies can be found on the Internet at <http://www.dominant-semi.com>.

Please contact us for more information:

Head Quarter

DOMINANT Opto Technologies Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com

