
QUINT 2-INPUT OR/NOR GATE

SY100S302

FEATURES

- **Max. propagation delay of 700ps**
- **I_{EE} min. of –45mA**
- **Industry standard 100K ECL levels**
- **Extended supply voltage option: V_{EE} = –4.2V to –5.5V**
- **Voltage and temperature compensation for improved noise immunity**
- **Internal 75KΩ input pull-down resistors**
- **50% faster than Fairchild 300K**
- **Function and pinout compatible with Fairchild F100K**
- **Available in 24-pin CERPACK and 28-pin PLCC packages**


BLOCK DIAGRAM




DESCRIPTION

The SY100S302 offers five 2-input OR/NOR gates designed for use in high-performance ECL systems. The five gates are controlled by a common Enable signal. All inputs have 75KΩ pull-down resistors and all outputs are buffered.

PIN CONFIGURATIONS





PIN NAMES

Pin	Function
D_{na} – D_{ne}	Data Inputs (n-1...5)
E	Enable Input
O_a – O_e	Data Outputs
$\overline{O_a}$ – $\overline{O_e}$	Complementary Data Outputs
V_{EES}	V_{EE} Substrate
V_{CCA}	V_{CCO} for ECL Outputs

TRUTH TABLE[1]

D1X	D2X	E	OX	$\overline{OX}$
L	L	L	L	H
L	L	H	H	L
L	H	L	H	L
L	H	H	H	L
H	L	L	H	L
H	L	H	H	L
H	H	L	H	L
H	H	H	H	L

NOTE:

1. H = High Voltage Level
   L = Low Voltage Level

DC ELECTRICAL CHARACTERISTICS

V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current, All Inputs	—	—	200	µA	V_{IN} = V_{IH} (Max.)
I_{EE}	Power Supply Current	–45	–28	–21	mA	Inputs Open

AC ELECTRICAL CHARACTERISTICS

CERPACK

V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND


Symbol	Parameter	T_A = 0°C		T_A = +25°C		T_A = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	300	750	300	750	300	750	ps	
t_{PLH} t_{PHL}	Propogation Delay Enable to Output	250	950	250	950	250	950	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

PLCC

V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND

Symbol	Parameter	T_A = 0°C		T_A = +25°C		T_A = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	250	700	250	700	250	700	ps	
t_{PLH} t_{PHL}	Propogation Delay Enable to Output	250	900	250	900	250	900	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

TIMING DIAGRAM




Propagation Delay and Transition Times

NOTE:
V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY100S302FC	F24-1	Commercial
SY100S302JC	J28-1	Commercial
SY100S302JCTR	J28-1	Commercial


24 LEAD CERPACK (F24-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. THIS DIMENSION INCLUDES GLASS PROTRUSION AND CAP TO BASE ALIGNMENT TOLERANCES.
3. DIMENSIONS SHOWN ARE MAX/MIN, WHERE NOTED.

Rev. 03

28 LEAD PLCC (J28-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB http://www.micrel.com

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated