

Surface Mount

Power Splitter/Combiner

SYPS-3-12W+

3 Way-0° 50Ω

20 to 1200 MHz



CASE STYLE: AH202

PRICE: \$ 9.95 ea. QTY (1-9)


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.15W max.

Pin Connections

SUM PORT	8
PORT 1	1
PORT 2	4
PORT 3	5
GROUND	2,3,6,7

Outline Drawing



Outline Dimensions (inch)

A	B	C	D	E	F	G	H	
.375	.500	.25	.020	0.35	.050	.140	.180	
9.53	12.70	6.35	0.51	8.89	1.27	3.56	4.57	
J	K	L	M	N	P	Q	R	wt
.320	.360	.450	.320	.360	.135	.240	.280	grams
8.13	9.14	11.43	8.13	9.14	3.43	6.10	7.11	0.80

Features

- low insertion loss 1.0 dB typ.
- wide frequency band, 20 to 1200 MHz, usable 5 to 1250 MHz
- low amplitude unbalance, 0.1 dB typ.

Applications

- VHF/UHF CATV
- cellular


Splitter Electrical Specifications

FREQUENCY (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 4.8 dB		PHASE UNBALANCE (deg.)	AMPLITUDE UNBALANCE (dB)
	Typ.	Min.	Typ.	Max.	Max.	Max.
20-500	24	16	0.7	1.4	2	0.3
500-1000	20	15	1.2	2.0	4	0.7
1000-1200	24	16	1.7	2.9	6	0.9


Typical Performance Data

FREQ. (MHz)	INSERTION LOSS (dB)			AMPLITUDE UNBALANCE (dB)	ISOLATION (dB)			PHASE UNBALANCE (deg.)	VSWR			
	S-1	S-2	S-3		1-2	1-3	2-3		S	1	2	3
20.00	5.26	5.27	5.26	0.01	33.11	33.43	33.56	0.08	1.14	1.18	1.17	1.17
50.00	5.22	5.24	5.23	0.01	31.13	31.72	31.88	0.10	1.13	1.17	1.16	1.16
100.00	5.24	5.25	5.24	0.01	27.63	28.50	28.60	0.18	1.16	1.16	1.15	1.16
200.00	5.34	5.34	5.33	0.01	23.67	24.84	24.91	0.32	1.25	1.15	1.15	1.16
300.00	5.49	5.47	5.46	0.03	21.17	22.46	22.54	0.44	1.35	1.14	1.15	1.16
400.00	5.66	5.61	5.61	0.05	19.44	20.80	20.90	0.52	1.44	1.13	1.14	1.17
500.00	5.82	5.74	5.74	0.09	18.40	19.82	19.98	0.56	1.51	1.12	1.14	1.16
600.00	5.97	5.84	5.85	0.13	17.84	19.31	19.56	0.52	1.54	1.11	1.12	1.15
700.00	6.09	5.90	5.93	0.18	17.68	19.24	19.63	0.40	1.54	1.11	1.11	1.14
800.00	6.18	5.93	5.96	0.25	18.11	19.80	20.45	0.19	1.47	1.10	1.08	1.11
900.00	6.26	5.94	5.98	0.32	19.22	21.23	22.40	0.19	1.36	1.09	1.05	1.06
1000.00	6.38	5.98	6.03	0.41	21.28	24.38	27.02	0.71	1.18	1.09	1.04	1.04
1090.00	6.62	6.12	6.18	0.50	23.65	31.70	42.96	1.40	1.04	1.08	1.08	1.11
1150.00	6.91	6.35	6.41	0.56	23.44	36.09	29.45	1.96	1.20	1.08	1.13	1.18
1200.00	7.27	6.65	6.72	0.62	21.47	27.81	23.54	2.56	1.39	1.08	1.17	1.25


SYPS-3-12W
INSERTION LOSS



SYPS-3-12W
ISOLATION



SYPS-3-12W
VSWR



electrical schematic



Mini-Circuits®

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

INTERNET <http://www.minicircuits.com>



REV. OR
M101809
SYPS-3-12W
ED-12388A/1
WL/RS/CP
051215