
RADSL Transformer

Reinforced Insulation Per EN 41003/EN 60950

Schematic Diagram





Parameter	Min.	Max.	Units
Turns Ratio (1-3) : (10-7) with 8 & 9 shorted	1 : 3.93	1 : 4.17	
Turns Ratio (2-4) : (10-7) with 8 & 9 shorted	1 : 1.96	1 : 2.08	
Primary Inductance Pins 1-3, All others windings open	25	30	µH
Leakage Inductance(1)		.5	µH
Leakage Inductance(2)		5	µH
Interwinding Capacitance(3)		30	pF
Interwinding Capacitance(4)		35	pF
Resistance pins (1-3)		0.5	ohms
Resistance pins (2-4)		1.0	ohms
Resistance pins (7-10) with 8,9 shorted		2.0	ohms
Isolation (Hi-Pot)	3000		V_{RMS}
DC Bias		2	mA
Insertion Loss 35 kHz to 1.0 MHz		0.5	dB
Longitudinal Balance 35 KHz to 650 KHz		-60	dB
Signal Voltage (secondary)		15	Vp-p
THD, Total Harmonic Distortion 15 Vp-p @ 100 KHz at (7-10) with 8,9 shorted		-90	dB


1. Tested at 100 KHz & 100 mV (1-3) with 2,4 open 7,8,9,10 shorted
2. Tested at 100 KHz & 100 mV (2-4) with 1,3 open 7,8,9,10 shorted
3. Tested at 100 KHz & 100 mV (1-3) to (10-7) with 8,9 shorted
4. Tested at 100 KHz & 100 mV (2-4) to (10-7) with 8,9 shorted


Physical Dimensions

inches (mm)









RHOMBUS P/N: T-1016G	
CUST P/N:	NAME: GLOBESPAN
DATE: 01/02/98	SHEET: 1 of 1

Rhombus Industries Inc.
Transformers & Magnetic Products

FSCM No. 16714

15801 Chemical Lane, Huntington Beach, CA 92649
Phone: (714) 898-0960
FAX: (714) 896-0971