ADSL Transformer


Reinforced Insulation Per EN 41003/EN 60950

Turns Ratio (± 3 %)	1.4 : 1

PARAMETER	MIN.	MAX.	UNITS
Primary Inductance[1] Pins 1-4 with 2 & 3 shorted.	895	1200	µH
Secondary Inductance Pins 10-7 with 8 & 9 shorted.	453	550	µH
Leakage Inductance		15	µH
Interwinding Capacitance		20	pF
Primary DC Resistance Pins 1-3 or 2-4		0.4	ohms
Secondary DC Resistance Pins 10-8, or 9-7		0.4	ohms
Isolation (Hi-Pot)	3000		V_{RMS}
DC Bias		2	mA


[1]Tested @ 100kHz & 100 mV_{RMS}

Schematic Diagram



This part is available in Surface Mount. Add Suffix "G" to part number.

Physical Dimensions
inches (mm)



Unused Pins Omitted

RHOMBUS P/N: T-1114G	
CUST P/N:	NAME:
DATE: 1/15/98	SHEET: 1 of 1

Rhombus Industries Inc.
Transformers & Magnetic Products

15801 Chemical Lane, Huntington Beach, CA 92649
Phone: (714) 898-0960
FAX: (714) 896-0971

www.rhombus-ind.com