T-998

DDS Aplications
Pulse Transformers

PARAMETER		UNITS
Turns Ratio	1 : 1 ±1%	
Line Impedance	143	Ω
Inductance (Line Side)	40 Min	mH
Leakage Inductance 10 kHz - 0.5V_{RMS}	40 Max.	µH
Primary DC Resistance	2.9 Typ.	Ω
Secondary DC Resistance	5.9 Typ.	Ω
Frequency Response 1 kHz - 200 kHz	1.0 Max.	dB
Insertion Loss @ 10kHz	0.5 Typ.	dB
Isolation (HI-POT)	1875	V_{RMS}
Primary DC	0	mA
Return Loss @ 1 kHz - 200 kHz	15 Typ.	dB
Longitudinal Balance 200 - 1000 Hz 15 kHz	40 Typ. 35 Typ.	dB dB
Interwinding Capacitance 10 kHz - 1 V_{RMS}	65 Max.	pF

Designed to meet the requirements of Bellcore TR-NWT-000499, Synchronous Digital Data Interface-64 Kbps and Subrates


Recomended for use with level one LXT441


Custom versions of this transformer are available.

A Surface Mount version of this transformer is available


Compatible with Level One transceiver ICs

SCHEMATIC DIAGRAM:






Pin Diameter is 0.025 (0.64)



Physical Dimensions in inches (mm)

PIN POSITION GRID 0.100 (2.54)

● HOLES FOR BOBBIN PINS



4/15/98

Rhombus Industries Inc.
Transformers & Magnetic Products

15801 Chemical Lane, Huntington Beach, CA 92649
Phone: (714) 898-0960
FAX: (714) 896-0971

www.rhombus-ind.com