



Features

- 100A Peak Pulse Current @ 10/1000 s
- 400A Peak Pulse Current @ 8/20 s
- 58 - 320V Stand-Off Voltages
- Oxide-Glass Passivated Junction
- Bi-Directional Protection In a Single Device
- High Off-State impedance and Low On-State Voltage



Mechanical Data

- Case: SMB/DO-214AA, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.093 grams (approx.)



SMB(DO-214AA)		
Dim	Min	Max
A	3.30	3.94
B	4.06	4.70
C	1.91	2.21
D	0.15	0.31
E	5.00	5.59
G	0.10	0.20
H	0.76	1.52
J	2.00	2.62
All Dimensions in mm		


Maximum Ratings and Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	Value	Unit
Non-Repetitive Peak Impulse Current @ 10/1000us	I_{pp}	100	A
Non-Repetitive Peak On-State Current @ 8.3ms (one-half cycle)	I_{TSM}	50	A
Junction Temperature Range	T_j	-40 to +150	C
Storage Temperature Range	T_{STG}	-55 to +150	C
Thermal Resistance, Junction to Lead	R_{JL}	20	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient	R_{JA}	100	$^\circ\text{C/W}$
Typical Positive Temperature Coefficient for Breakdown Voltage	VBR/T_j	0.1	$\%/^\circ\text{C}$

Maximum Rated Surge Waveform

Waveform	Standard	I_{pp} (A)
2/10 us	GR-1089-CORE	500
8/20 us	IEC 61000-4-5	400
10/160 us	FCC Part 68	250
10/700 us	ITU-T, K20/K21	200
10/560 us	FCC Part 68	160
10/1000 us	GR-1089-CORE	100



Electrical Characteristics

@ $T_A = 25^\circ\text{C}$ unless otherwise specified

Part Number	Marking Code	Rated Repetitive Off-State Voltage	Off-State Leakage Current @ V_{DRM}	Breakover Voltage	On-State Voltage @ $I_T = 1\text{A}$	Breakover Current I_{BO}		Holding Current I_{H}		Off-State Capacitance
		V_{DRM} (V)	I_{DRM} (μA)	V_{BO} (V)	V_{T} (V)	Min (mA)	Max (mA)	Min (mA)	Max (mA)	C_{O} (pF)
TB0640H	T064H	58	5	77	3.5	50	800	150	800	200
TB0720H	T072H	65	5	88	3.5	50	800	150	800	200
TB0900H	T090H	75	5	98	3.5	50	800	150	800	200
TB1100H	T110H	90	5	130	3.5	50	800	150	800	120
TB1300H	T130H	120	5	160	3.5	50	800	150	800	120
TB1500H	T150H	140	5	180	3.5	50	800	150	800	120
TB1800H	T180H	160	5	220	3.5	50	800	150	800	120
TB2300H	T230H	190	5	265	3.5	50	800	150	800	80
TB2600H	T260H	220	5	300	3.5	50	800	150	800	80
TB3100H	T310H	275	5	350	3.5	50	800	150	800	80
TB3500H	T350H	320	5	400	3.5	50	800	150	800	80

Symbol	Parameter
V_{DRM}	Stand-off Voltage
I_{DRM}	Leakage current at stand-off voltage
V_{BR}	Breakdown voltage
I_{BR}	Breakdown current
V_{BO}	Breakover voltage
I_{BO}	Breakover current
I_{H}	Holding current
V_{T}	On state voltage
I_{PP}	Peak pulse current
C_{O}	Off-state capacitance

- Notes:
- $I_{\text{H}} > (V_{\text{L}}/R_{\text{L}})$ If this criterion is not obeyed, the TSPD triggers but does not return correctly to high-resistance state. The surge recovery time does not exceed 30ms.
 - Off-state capacitance measured at $f = 1.0\text{MHz}$, $1.0V_{\text{RMS}}$ signal, $V_{\text{R}} = 2V_{\text{DC}}$ bias.

