
35.0A Glass Passivated Bridge Rectifier



TB35W

Features

- High forward surge current capability
- Ideal for printed circuit board
- High temperature soldering guaranteed: 260°C/10 seconds, 5 lbs (2.3kg) tension
- RoHS Compliant

Mechanical Data

Case:	Molded plastic body with Metal Heat Sink
Polarity:	Polarity symbols marked on case
Terminals:	Plated 0.25" (6.35mm) lug
Mounting Position:	Thru hole for #10 screw,20 in -lbs. torque max
Weight:	0.53 ounce, 15 grams

Maximum Ratings & Electrical Characteristics *($T_{Ambient}$=25ºC unless noted otherwise)*

Symbols	Description	TB3505GW	TB351GW	TB352GW	TB354GW	TB356GW	TB358GW	TB3510GW	Unit
V_{RRM}	Max. recurrent peak reverse voltage	50	100	200	400	600	800	1000	V
V_{RMS}	Max. RMS voltage	35	70	140	280	420	560	700	V
V_{DC}	Max. DC blocking voltage	50	100	200	400	600	800	1000	V
$I_{O(AV)}$	Max. average forward rectified current @ TC=50° C	35.0							A
I_{FSM}	Peak forward surge current (Note 1)	400							A
V_{ISO}	Isolation Voltage from case to lugs	2500							V
C_J	Typical Capacitance Junction(per element)(Note 2)	300							pF
T_J	Operating junction temperature range	-55 to +150							° C
T_{STG}	Storage Temperature Range	-55 to +150							° C

Symbol	Description		TB3505GW	TB351GW	TB352GW	TB354GW	TB356GW	TB358GW	TB3510GW	Unit
V_F	Maximum Instantaneous Forward Voltage Drop Per Leg@17.5 A		1.1							V
I_R	Maximum DC Reverse Current Rated DC Blocking Voltage	T_A=25° C	10.0							uA
		T_A=125° C	500							uA
$R_{\theta-JC}$	Maximum Thermal Resistance (Note 3)		1.9							° C/W

NOTES:

1. 8.3ms single half sine-wave superimposed on rated load (JEDEC method).
2. Measured at 1MHz and applied reverse voltage of 4.0Volts D.C.
3. Thermal resistance junction to case mounted on heat sink.

Typical Characteristics Curves

Fig.1- Typical Forward Current Derating Curve




Fig.2-Max. Non-repetitive Peak Forward Surge Current




Fig.3- Typical Instantaneous Forward Characteristics




Fig.4- Typical Reverse Characteristics






Fig.5-Typical junction capacitance



Dimensions in inches (mm)

TB35W



How to contact us

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162
Tel: (800) TAITRON (800) 824-8766 (661) 257-6060
Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415
Email: taitron@taitroncomponents.com
Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P. 42970 MEXICO
Tel: +52-55-5560-1519
Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL
Tel: +55-11-5574-7949
Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA
Tel: +86-21-5424-9942
Fax: +86-21-5424-9931