RECTRON SEMICONDUCTOR
TECHNICAL SPECIFICATION

TEP0801S-15LC

Ultra Low Capacitance TVS/ESD Protection Diode

DESCRIPTION

TEP0801S-15LC is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. With typical capacitance of 0.35pF only, TEP0801S-15LCis designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 (±15kV air, ±8kV contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

TEP0801S-15LC uses ultra-small DFN1006 package. Each TEP0801S-15LC device can protect one high-speed data line. It offers system designers flexibility to protect single data line where space is a premium concern. The combined features of low capacitance, ultra-small size and high ESD robustness make TEP0801S-15LC ideal for high-speed data port and high-frequency line (e.g., USB 2.0 & antenna line) applications, such as cellular phones and HD visual devices.

FEATURES

✧Transient protection for high-speed data lines
IEC 61000-4-2 (ESD) ±15kV (Air)
±8kV (Contact)
IEC 61000-4-4 (EFT) 40A (5/50 ns)
Cable Discharge Event (CDE)
✧Package optimized for high-speed lines
✧Ultra-small package (1.0mm×0.6mm×0.55mm)
✧Protects one data, control or power line
✧Low capacitance: 0.35pF (Typical)
✧Low leakage current: 10nA @ VRWM (Typical)
✧Low clamping voltage
✧Each I/O pin can withstand over 1000 ESD strikes for ±8KV contact discharge

MACHANICAL DATA

✧DFN1006 package
✧Flammability Rating: UL 94V-0
✧Packaging: Tape and Reel
✧High temperature soldering guaranted:260℃/10s
✧Reel size: 7 inch


ORDERING INFORMATION

✧Device:TEP0801S-15LC
✧Package: DFN1006
✧Marking: o
✧Material: Halogen free
✧Packing: Tape & Reel
✧Quantity per reel: 10,000pcs


APPLICATIONS

✧Serial ATA
✧USB Ports
✧PCI Express
✧Cellular Phones
✧Desktops, Severs and Notebooks

PIN CONFIGURATION



PACKAGE OUTLINE



2017-06
REV:O1

ABSOLUTE MAXIMUM RATING


Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	±15 ±12	kV
T_{OPT}	Operating Temperature	-55/+125	°C
T_{STG}	Storage Temperature	-55/+150	°C

ELECTRICAL CHARACTERISTICS (Tamb=25°C)


Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V_{RWM}	Reverse Working Voltage				15.0	V
V_{BR}	Reverse Breakdown Voltage	I_T = 1mA	16.7	20	24	V
I_R	Reverse Leakage Current	V_{RWM} = 15V		0.01	1.0	μA
V_C	Clamping Voltage 1	I_{PP} = 1A, t_p = 8/20μs		23	27	V
C_J	Junction Capacitance	V_R = 0V, f = 1MHz		0.35	0.50	pF

RATING AND CHARACTERISTICS CURVES (TEP0801S-15LC)

Voltage Sweeping of I/O to I/O




Insertion Loss S21 of I/O to I/O




Capacitance vs. Voltage of I/O to I/O (f = 1MHz)


Capacitance *vs.* Reverse Voltage




Normalized Capacitance *vs.* Reverse Voltage




ESD Clamping of I/O to I/O (+8kV Contact per IEC 61000-4-2)



ESD Clamping of I/O to I/O (-8kV Contact per IEC 61000-4-2)





[illegible]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Minimum	Maximum	Minimum	Maximum
A	0.400	0.550	0.016	0.022
A1	0.000	0.050	0.000	0.002
A3	0.125 REF		0.005 REF	
D	0.950	1.050	0.037	0.041
E	0.550	0.650	0.022	0.026
L	0.450	0.550	0.018	0.022
b	0.250	0.400	0.100	0.016

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.