
2.0A Glass Passivated Fast Recovery Rectifier



D0-15

Features

- Low forward voltage drop
- High current capability
- High reliability
- High forward surge current capability
- High temperature soldering guaranteed 250°C/10 seconds /.0375" (9.5mm) lead length, 5lbs (2.3kg) tension
- RoHS Compliance

Mechanical Data

Case:	D0-15, molded plastic
Epoxy:	UL 94V-0 rate flame retardant
Terminals:	Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
Polarity:	Color band denotes cathode end
Weight:	0.40 gram

Maximum Ratings and Electrical Characteristics *(T_A=25ºC unless noted otherwise)*

Symbol	Description	TF 201G	TF 202G	TF 203G	TF 204G	TF 205G	TF 206G	TF 207G	Unit	Conditions
V_{RRM}	Maximum Repetitive Peak Reverse Voltage	50	100	200	400	600	800	1000	V	
V_{RMS}	Maximum RMS Voltage	35	70	140	280	420	560	700	V	
V_{DC}	Maximum DC Blocking Voltage	50	100	200	400	600	800	1000	V	
I_{AV}	Maximum Average Forward Rectified Current	2.0							A	Ta=55 ˚C
I_{FSM}	Peak Forward Surge Current	70							A	8.3ms single half sine-wave superimposed on rated load (JEDEC method)

Tel: (800)-TAITRON (800)-824-8766 (661)-257-6060
Fax: (800)-TAITFAX (800)-824-8329 (661)-257-6415

TF201G - TF207G

Symbol	Description	TF 201G	TF 202G	TF 203G	TF 204G	TF 205G	TF 206G	TF 207G	Unit	Conditions
V_F	Maximum Instantaneous Forward Voltage	1.3							V	I_F=2.0 A
I_R	Maximum DC Reverse Current at Rated DC Blocking Voltage	5.0							μA	T_A=25° C
		100								T_A=100° C
T_{rr}	Typical Reverse Recovery Time	150				250	500		nS	I_F=0.5A, I_R=1A, I_{rr}=0.25A
C_J	Typical Junction Capacitance	25							pf	VR=4V, f=1MHz
T_J	Operating Temperature range	-55 to +150							° C	
T_{STG}	Storage Temperature Range	-55 to +150								

Typical Characteristics Curves

Fig.1-Max. Forward Current Derating Curve




Fig.2-Max. Non-Repetitive Forward Surge Current




Fig.3- Typical Forward Characteristics






Fig.4- Typical Junction Capacitance



Dimensions in inches (mm)



D0-15

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKAWAY, VALENCIA, CA 91355-4162
Tel: (800) TAITRON (800) 824-8766 (661) 257-6060
Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415
Email: taitron@taitroncomponents.com
Http://www.taitroncomponents.com

TAITRON COMPONETS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P. 42970 MEXICO
Tel: +52-55-5560-1519
Fax: +52-55-5560-2190

TAITRON COMPONETS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL
Tel: +55-11-5574-7949
Fax: +55-11-5572-0052

TAITRON COMPONETS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA
Tel: +86-21-5424-9942
Fax: +86-21-5424-9931