Ordering number : ENA1616A

SANYO Semiconductors

DATA SHEET

An ON Semiconductor Company

N-channel Silicon Junction FET

TF256 — Electret Condenser Microphone Applications

Features

- High gain : G_V=2.7dB typ (V_{CC}=2V, R_L=2.2kΩ, Cin=5pF, V_{IN}=10mV, f=1kHz)
- Ultrasmall package facilitates miniaturization in end products [1.0mm×0.6mm×0.27mm (max 0.3mm)]
- Best suited for use in electret condenser microphone for audio equipments and telephones
- Excellent transient characteristics
- Adoption of FBET process
- Halogen free compliance

Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Gate-to-Drain Voltage	V_{GDO}		−20	V
Gate Current	I_G		10	mA
Drain Current	I_D		1	mA
Allowable Power Dissipation	P_D		30	mW
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		−55 to +150	°C

Package Dimensions

unit : mm (typ)

7055-001



Product & Package Information

- Package : USFP
- JEITA, JEDEC : -
- Minimum Packing Quantity : 10,000 pcs./real

Packing Type: TL



Marking

Electrical Connection



Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings				Unit
			Rank	min	typ	max	
Gate-to-Drain Breakdown Voltage	$V_{(BR)GDO}$	I_G=−100μA		−20			V
Cutoff Voltage	V_{GS}(off)	V_{DS}=2V, I_D=1μA		−0.1	−0.35	−1.0	V
Drain Current	I_{DSS}	V_{DS}=2V, V_{GS}=0V	3	100		180	μA
			4	140		280	
			5	240		450	
Forward Transfer Admittance	| yfs |	V_{DS}=2V, V_{GS}=0V, f=1kHz		0.75	1.7		mS
Input Capacitance	Ciss	V_{DS}=2V, V_{GS}=0V, f=1MHz			3.1		pF
Reverse Transfer Capacitance	Crss	V_{DS}=2V, V_{GS}=0V, f=1MHz			1.0		pF
[Ta=25°C, V_{CC}=2.0V, R_L=2.2kΩ, Cin=5pF, See specified Test Circuit.]							
Voltage Gain	G_V	V_{IN}=10mV, f=1kHz	3		1.0		dB
			4		2.0		
			5		3.0		
Reduced Voltage Characteristic	ΔG_{VV}	V_{IN}=10mV, f=1kHz, V_{CC}=2.0V → 1.5V	3		−0.5	−1.0	dB
			4		−0.6	−1.3	
			5		−0.9	−2.0	
Frequency Characteristic	ΔGvf	f=1kHz to 110Hz				−1.0	dB
Total Harmonic Distortion	THD	V_{IN}=30mV, f=1kHz	3		1.4		%
			4		0.9		
			5		0.35		
Output Noise Voltage	V_{NO}	V_{IN}=0V, A curve			−105	−100	dB

Test Circuit

Voltage gain
Frequency Characteristic
Distortion
Reduced Voltage Characteristic








ID -- VGS
VDS=2V
Ta=75°C
25°C
–25°C
Drain Current, ID – μA
Gate-to-Source Voltage, VGS – V
IT15215


| yfs | -- IDSS
VDS=2V
VGS=0V
f=1kHz
Forward Transfer Admittance, | yfs | – mS
Drain Current, IDSS – μA
IT16272


VGS(off) -- IDSS
VDS=2V
ID=1μA
Cutoff Voltage, VGS(off) – V
Drain Current, IDSS – μA
IT16273


Ciss -- VDS
VGS=0V
f=1MHz
Input Capacitance, Ciss – pF
Drain-to-Source Voltage, VDS – V
IT15218


Crss -- VDS
VGS=0V
f=1MHz
Reverse Transfer Capacitance, Crss – pF
Drain-to-Source Voltage, VDS – V
IT15219


GV -- IDSS
GV : VCC=2V
VIN=10mV
f=1kHz
RL=2.2kΩ
Cin=5pF
IDSS : VDS=2V
Voltage Gain, GV – dB
Drain Current, IDSS – μA
IT16274


GV -- VCC
GV : VIN=10mV
f=1kHz
RL=2.2kΩ
Cin=5pF
IDSS=450μA
300μA
150μA
100μA
Voltage Gain, GV – dB
Supply Voltage, VCC – V
IT16275


GV -- Cin
GV : VCC=2V
VIN=10mV
f=1kHz
RL=2.2kΩ
IDSS=450μA
300μA
150μA
100μA
Voltage Gain, GV – dB
Electret Capacitance, Cin – pF
IT16276


ΔGVV -- IDSS
ΔGVV : VCC=2V→1.5V
VIN=10mV
f=1kHz
RL=2.2kΩ
Cin=5pF
IDSS : VDS=2V
Reduced Voltage Characteristic, ΔGVV – dB
Drain Current, IDSS – μA
IT16277


THD -- VIN
THD : VCC=2V
f=1kHz
RL=2.2kΩ
Cin=5pF
IDSS=100μA
150μA
300μA
450μA
Total Harmonic Distortion, THD – %
Input Voltage, VIN – mV
IT16278


THD -- IDSS
THD : VCC=2V
VIN=30mV
f=1kHz
RL=2.2kΩ
Cin=5pF
IDSS : VDS=2V
Total Harmonic Distortion, THD – %
Drain Current, IDSS – μA
IT16279


PD -- Ta
Allowable Power Dissipation, PD – mW
Ambient Temperature, Ta – °C
IT15226

■ Any and all SANYO Semiconductor Co.,Ltd. products described or contained herein are, with regard to "standard application", intended for the use as general electronics equipment (home appliances, AV equipment, communication device, office equipment, industrial equipment etc.). The products mentioned herein shall not be intended for use for any "special application" (medical equipment whose purpose is to sustain life, aerospace instrument, nuclear control device, burning appliances, transportation machine, traffic signal system, safety equipment etc.) that shall require extremely high level of reliability and can directly threaten human lives in case of failure or malfunction of the product or may cause harm to human bodies, nor shall they grant any guarantee thereof. If you should intend to use our products for applications outside the standard applications of our customer who is considering such use and/or outside the scope of our intended standard applications, please consult with us prior to the intended use. If there is no consultation or inquiry before the intended use, our customer shall be solely responsible for the use.

■ Specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ SANYO Semiconductor Co.,Ltd. assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein.

■ SANYO Semiconductor Co.,Ltd. strives to supply high-quality high-reliability products, however, any and all semiconductor products fail or malfunction with some probability. It is possible that these probabilistic failures or malfunction could give rise to accidents or events that could endanger human lives, trouble that could give rise to smoke or fire, or accidents that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all SANYO Semiconductor Co.,Ltd. products described or contained herein are controlled under any of applicable local export control laws and regulations, such products may require the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written consent of SANYO Semiconductor Co.,Ltd.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO Semiconductor Co.,Ltd. product that you intend to use.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.

■ Upon using the technical information or products described herein, neither warranty nor license shall be granted with regard to intellectual property rights or any other rights of SANYO Semiconductor Co.,Ltd. or any third party. SANYO Semiconductor Co.,Ltd. shall not be liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above.

This catalog provides information as of January, 2011. Specifications and information herein are subject to change without notice.