User's Guide
SLUUBN2–March 2017

TPS549B22EVM-847, 25-A Single Synchronous Step-Down Converter With Full Differential Sense and PMBus™

This user's guide describes the characteristics, operation, and use of the TPS549B22 Evaluation Module (EVM). The user's guide includes test information, descriptions, and results. A complete schematic diagram, printed-circuit board layouts, and bill of materials are also included in this document. Throughout this user's guide, the abbreviations EVM, TPS549B22EVM, and the term evaluation module are synonymous with the TPS549B22EVM-847, unless otherwise noted.

Contents

1 Introduction 3
1.1 Before You Begin 3
2 Description 4
2.1 Typical End-User Applications 4
2.2 EVM Features 4
3 EVM Electrical Performance Specifications 5
4 Schematic 6
5 Test Setup 7
5.1 Test and Configuration Software 7
6 Test Equipment 8
7 PWR-847EVM 9
8 List of Test Points, Jumpers, and Switch 11
9 EVM Configuration Using the Fusion GUI 12
10 Test Procedure 13
10.1 Line and Load Regulation Measurement Procedure 13
10.2 Efficiency 13
10.3 Equipment Shutdown 13
11 Performance Data and Typical Characteristic Curves 14
11.1 Efficiency 14
11.2 Load Regulation 14
11.3 Line Regulation 15
11.4 Transient Response 18
11.5 Output Ripple 18
11.6 Control On 19
11.7 Control Off 20
11.8 Thermal Image 21
12 Fusion GUI 22
13 EVM Assembly Drawing and PCB Layout 33
14 List of Materials 38

List of Figures

1 PWR-847EVM Schematic 6
2 PWR-847EVM Overview 9
3 Tip and Barrel Measurement 9
4 EVM and USB Interface Adapter 10
5 Efficiency vs Output Current SKIP Mode 14
6 Power Loss vs Output Current SKIP Mode 14

Copyright © 2017, Texas Instruments Incorporated

7 Line Regulation of 1-V Output 15
8 PMBus V_{OUT} Step-Up = 0.6 V to 1.2 V at 0 A 15
9 PMBus V_{OUT} Step-Down = 1.2 V to 0.6 V at 0 A 16
10 PMBus V_{OUT} Step-Up = 0.6 V to 1.2 V at 25 A 16
11 PMBus V_{OUT} Step-Down = 1.2 V to 0.6 V at 25 A 17
12 PMBUS Multiple Commands 17
13 Transient Response of 1-V Output at 12 V_{IN}, Transient is 0.5 A to 15.5 A, the Step is 15 A at 40 A/µs 18
14 Output Ripple and SW Node of 1-V Output at 12 V_{IN}, 25-A Output 18
15 Output Ripple and SW Node of 1-V Output at 12 V_{IN}, 0-A Output 19
16 Start up from Control, 1-V Output at 12 V_{IN}, 0-A Output 19
17 0.5-V Pre-bias start up from Control, 1-V Output at 12 V_{IN}, 10-A Output 20
18 Start-Up and Shutdown, 1-V Output at 12 V_{IN}, 0.5-A Output 20
19 Thermal Image at 1-V Output at 12 V_{IN}, 25-A Output, 650 kHz at 25°C Ambient 21
20 First Window at Fusion Launch 22
21 Scan Finds Device Successfully 22
22 Software Launch Continued 22
23 Software Launch Continued 22
24 First Screen After Successful Launch Configure: Limits and On/Off 23
25 Configure: Frequency- FS Configuration Pop-up 24
26 Configure: Frequency- FS Config Pop-Up with Change 25
27 Configure: *Store Config to NVM* 26
28 Change View Screen to Monitor Screen 27
29 System Dashboard 28
30 Status Screen 29
31 Store Configuration To Memory 30
32 PMBus Logging 31
33 PMBus Log Details 32
34 PWR-847EVM Top Layer Assembly Drawing (Top View) 33
35 PWR-847EVM Top Solder Mask (Top View) 33
36 PWR-847EVM Top Layer (Top View) 34
37 PWR-847EVM Inner Layer 1 (Top View) 34
38 PWR-847EVM Inner Layer 2 (Top View) 35
39 PWR-847EVM Inner Layer 3 (Top View) 35
40 PWR-847EVM Inner Layer 4 (Top View) 36
41 PWR-847EVM Bottom Layer (Top View) 36
42 PWR-847EVM Bottom Solder Mask (Top View) 37
43 PWR-847EVM Bottom Overlay Layer (Top View) 37

List of Tables

1 PWR-847EVM Electrical Performance Specifications 5
2 Test Point Functions 11
3 Key Factory Configuration Parameters 12
4 List of Test Points for Line and Load Measurements 13
5 List of Test Points for Efficiency Measurements 13
6 PWR847 List of Materials 38

Copyright © 2017, Texas Instruments Incorporated

1 Introduction

The PWR847EVM evaluation module uses the TPS549B22 device. The TPS549B22 is a highly integrated synchronous buck converter that is designed for up to 25-A current output.

1.1 Before You Begin

The following warnings and cautions are noted for the safety of anyone using or working close to the TPS549B22EVM-847. Observe all safety precautions.



Warning The TPS549B22EVM-847 circuit module may become hot during operation due to dissipation of heat. Avoid contact with the board. Follow all applicable safety procedures applicable to your laboratory.



Caution Do not leave the EVM powered when unattended.

WARNING

The circuit module has signal traces, components, and component leads on the bottom of the board. This may result in exposed voltages, hot surfaces or sharp edges. Do not reach under the board during operation.

CAUTION

The circuit module may be damaged by over temperature. To avoid damage, monitor the temperature during evaluation and provide cooling, as needed, for your system environment.

CAUTION

Some power supplies can be damaged by application of external voltages. If using more than 1 power supply, check your equipment requirements and use blocking diodes or other isolation techniques, as needed, to prevent damage to your equipment.

CAUTION

The communication interface is not isolated on the EVM. Be sure no ground potential exists between the computer and the EVM. Also be aware that the computer is referenced to the Battery- potential of the EVM.

Copyright © 2017, Texas Instruments Incorporated

2 Description

The PWR-847EVM is designed as a single output DC-DC converter that demonstrates the TPS549B22 in a typical low-voltage application while providing a number of test points to evaluate the performance. It uses a nominal 12-V input bus to produce a regulated 1-V output at up to 25-A load current.

2.1 Typical End-User Applications

- Enterprise Storage, SSD, NAS
- Wireless and Wired Communication Infrastructure
- Industrial PCs, Automation, ATE, PLC, Video Surveillance
- Enterprise Server, Switches, Routers
- ASIC, SoC, FPGA, DSP Core and I/O Rails

2.2 EVM Features

- Regulated 1-V output up to 25-A, steady-state output current
- Convenient test points for probing critical waveforms
- PMBus™ connector for easy connection with the TI USB adapter

Copyright © 2017, Texas Instruments Incorporated

3 EVM Electrical Performance Specifications

Table 1 lists the PWR-847EVM electrical performance specifications.


Table 1. PWR-847EVM Electrical Performance Specifications

Parameter		Test Conditions	Min	Typ	Max	Units
Input Characteristics						
	Voltage range	V_{IN} tied to VDD	5	12	14	V
	Maximum input current	V_{IN} = 12 V, I_O = 25 A			12	A
	No load input current	V_{IN} = 12 V, I_O = 0 A		60		mA
Output Characteristics						
V_{OUT}	Output voltage	Output current = 10 A		1		V
I_{OUT}	Output load current	$I_{OUT(min)}$ to $I_{OUT(max)}$	0		25	A
	Output voltage regulation	Line regulation: input voltage = 5 V to 14 V		0.5%		
		Load regulation: output current = 0 A to $I_{OUT(max)}$		0.5%		
V_{OUT}	Output voltage ripple	V_{IN} = 12 V, I_{OUT} = 25 A		10		mV_{PP}
V_{OUT}	Output overcurrent			32		A
Systems Characteristics						
	Switching frequency	F_{SW}		650		kHz
V_{OUT}	Peak efficiency	V_{IN} = 12 V, I_O = 12 A, F_{SW} = 650 kHz		90%		
	Operating temperature	T_{oper}	0		85	ºC

Copyright © 2017, Texas Instruments Incorporated

4 Schematic

Figure 1 illustrates the PWR-847EVM schematic.



Copyright © 2017, Texas Instruments Incorporated

Figure 1. PWR-847EVM Schematic

Copyright © 2017, Texas Instruments Incorporated

5 Test Setup

5.1 Test and Configuration Software

To change any of the default configuration parameters on the EVM, it is necessary to obtain the TI Fusion Digital Power Designer software. This can be downloaded from the TI website.

5.1.1 Description

The Fusion Digital Power Designer is the graphical user interface (GUI) used to configure and monitor the Texas Instruments TPS549B22 power converter installed on this evaluation module. The application uses the PMBus protocol to communicate with the controller over serial bus by way of a TI USB adapter. This adapter can be purchased at http://www.ti.com/tool/usb-to-gpio.

NOTE: The TI USB adapter must be purchased separately. It is not included with this EVM kit.

5.1.2 Features

Some of the tasks performed with the GUI include:

- Turn on or off the power supply output, either through the hardware control line or the PMBus operation command.
- Monitor status registers. Items such as input voltage, output voltage, output current, temperature, and warnings and faults are continuously monitored and displayed by the GUI.
- Configure common operating characteristics such as VOUT, UVLO, soft-start time, warning and fault thresholds, fault response, and ON/OFF.

This software is available for download at http://www.ti.com/tool/fusion_digital_power_designer.

Copyright © 2017, Texas Instruments Incorporated

6 Test Equipment

Voltage Source: The input voltage source VIN must be a 0-V to 18-V variable DC source capable of supplying at least 12 A_{DC}.

Multimeters: It is recommended to use two separate multimeters Figure 2. One meter is used to measure V_{IN} and one to measure V_{OUT}.

Output Load: A variable electronic load is recommended for testing Figure 2. It must be capable of 25 A at voltages as low as 0.6 V.

Oscilloscope: An oscilloscope is recommended for measuring output noise and ripple. Output ripple must be measured using a tip-and-barrel method or better as shown in Figure 3.The scope must be adjusted to 20-MHz bandwidth, AC coupling at 50 mV/division, and must be set to 1-µs/division.

Fan: During prolonged operation at high loads, it may be necessary to provide forced air cooling with a small fan aimed at the EVM. Temperature of the devices on the EVM must be maintained below 105°C.

USB-to-GPIO Interface Adapter: A communications adapter is required between the EVM and the host computer. This EVM was designed to use TI's USB-to-GPIO adapter. Purchase this adapter at http://www.ti.com/tool/usb-to-gpio.

Recommended Wire Gauge: The voltage drop in the load wires must be kept as low as possible in order to keep the working voltage at the load within its operating range. Use the AWG 14 wire (2 wires parallel for VOUT positive and 2 wires parallel for the VOUT negative) of no more than 1.98 feet between the EVM and the load. This recommended wire gauge and length should achieve a voltage drop of no more than 0.2 V at the maximum 25-A load.

Copyright © 2017, Texas Instruments Incorporated

7 PWR-847EVM

Figure 2 and Figure 3 illustrate the PWR-847EVM overview, tip and barrel measurement.




Figure 2. PWR-847EVM Overview




Figure 3. Tip and Barrel Measurement

Copyright © 2017, Texas Instruments Incorporated

Figure 4 illustrates the EVM and USB interface adapter.




Figure 4. EVM and USB Interface Adapter

Copyright © 2017, Texas Instruments Incorporated

8 List of Test Points, Jumpers, and Switch

Table 2 lists the test points and their descriptions.

Table 2. Test Point Functions

Item	Type	Name	Description
TP5	T-H loop	SW	Power supply Switch node
TP7	T-H loop	CH-A	Measure loop stability
TP6	T-H loop	CH-B	Measure loop stability
TP2	T-H loop	LocS+	Sense VOUT + locally across C25. Use for efficiency and ripple measurements
TP10	T-H loop	LocS-	Sense VOUT– locally across C25. Use for efficiency and ripple measurements
TP3	T-H loop	RemS+	Remote sense +
TP11	T-H loop	RemS-	Remote sense –
TP4	T-H loop	PVIN	Sense VIN + across C10
TP13	T-H loop	PGND	Sense VIN – across C10
TP1	T-H loop	VDD	Supplies the internal circuitry
TP17	T-H loop	ADDR	Monitor the ADDR external resistor divider ratio during initial power up.
TP15	T-H loop	VSEL	Monitor the VSEL external resistor divider ratio during initial power up.
TP9	T-H loop	BP	LDO output
TP8	T-H loop	PG	Power good
TP16	T-H loop	MODE	Monitor the MODE external resistor divider ratio during initial power up.
TP12	T-H loop	ILIM	Program over-current limit.
TP14	T-H loop	RESV_TRK	Do not connect.
TP19	T-H loop	PGND	Common GND
TP18	T-H loop	PGND	Common GND
TP20	T-H loop	PMB_CLK	Clock input for the PMBus interface.
TP21	T-H loop	PMB_DATA	Data I/O for the PMBus interface.
TP22	T-H loop	SMB_ALRT#	$\overline{\text{Alert}}$ output for the PMBus interface.
JP4	2-pin jumper	CNTL	Shunts control pin to GND

Copyright © 2017, Texas Instruments Incorporated

9 EVM Configuration Using the Fusion GUI

The TPS549B22 installed on this EVM leave the factory pre-configured. See Table 3 for a short list of key factory configuration parameters as obtained from the configuration file.

Table 3. Key Factory Configuration Parameters

Cmd ID With Phase	Cmd Code Hex	Encoded Hex [HiByte|LoByte]	Comments
CAPABILITY	0x19	0xD0	Max Bus: 1000 kHz; PEC: Yes; SMBALERT#: Yes
MFR_00	0xD0	0x00	0
MFR_01 (PGOOD_DLY)	0xD1	0x12	PGD:1024?s [010b], POD:1024?s [010b]
MFR_02	0xD2	0x13	CM: True, HICLOFF: True, SST: 0x00, FORCESKIPSS: True, SEQ: False, TRK: False
MFR_03	0xD3	0x93	FS:650 kHz [011b], RCSP:R ? 1 [01b], DCAP3:True
MFR_04	0xD4	0x80	DCAP3_Offset:0mV [00b], DCAP3_Offset_Sel:True
MFR_06	0xD6	0x05	VDDUVLO:4.25V [101b]
MFR_07	0xD7	0x8F	VTRKIN:1.25V [1111b], TRKOPTION:False, SPARE:False, VPBAD:True
MFR_33	0xF1	0x00	0
MFR_42	0xFA	0x00	0
MFR_44	0xFC	0x0201	ID: 0x020 (TPS549B22), Revision: 0x8
ON_OFF_CONFIG	0x02	0x17	Mode: CONTROL Pin Only; Control: Active High, Turn off Immediately
OPERATION	0x01	0x00	Operation is not used to enable regulatio; Unit: ImmediateOff; Margin: None
STATUS_BYTE	0x78	0x00	Status: Output Off, Vout OV Fault, IOUT OC Fault, Vin UV Fault, Temperature, CML
STATUS_CML	0x7E	0x00	Status: Invalid Command, Invalid Data, PEC Fault, Other Comms Fault
STATUS_IOUT	0x7B	0x00	Status: Iout OC Fault, Iout OC Fault with LV Shutdown, Iout UC Fault
STATUS_VOUT	0x7A	0x00	Status: Vout OV Fault, OV Warning, UV Fault, UV Warning
VOUT_COMMAND	0x21	0x01CD	VOUT_COMMAND=0.900 V
VOUT_MARGIN_HIGH	0x25	0x0266	VOUT_MARGIN_HIGH=1.199 V
VOUT_MARGIN_LOW	0x26	0x0266	VOUT_MARGIN_LOW=1.199 V
WRITE_PROTECT	0x10	0x00	Enable Writes To All Commands

If it is desired to configure the EVM to settings other than the factory settings shown in Table 3, the TI Fusion Digital Power Designer software can be used for reconfiguration. It is necessary to have input voltage applied to the EVM prior to launching the software so that the TPS549B22 installed is active and able to respond to the GUI and the GUI can recognize the device.

Copyright © 2017, Texas Instruments Incorporated

10 Test Procedure

10.1 Line and Load Regulation Measurement Procedure

Use the following procedures for line and load regulation measurement.

1. Connect VOUT to J3 and VOUT_GND to J5 Figure 2.
2. Ensure that the electronic load is set to draw 0 A_{DC}.
3. Connect VIN to J1 and VIN_GND to J2 Figure 2.
4. Connect the USB interface adapter as shown in Figure 4.
5. Increase V_{IN} from 0 V to 12 V using the digital multimeter to measure input voltage.
6. Launch the Fusion GUI software. See the screen shots in Section 12 for more information.
7. Configure the EVM operating parameters as desired.
8. Use the other digital multimeter or the oscilloscope to measure output voltage V_{OUT} at TP2 and TP10 as you vary the external voltage source.

Table 4. List of Test Points for Line and Load Measurements

Test Point	Node Name	Description
TP2	LocS+	Sense VOUT + locally across C5. Use for efficiency and ripple measurements
TP10	LocS–	Sense VOUT - locally across C5. Use for efficiency and ripple measurements
TP4	PVIN	Sense VIN + across C10
TP13	PGND	Sense VIN - across C10

9. Vary the load from 0 A_{DC} to maximum rated output 25 A_{DC}. V_{OUT} must remain in regulation as defined in Table 1.
10. Vary V_{IN} from 5 V to 14 V. V_{OUT} must remain in regulation as defined in Table 1.
11. Decrease the load to 0 A.
12. Decrease V_{IN} to 0 V or turn off the supply.

10.2 Efficiency

To measure the efficiency of the power train on the EVM, it is important to measure the voltages at the correct location. This is necessary because otherwise the measurements will include losses in efficiency that are not related to the power train itself. Losses incurred by the voltage drop in the copper traces and in the input and output connectors are not related to the efficiency of the power train, and they must not be included in efficiency measurements.

Table 5. List of Test Points for Efficiency Measurements

Test Point	Node Name	Description
TP2	LocS+	Sense VOUT + locally across C25. Use for efficiency and ripple measurements
TP10	LocS-	Sense VOUT - locally across C25. Use for efficiency and ripple measurements
TP4	PVIN	Sense VIN + across C10
TP13	PGND	Sense VIN - across C10

Input current can be measured at any point in the input wires, and output current can be measured anywhere in the output wires of the output being measured. Using these measurement points result in efficiency measurements that do not include losses due to the connectors and PCB traces.

10.3 Equipment Shutdown

1. Reduce the load current to 0 A.
2. Reduce input voltage to 0 V.
3. Shut down the external fan if in use.
4. Shut down equipment.

Copyright © 2017, Texas Instruments Incorporated

11 Performance Data and Typical Characteristic Curves

Figure 5 through Figure 18 present typical performance curves for the PWR-847EVM.

11.1 Efficiency




Figure 5. Efficiency vs Output Current SKIP Mode

11.2 Load Regulation




Figure 6. Power Loss vs Output Current SKIP Mode

Copyright © 2017, Texas Instruments Incorporated

11.3 Line Regulation




Figure 7. Line Regulation of 1-V Output



Figure 8. PMBus V_{OUT} Step-Up = 0.6 V to 1.2 V at 0 A

Copyright © 2017, Texas Instruments Incorporated



Figure 9. PMBus V_{OUT} Step-Down = 1.2 V to 0.6 V at 0 A



Figure 10. PMBus V_{OUT} Step-Up = 0.6 V to 1.2 V at 25 A

Copyright © 2017, Texas Instruments Incorporated




Figure 11. PMBus V_{OUT} Step-Down = 1.2 V to 0.6 V at 25 A




Figure 12. PMBUS Multiple Commands

Copyright © 2017, Texas Instruments Incorporated

11.4 Transient Response



Figure 13. Transient Response of 1-V Output at 12 V_{IN}, Transient is 0.5 A to 15.5 A, the Step is 15 A at 40 A/µs

11.5 Output Ripple




Figure 14. Output Ripple and SW Node of 1-V Output at 12 V_{IN}, 25-A Output

Copyright © 2017, Texas Instruments Incorporated




Figure 15. Output Ripple and SW Node of 1-V Output at 12 V_{IN}, 0-A Output

11.6 Control On




Figure 16. Start up from Control, 1-V Output at 12 V_{IN}, 0-A Output

Copyright © 2017, Texas Instruments Incorporated




Figure 17. 0.5-V Pre-bias start up from Control, 1-V Output at 12 V_{IN}, 10-A Output

11.7 Control Off



Figure 18. Start-Up and Shutdown, 1-V Output at 12 V_{IN}, 0.5-A Output

Copyright © 2017, Texas Instruments Incorporated

11.8 Thermal Image

Figure 19 illustrates the thermal image at 1-V output at 12 V_{IN}, 25-A output, 650 kHz at 25°C ambient.




Figure 19. Thermal Image at 1-V Output at 12 V_{IN}, 25-A Output, 650 kHz at 25°C Ambient

Copyright © 2017, Texas Instruments Incorporated

12 Fusion GUI

Figure 20 through Figure 23 illustrate the Fusion GUI launch and installation dialog windows.




Figure 20. First Window at Fusion Launch




Figure 21. Scan Finds Device Successfully



Figure 22. Software Launch Continued



Figure 23. Software Launch Continued

Copyright © 2017, Texas Instruments Incorporated

Use the *All Config* tab to configure all of the configurable parameters (Figure 24). The screen also shows other details like hexadecimal (hex) encoding. Use this screen to configure:

- Power Good Delay
- Power On Delay
- Mode Settings
- Frequency, RAMP, DCAP3
- VDD UVLO
- On/Off Configuration
- Track and Sequencing
- Write Protect
- VOUT Command Voltage
- VOUT Margin
- Operation




Figure 24. First Screen After Successful Launch
Configure: Limits and On/Off

Copyright © 2017, Texas Instruments Incorporated

Changing the frequency prompts a pop-up window with details of the options Figure 25).




Figure 25. Configure: Frequency- FS Configuration Pop-up

Copyright © 2017, Texas Instruments Incorporated

After a change is selected, orange **U** icon is displayed to offer *Undo Change* option. Change is not retained until either *Write to Hardware* or *Store Config to NVM* is selected. When *Write to Hardware* is selected, change is committed to volatile memory and defaults back to previous setting on input power cycle. When *Store Config to NVM* is selected, change is committed to nonvolatile memory and becomes the new default (Figure 26).




Figure 26. Configure: Frequency- FS Config Pop-Up with Change

Copyright © 2017, Texas Instruments Incorporated

After making changes to one or more configurable parameters, the changes can be committed to nonvolatile memory by selecting *Store Config to NVM*. This action prompts a *confirm selection* pop-up, and if confirmed, the changes are committed to nonvolatile memory (Figure 27).




Figure 27. Configure: *Store Config to NVM*

Copyright © 2017, Texas Instruments Incorporated

In the lower left corner, the different view screens can be changed. The view screens can be changed between *Configure*, *Monitor* and *Status* as needed (Figure 28).




Figure 28. Change View Screen to Monitor Screen

Copyright © 2017, Texas Instruments Incorporated

Selecting *System Dashboard* from mid-left screen adds a new window which displays system-level information (Figure 29).




Figure 29. System Dashboard

Copyright © 2017, Texas Instruments Incorporated

Selecting *Status* from lower left corner shows the status of the controller (Figure 30).




Figure 30. Status Screen

Copyright © 2017, Texas Instruments Incorporated

Selecting *Store User Configuration to Flash Memory* from the device pull-down menu has the same functionality as the *Store Config to NVM* button from the configure screen. It results in committing the current configuration to nonvolatile memory (Figure 31).




Figure 31. Store Configuration To Memory

Copyright © 2017, Texas Instruments Incorporated

Selecting *PMBus Logging* (Figure 32) from the Tools drop-down menu enables the logging of all PMBus activity. This includes communications traffic for each polling loop between the GUI and the device. The user is prompted to select a location for the file to be stored. See next screen (Figure 33).




Figure 32. PMBus Logging

Copyright © 2017, Texas Instruments Incorporated

Select the storage location for the file and the type of file. As shown (Figure 33), the file is a CSV file to be stored in the directory path shown. Logging begins when the *Start Logging* button is selected, and stops when it is reselected (as *Stop Logging*). This file can rapidly grow in size, so caution is advised when using this function.




Figure 33. PMBus Log Details

Copyright © 2017, Texas Instruments Incorporated

13 EVM Assembly Drawing and PCB Layout

Figure 34 through Figure 43 show the design of the PWR-847EVM printed-circuit board (PCB). The PWR-847EVM has a 2-oz. copper finish for all layers.




Figure 34. PWR-847EVM Top Layer Assembly Drawing (Top View)




Figure 35. PWR-847EVM Top Solder Mask (Top View)

Copyright © 2017, Texas Instruments Incorporated




Figure 36. PWR-847EVM Top Layer (Top View)




Figure 37. PWR-847EVM Inner Layer 1 (Top View)

Copyright © 2017, Texas Instruments Incorporated




Figure 38. PWR-847EVM Inner Layer 2 (Top View)




Figure 39. PWR-847EVM Inner Layer 3 (Top View)

Copyright © 2017, Texas Instruments Incorporated




Figure 40. PWR-847EVM Inner Layer 4 (Top View)




Figure 41. PWR-847EVM Bottom Layer (Top View)

Copyright © 2017, Texas Instruments Incorporated




Figure 42. PWR-847EVM Bottom Solder Mask (Top View)




Figure 43. PWR-847EVM Bottom Overlay Layer (Top View)

Copyright © 2017, Texas Instruments Incorporated

14 List of Materials

The EVM components list, according to the schematic, is shown in Table 6.

Table 6. PWR847 List of Materials

Designator	Qty	Value	Description	Package Reference	Part Number	Manufacturer	Alternate Part Number	Alternate Manufacturer
!PCB1	1		Printed Circuit Board		PWR847	Any		
C2, C3, C4, C5, C6, C7, C8, C9, C13	9	22uF	CAP, CERM, 22 µF, 25 V, +/- 10%, X7R, 1210	1210	GRM32ER71E226KE15L	Murata		
C10	1	2200pF	CAP, CERM, 2200 pF, 25 V, +/- 10%, X5R, 0402	0402	GRM155R61E222KA01D	Murata		
C11	1	100uF	CAP, AL, 100uF, 35V, +/-20%, 0.15 ohm, SMD	SMT Radial G	EEE-FC1V101P	Panasonic		
C22	1	0.1uF	CAP, CERM, 0.1 µF, 50 V, +/- 10%, X7R, 0603	0603	GRM188R71H104KA93D	Murata		
C24, C38	2	470uF	CAP, Tantalum Polymer, 470 µF, 2.5 V, +/- 20%, 0.006 ohm, 7.3x2.8x4.3mm SMD	7.3x2.8x4.3mm	2R5TPF470M6L	Panasonic		
C25, C26, C29, C33, C39, C40, C42	7	100uF	CAP, CERM, 100 µF, 6.3 V, +/- 20%, X5R, 1210	1210	GRM32ER60J107ME20L	Murata		
C35	1	1uF	CAP, CERM, 1 µF, 16 V, +/- 10%, X5R, 0603	0603	C0603C105K4PACTU	Kemet		
C45	1	4.7uF	CAP, CERM, 4.7 µF, 16 V, +/- 10%, X7R, 0805	0805	GRM21BR71C475KA73L	Murata		
H9, H10, H11, H12	4		Bumpon, Hemisphere, 0.44 X 0.20, Clear	Transparent Bumpon	SJ-5303 (CLEAR)	3M		
J1, J2, J3, J5	4		TERMINAL BLOCK 5.08MM VERT 2POS, TH	TERM_BLK, 2pos, 5.08mm	ED120/2DS	On-Shore Technology		
J4	1		Header, 100mil, 2x1, Tin, TH	Header, 2 PIN, 100mil, Tin	PEC02SAAN	Sullins Connector Solutions		
J6	1		Header (shrouded), 100mil, 5x2, Gold, TH	5x2 Shrouded header	5103308-1	TE Connectivity		
L1	1	330nH	Inductor, Shielded Drum Core, Ferrite, 330 nH, 50 A, 0.000165 ohm, SMD	12.5x13mm	744309033	Wurth Elektronik		
LBL1	1		Thermal Transfer Printable Labels, 0.650" W x 0.200" H - 10,000 per roll	PCB Label 0.650"H x 0.200"W	THT-14-423-10	Brady		
R1	1	1.00	RES, 1.00, 1%, 0.1 W, 0603	0603	RC0603FR-071RL	Yageo America		
R4, R7, R10, R11, R16	5	0	RES, 0, 5%, 0.1 W, 0603	0603	CRCW06030000Z0EA	Vishay-Dale		
R6	1	200k	RES, 200 k, 1%, 0.1 W, 0603	0603	CRCW0603200KFKEA	Vishay-Dale		
R8	1	1.10k	RES, 1.10 k, 1%, 0.1 W, 0603	0603	CRCW06031K10FKEA	Vishay-Dale		
R12, R13, R20, R21, R22	5	100k	RES, 100 k, 1%, 0.1 W, 0603	0603	CRCW0603100KFKEA	Vishay-Dale		
R15	1	10.0k	RES, 10.0k ohm, 1%, 0.1W, 0603	0603	CRCW060310K0FKEA	Vishay-Dale		
R19	1	61.9k	RES, 61.9 k, 1%, 0.1 W, 0603	0603	CRCW060361K9FKEA	Vishay-Dale		
R23	1	37.4k	RES, 37.4 k, 1%, 0.1 W, 0603	0603	CRCW060337K4FKEA	Vishay-Dale		
R24	1	42.2k	RES, 42.2 k, 1%, 0.1 W, 0603	0603	CRCW060342K2FKEA	Vishay-Dale		
R25	1	25.5k	RES, 25.5 k, 1%, 0.1 W, 0603	0603	CRCW060325K5FKEA	Vishay-Dale		

Copyright © 2017, Texas Instruments Incorporated

Table 6. PWR847 List of Materials (continued)

Designator	Qty	Value	Description	Package Reference	Part Number	Manufacturer	Alternate Part Number	Alternate Manufacturer
TP1, TP5, TP6, TP7, TP8, TP9, TP12, TP14, TP15, TP16, TP17, TP20, TP21, TP22	14	White	Test Point, Multipurpose, White, TH	White Multipurpose Testpoint	5012	Keystone		
TP2, TP3, TP4	3	Red	Test Point, Multipurpose, Red, TH	Red Multipurpose Testpoint	5010	Keystone		
TP10, TP11, TP13, TP18, TP19	5	Black	Test Point, Multipurpose, Black, TH	Black Multipurpose Testpoint	5011	Keystone		
U1	1		1.5-V to 16-V VIN, 4.5-V to 22-V VDD, 25-A SWIFT Synchronous Step-Down Converter with Full Differential Sense, RVF0040A (LQFN-CLIP-40)	RVF0040A	TPS549B22RVFR	Texas Instruments	TPS549B22RVFT	Texas Instruments
C1, C12	0	330uF	CAP, TA, 330 µF, 6.3 V, +/- 20%, 0.025 ohm, SMD	7.3x2.8x4.3mm	6TPE330ML	Sanyo		
C14, C15, C16, C17, C18, C19, C20	0	22uF	CAP, CERM, 22 µF, 25 V, +/- 10%, X7R, 1210	1210	GRM32ER71E226KE15L	Murata		
C21	0	470pF	CAP, CERM, 470 pF, 50 V, +/- 10%, X7R, 0603	0603	GRM188R71H471KA01D	Murata		
C23, C37	0	470uF	CAP, Tantalum Polymer, 470 µF, 2.5 V, +/- 20%, 0.006 ohm, 7.3x2.8x4.3mm SMD	7.3x2.8x4.3mm	2R5TPF470M6L	Panasonic		
C27, C28, C30, C41, C43	0	100uF	CAP, CERM, 100 µF, 6.3 V, +/- 20%, X5R, 1210	1210	GRM32ER60J107ME20L	Murata		
C31	0	0.1uF	CAP, CERM, 0.1 µF, 50 V, +/- 10%, X7R, 0603	0603	GRM188R71H104KA93D	Murata		
C32	0	6800pF	CAP, CERM, 6800 pF, 50 V, +/- 10%, X7R, 0603	0603	GRM188R71H682KA01D	Murata		
C34, C44	0	1uF	CAP, CERM, 1 µF, 16 V, +/- 10%, X5R, 0603	0603	C0603C105K4PACTU	Kemet		
C36	0	1000pF	CAP, CERM, 1000 pF, 25 V, +/- 10%, X7R, 0603	0603	GRM188R71E102KA01D	Murata		
C46	0	1000pF	CAP, CERM, 1000 pF, 50 V, +/- 5%, C0G/NP0, 0603	0603	C0603C102J5GACTU	Kemet		
FID1, FID2, FID3, FID4, FID5, FID6	0		Fiducial mark. There is nothing to buy or mount.	Fiducial	N/A	N/A		
R2, R3, R14, R17, R18	0	0	RES, 0, 5%, 0.1 W, 0603	0603	CRCW06030000Z0EA	Vishay-Dale		
R5	0	1.50k	RES, 1.50 k, 1%, 0.1 W, 0603	0603	RC0603FR-071K5L	Yageo America		
R9	0	3.01	RES, 3.01 ohm, 1%, 0.125W, 0805	0805	CRCW08053R01FKEA	Vishay-Dale		
	Notes:	Unless otherwise noted in the Alternate Part Number or Alternate Manufacturer columns, all parts may be substituted with equivalents.						

Copyright © 2017, Texas Instruments Incorporated

STANDARD TERMS FOR EVALUATION MODULES

1. *Delivery:* TI delivers TI evaluation boards, kits, or modules, including any accompanying demonstration software, components, and/or documentation which may be provided together or separately (collectively, an “EVM” or “EVMs”) to the User (“User”) in accordance with the terms set forth herein. User's acceptance of the EVM is expressly subject to the following terms.

   1.1 EVMs are intended solely for product or software developers for use in a research and development setting to facilitate feasibility evaluation, experimentation, or scientific analysis of TI semiconductors products. EVMs have no direct function and are not finished products. EVMs shall not be directly or indirectly assembled as a part or subassembly in any finished product. For clarification, any software or software tools provided with the EVM (“Software”) shall not be subject to the terms and conditions set forth herein but rather shall be subject to the applicable terms that accompany such Software

   1.2 EVMs are not intended for consumer or household use. EVMs may not be sold, sublicensed, leased, rented, loaned, assigned, or otherwise distributed for commercial purposes by Users, in whole or in part, or used in any finished product or production system.

2 *Limited Warranty and Related Remedies/Disclaimers*:

   2.1 These terms do not apply to Software. The warranty, if any, for Software is covered in the applicable Software License Agreement.

   2.2 TI warrants that the TI EVM will conform to TI's published specifications for ninety (90) days after the date TI delivers such EVM to User. Notwithstanding the foregoing, TI shall not be liable for a nonconforming EVM if (a) the nonconformity was caused by neglect, misuse or mistreatment by an entity other than TI, including improper installation or testing, or for any EVMs that have been altered or modified in any way by an entity other than TI, (b) the nonconformity resulted from User's design, specifications or instructions for such EVMs or improper system design, or (c) User has not paid on time. Testing and other quality control techniques are used to the extent TI deems necessary. TI does not test all parameters of each EVM. User's claims against TI under this Section 2 are void if User fails to notify TI of any apparent defects in the EVMs within ten (10) business days after delivery, or of any hidden defects with ten (10) business days after the defect has been detected.

   2.3 TI's sole liability shall be at its option to repair or replace EVMs that fail to conform to the warranty set forth above, or credit User's account for such EVM. TI's liability under this warranty shall be limited to EVMs that are returned during the warranty period to the address designated by TI and that are determined by TI not to conform to such warranty. If TI elects to repair or replace such EVM, TI shall have a reasonable time to repair such EVM or provide replacements. Repaired EVMs shall be warranted for the remainder of the original warranty period. Replaced EVMs shall be warranted for a new full ninety (90) day warranty period.

3 *Regulatory Notices:*

   3.1 *United States*

      3.1.1 *Notice applicable to EVMs not FCC-Approved:*

      FCC NOTICE: This kit is designed to allow product developers to evaluate electronic components, circuitry, or software associated with the kit to determine whether to incorporate such items in a finished product and software developers to write software applications for use with the end product. This kit is not a finished product and when assembled may not be resold or otherwise marketed unless all required FCC equipment authorizations are first obtained. Operation is subject to the condition that this product not cause harmful interference to licensed radio stations and that this product accept harmful interference. Unless the assembled kit is designed to operate under part 15, part 18 or part 95 of this chapter, the operator of the kit must operate under the authority of an FCC license holder or must secure an experimental authorization under part 5 of this chapter.

      3.1.2 *For EVMs annotated as FCC – FEDERAL COMMUNICATIONS COMMISSION Part 15 Compliant:*

      CAUTION

      This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

      Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

      FCC Interference Statement for Class A EVM devices

      NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

FCC Interference Statement for Class B EVM devices

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- *Reorient or relocate the receiving antenna.*
- *Increase the separation between the equipment and receiver.*
- *Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.*
- *Consult the dealer or an experienced radio/TV technician for help.*

3.2 *Canada*

3.2.1 *For EVMs issued with an Industry Canada Certificate of Conformance to RSS-210 or RSS-247*

Concerning EVMs Including Radio Transmitters:

This device complies with Industry Canada license-exempt RSSs. Operation is subject to the following two conditions:

(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Concernant les EVMs avec appareils radio:

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Concerning EVMs Including Detachable Antennas:

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication. This radio transmitter has been approved by Industry Canada to operate with the antenna types listed in the user guide with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Concernant les EVMs avec antennes détachables

Conformément à la réglementation d'Industrie Canada, le présent émetteur radio peut fonctionner avec une antenne d'un type et d'un gain maximal (ou inférieur) approuvé pour l'émetteur par Industrie Canada. Dans le but de réduire les risques de brouillage radioélectrique à l'intention des autres utilisateurs, il faut choisir le type d'antenne et son gain de sorte que la puissance isotrope rayonnée équivalente (p.i.r.e.) ne dépasse pas l'intensité nécessaire à l'établissement d'une communication satisfaisante. Le présent émetteur radio a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés dans le manuel d'usage et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur

3.3 *Japan*

3.3.1 *Notice for EVMs delivered in Japan:* Please see http://www.tij.co.jp/lsds/ti_ja/general/eStore/notice_01.page 日本国内に輸入される評価用キット、ボードについては、次のところをご覧ください。
http://www.tij.co.jp/lsds/ti_ja/general/eStore/notice_01.page

3.3.2 *Notice for Users of EVMs Considered "Radio Frequency Products" in Japan:* EVMs entering Japan may not be certified by TI as conforming to Technical Regulations of Radio Law of Japan.

If User uses EVMs in Japan, not certified to Technical Regulations of Radio Law of Japan, User is required to follow the instructions set forth by Radio Law of Japan, which includes, but is not limited to, the instructions below with respect to EVMs (which for the avoidance of doubt are stated strictly for convenience and should be verified by User):

1. Use EVMs in a shielded room or any other test facility as defined in the notification #173 issued by Ministry of Internal Affairs and Communications on March 28, 2006, based on Sub-section 1.1 of Article 6 of the Ministry's Rule for Enforcement of Radio Law of Japan,
2. Use EVMs only after User obtains the license of Test Radio Station as provided in Radio Law of Japan with respect to EVMs, or
3. Use of EVMs only after User obtains the Technical Regulations Conformity Certification as provided in Radio Law of Japan with respect to EVMs. Also, do not transfer EVMs, unless User gives the same notice above to the transferee. Please note that if User does not follow the instructions above, User will be subject to penalties of Radio Law of Japan.

【無線電波を送信する製品の開発キットをお使いになる際の注意事項】 開発キットの中には技術基準適合証明を受けていないものがあります。 技術適合証明を受けていないもののご使用に際しては、電波法遵守のため、以下のいずれかの措置を取っていただく必要がありますのでご注意ください。

1. 電波法施行規則第6条第1項第1号に基づく平成18年3月28日総務省告示第173号で定められた電波暗室等の試験設備でご使用いただく。
2. 実験局の免許を取得後ご使用いただく。
3. 技術基準適合証明を取得後ご使用いただく。

なお、本製品は、上記の「ご使用にあたっての注意」を譲渡先、移転先に通知しない限り、譲渡、移転できないものとします。

上記を遵守頂けない場合は、電波法の罰則が適用される可能性があることをご留意ください。 日本テキサス・インスツルメンツ株式会社

東京都新宿区西新宿６丁目２４番１号

西新宿三井ビル

3.3.3 *Notice for EVMs for Power Line Communication:* Please see http://www.tij.co.jp/lsds/ti_ja/general/eStore/notice_02.page

電力線搬送波通信についての開発キットをお使いになる際の注意事項については、次のところをご覧ください。http://www.tij.co.jp/lsds/ti_ja/general/eStore/notice_02.page

3.4 *European Union*

3.4.1 *For EVMs subject to EU Directive 2014/30/EU (Electromagnetic Compatibility Directive)*:

This is a class A product intended for use in environments other than domestic environments that are connected to a low-voltage power-supply network that supplies buildings used for domestic purposes. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

4 *EVM Use Restrictions and Warnings:*

4.1 EVMS ARE NOT FOR USE IN FUNCTIONAL SAFETY AND/OR SAFETY CRITICAL EVALUATIONS, INCLUDING BUT NOT LIMITED TO EVALUATIONS OF LIFE SUPPORT APPLICATIONS.

4.2 User must read and apply the user guide and other available documentation provided by TI regarding the EVM prior to handling or using the EVM, including without limitation any warning or restriction notices. The notices contain important safety information related to, for example, temperatures and voltages.

4.3 *Safety-Related Warnings and Restrictions:*

4.3.1 User shall operate the EVM within TI's recommended specifications and environmental considerations stated in the user guide, other available documentation provided by TI, and any other applicable requirements and employ reasonable and customary safeguards. Exceeding the specified performance ratings and specifications (including but not limited to input and output voltage, current, power, and environmental ranges) for the EVM may cause personal injury or death, or property damage. If there are questions concerning performance ratings and specifications, User should contact a TI field representative prior to connecting interface electronics including input power and intended loads. Any loads applied outside of the specified output range may also result in unintended and/or inaccurate operation and/or possible permanent damage to the EVM and/or interface electronics. Please consult the EVM user guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative. During normal operation, even with the inputs and outputs kept within the specified allowable ranges, some circuit components may have elevated case temperatures. These components include but are not limited to linear regulators, switching transistors, pass transistors, current sense resistors, and heat sinks, which can be identified using the information in the associated documentation. When working with the EVM, please be aware that the EVM may become very warm.

4.3.2 EVMs are intended solely for use by technically qualified, professional electronics experts who are familiar with the dangers and application risks associated with handling electrical mechanical components, systems, and subsystems. User assumes all responsibility and liability for proper and safe handling and use of the EVM by User or its employees, affiliates, contractors or designees. User assumes all responsibility and liability to ensure that any interfaces (electronic and/or mechanical) between the EVM and any human body are designed with suitable isolation and means to safely limit accessible leakage currents to minimize the risk of electrical shock hazard. User assumes all responsibility and liability for any improper or unsafe handling or use of the EVM by User or its employees, affiliates, contractors or designees.

4.4 User assumes all responsibility and liability to determine whether the EVM is subject to any applicable international, federal, state, or local laws and regulations related to User's handling and use of the EVM and, if applicable, User assumes all responsibility and liability for compliance in all respects with such laws and regulations. User assumes all responsibility and liability for proper disposal and recycling of the EVM consistent with all applicable international, federal, state, and local requirements.

5. *Accuracy of Information:* To the extent TI provides information on the availability and function of EVMs, TI attempts to be as accurate as possible. However, TI does not warrant the accuracy of EVM descriptions, EVM availability or other information on its websites as accurate, complete, reliable, current, or error-free.

6. *Disclaimers:*

   6.1 EXCEPT AS SET FORTH ABOVE, EVMS AND ANY MATERIALS PROVIDED WITH THE EVM (INCLUDING, BUT NOT LIMITED TO, REFERENCE DESIGNS AND THE DESIGN OF THE EVM ITSELF) ARE PROVIDED "AS IS" AND "WITH ALL FAULTS." TI DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, REGARDING SUCH ITEMS, INCLUDING BUT NOT LIMITED TO ANY EPIDEMIC FAILURE WARRANTY OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER INTELLECTUAL PROPERTY RIGHTS.

   6.2 EXCEPT FOR THE LIMITED RIGHT TO USE THE EVM SET FORTH HEREIN, NOTHING IN THESE TERMS SHALL BE CONSTRUED AS GRANTING OR CONFERRING ANY RIGHTS BY LICENSE, PATENT, OR ANY OTHER INDUSTRIAL OR INTELLECTUAL PROPERTY RIGHT OF TI, ITS SUPPLIERS/LICENSORS OR ANY OTHER THIRD PARTY, TO USE THE EVM IN ANY FINISHED END-USER OR READY-TO-USE FINAL PRODUCT, OR FOR ANY INVENTION, DISCOVERY OR IMPROVEMENT, REGARDLESS OF WHEN MADE, CONCEIVED OR ACQUIRED.

7. *USER'S INDEMNITY OBLIGATIONS AND REPRESENTATIONS.* USER WILL DEFEND, INDEMNIFY AND HOLD TI, ITS LICENSORS AND THEIR REPRESENTATIVES HARMLESS FROM AND AGAINST ANY AND ALL CLAIMS, DAMAGES, LOSSES, EXPENSES, COSTS AND LIABILITIES (COLLECTIVELY, "CLAIMS") ARISING OUT OF OR IN CONNECTION WITH ANY HANDLING OR USE OF THE EVM THAT IS NOT IN ACCORDANCE WITH THESE TERMS. THIS OBLIGATION SHALL APPLY WHETHER CLAIMS ARISE UNDER STATUTE, REGULATION, OR THE LAW OF TORT, CONTRACT OR ANY OTHER LEGAL THEORY, AND EVEN IF THE EVM FAILS TO PERFORM AS DESCRIBED OR EXPECTED.

8. *Limitations on Damages and Liability:*

   8.1 *General Limitations*. IN NO EVENT SHALL TI BE LIABLE FOR ANY SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THESE TERMS OR THE USE OF THE EVMS , REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. EXCLUDED DAMAGES INCLUDE, BUT ARE NOT LIMITED TO, COST OF REMOVAL OR REINSTALLATION, ANCILLARY COSTS TO THE PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, RETESTING, OUTSIDE COMPUTER TIME, LABOR COSTS, LOSS OF GOODWILL, LOSS OF PROFITS, LOSS OF SAVINGS, LOSS OF USE, LOSS OF DATA, OR BUSINESS INTERRUPTION. NO CLAIM, SUIT OR ACTION SHALL BE BROUGHT AGAINST TI MORE THAN TWELVE (12) MONTHS AFTER THE EVENT THAT GAVE RISE TO THE CAUSE OF ACTION HAS OCCURRED.

   8.2 *Specific Limitations.* IN NO EVENT SHALL TI'S AGGREGATE LIABILITY FROM ANY USE OF AN EVM PROVIDED HEREUNDER, INCLUDING FROM ANY WARRANTY, INDEMITY OR OTHER OBLIGATION ARISING OUT OF OR IN CONNECTION WITH THESE TERMS, , EXCEED THE TOTAL AMOUNT PAID TO TI BY USER FOR THE PARTICULAR EVM(S) AT ISSUE DURING THE PRIOR TWELVE (12) MONTHS WITH RESPECT TO WHICH LOSSES OR DAMAGES ARE CLAIMED. THE EXISTENCE OF MORE THAN ONE CLAIM SHALL NOT ENLARGE OR EXTEND THIS LIMIT.

9. *Return Policy.* Except as otherwise provided, TI does not offer any refunds, returns, or exchanges. Furthermore, no return of EVM(s) will be accepted if the package has been opened and no return of the EVM(s) will be accepted if they are damaged or otherwise not in a resalable condition. If User feels it has been incorrectly charged for the EVM(s) it ordered or that delivery violates the applicable order, User should contact TI. All refunds will be made in full within thirty (30) working days from the return of the components(s), excluding any postage or packaging costs.

10. *Governing Law:* These terms and conditions shall be governed by and interpreted in accordance with the laws of the State of Texas, without reference to conflict-of-laws principles. User agrees that non-exclusive jurisdiction for any dispute arising out of or relating to these terms and conditions lies within courts located in the State of Texas and consents to venue in Dallas County, Texas. Notwithstanding the foregoing, any judgment may be enforced in any United States or foreign court, and TI may seek injunctive relief in any United States or foreign court.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2017, Texas Instruments Incorporated

IMPORTANT NOTICE FOR TI DESIGN INFORMATION AND RESOURCES

Texas Instruments Incorporated ('TI") technical, application or other design advice, services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using any particular TI Resource in any way, you (individually or, if you are acting on behalf of a company, your company) agree to use it solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources.

You understand and agree that you remain responsible for using your independent analysis, evaluation and judgment in designing your applications and that you have full and exclusive responsibility to assure the safety of your applications and compliance of your applications (and of all TI products used in or for your applications) with all applicable regulations, laws and other applicable requirements. You represent that, with respect to your applications, you have all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. You agree that prior to using or distributing any applications that include TI products, you will thoroughly test such applications and the functionality of such TI products as used in such applications. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

You are authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING TI RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY YOU AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You agree to fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of your non-compliance with the terms and provisions of this Notice.

This Notice applies to TI Resources. Additional terms apply to the use and purchase of certain types of materials, TI products and services. These include; without limitation, TI's standard terms for semiconductor products http://www.ti.com/sc/docs/stdterms.htm), evaluation modules, and samples (http://www.ti.com/sc/docs/sampterms.htm).

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2017, Texas Instruments Incorporated