
# High Power Infrared Emitting Diode, 940 nm, GaAlAs/GaAs



94 8389

## FEATURES

- Package type: leaded
- Package form: T-1¾
- Dimensions (in mm): Ø 5
- Peak wavelength: $\lambda_p$ = 940 nm
- High reliability
- High radiant power
- High radiant intensity
- Angle of half intensity: φ = ± 22°
- Low forward voltage
- Suitable for high pulse current operation
- Good spectral matching with Si photodetectors
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC

RoHS COMPLIANT GREEN (5-2008)**

**Note**

** Please see document “Vishay Material Category Policy”: www.vishay.com/doc?99902

## DESCRIPTION

TSAL7300 is an infrared, 940 nm emitting diode in GaAlAs/GaAs technology with high radiant power molded in a clear, untinted plastic package.

## APPLICATIONS

- Infrared remote control units with high power requirements
- Free air transmission systems
- Infrared source for optical counters and card readers

## PRODUCT SUMMARY

| COMPONENT | $I_e$ (mW/sr) | φ (deg) | $\lambda_p$ (nm) | $t_r$ (ns) |
|---|---|---|---|---|
| TSAL7300 | 45 | ± 22 | 940 | 800 |

**Note**

- Test conditions see table “Basic Characteristics”

## ORDERING INFORMATION

| ORDERING CODE | PACKAGING | REMARKS | PACKAGE FORM |
|---|---|---|---|
| TSAL7300 | Bulk | MOQ: 4000 pcs, 4000 pcs/bulk | T-1¾ |

**Note**

- MOQ: minimum order quantity

## ABSOLUTE MAXIMUM RATINGS ($T_{amb}$ = 25 °C, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
|---|---|---|---|---|
| Reverse voltage | | $V_R$ | 5 | V |
| Forward current | | $I_F$ | 100 | mA |
| Peak forward current | $t_p/T$ = 0.5, $t_p$ = 100 µs | $I_{FM}$ | 200 | mA |
| Surge forward current | $t_p$ = 100 µs | $I_{FSM}$ | 1.5 | A |
| Power dissipation | | $P_V$ | 160 | mW |
| Junction temperature | | $T_j$ | 100 | °C |
| Operating temperature range | | $T_{amb}$ | - 40 to + 85 | °C |
| Storage temperature range | | $T_{stg}$ | - 40 to + 100 | °C |
| Soldering temperature | t ≤ 5 s, 2 mm from case | $T_{sd}$ | 260 | °C |
| Thermal resistance junction/ambient | J-STD-051, leads 7 mm soldered on PCB | $R_{thJA}$ | 230 | K/W |



For technical questions, contact: emittertechsupport@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 1 - Power Dissipation Limit vs. Ambient Temperature





Fig. 2 - Forward Current Limit vs. Ambient Temperature

| **BASIC CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | |
|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| Forward voltage | $I_F$ = 100 mA, $t_p$ = 20 ms | $V_F$ | | 1.35 | 1.6 | V |
| | $I_F$ = 1 A, $t_p$ = 100 µs | $V_F$ | | 2.6 | 3 | V |
| Temperature coefficient of $V_F$ | $I_F$ = 1 mA | $TK_{VF}$ | | - 1.8 | | mV/K |
| Reverse current | $V_R$ = 5 V | $I_R$ | | | 10 | µA |
| Junction capacitance | $V_R$ = 0 V, f = 1 MHz, E = 0 | $C_j$ | | 25 | | pF |
| Radiant intensity | $I_F$ = 100 mA, $t_p$ = 20 ms | $I_e$ | 30 | 45 | 150 | mW/sr |
| | $I_F$ = 1 A, $t_p$ = 100 µs | $I_e$ | 260 | 350 | | mW/sr |
| Radiant power | $I_F$ = 100 mA, $t_p$ = 20 ms | $\phi_e$ | | 35 | | mW |
| Temperature coefficient of $\phi_e$ | $I_F$ = 20 mA | $TK\phi_e$ | | - 0.6 | | %/K |
| Angle of half intensity | | $\varphi$ | | ± 22 | | deg |
| Peak wavelength | $I_F$ = 100 mA | $\lambda_p$ | | 940 | | nm |
| Spectral bandwidth | $I_F$ = 100 mA | $\Delta\lambda$ | | 50 | | nm |
| Temperature coefficient of $\lambda_p$ | $I_F$ = 100 mA | $TK\lambda_p$ | | 0.2 | | nm/K |
| Rise time | $I_F$ = 100 mA | $t_r$ | | 800 | | ns |
| | $I_F$ = 1 A | $t_r$ | | 500 | | ns |
| Fall time | $I_F$ = 100 mA | $t_f$ | | 800 | | ns |
| | $I_F$ = 1 A | $t_f$ | | 500 | | ns |
| Virtual source diameter | Method: 63 % encircled energy | d | | 2.3 | | mm |


For technical questions, contact: emittertechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

**BASIC CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified)





Fig. 3 - Pulse Forward Current vs. Pulse Duration





Fig. 6 - Radiant Power vs. Forward Current





Fig. 4 - Forward Current vs. Forward Voltage





Fig. 7 - Relative Radiant Intensity/Power vs. Ambient Temperature





Fig. 5 - Radiant Intensity vs. Forward Current





Fig. 8 - Relative Radiant Power vs. Wavelength


For technical questions, contact: emittertechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000






Fig. 9 - Relative Radiant Intensity vs. Angular Displacement

## **PACKAGE DIMENSIONS** in millimeters




6.544-5259.05-4
Issue: 8; 19.05.09
96 12126


For technical questions, contact: emittertechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**