TX3-801B


SMD TCXO
Clipped sine wave

QuartzCom
the communications company

Features

- Applications: mobile communications, GPS, instrumentation, microwave
- Frequency range up to 50 MHz
- Tight frequency stability vs. temperature
- Low phase noise


Parameter	Specification		
	TX3-801BL	TX3-801BM	TX3-801BS
Frequency range	9.6 ~ 50 MHz		
Standard frequencies	10.00, 13.00, 16.384, 19.20, 19.44, 20.00, 20.48 & 27.00 MHz		
Frequency stability:			
vs. temperature	≤ ±1.0 ~ ± 2.5 ppm		
vs. supply & load change	≤ ±0.2 ppm		±5 %
vs. aging	≤ ±1.0 ppm		1st year
Frequency tolerance ex. factory	≤ ±0.5 ppm		@ +25 °C
Supply voltage	+3.0 V ±5 %	+3.3 V ±5 %	+5.0 V ±5 %
Supply current	1.5 ~ 4 mA		
Output signal	> 0.8 Vp-p		clipped sine wave
Output load	10 kΩ // 10 pF		
Frequency adjustment	> ± 3 ppm		by internal trimmer
Phase noise @ 13.0 MHz carrier frequency	-140 dBc/Hz		@ 1 kHz
Operating temperature range	-30 ~ +75 °C -40 ~ +85 °C		commercial application industrial application
Storage temperature range	-55 ~ +125 °C		
Packaging units	tape & reel		500 or 1'000 pieces
Customer specifications on request			



Pin function


# 1	not connected
# 2	GND
# 3	Output
# 4	Vdc

Example for solder pattern



Do not design any conductive path between the pattern

Example for IR reflow soldering temperature



2002/95/EC RoHS compliant

30 Apr. 10

QuartzCom AG
sales@quartzcom.com

QuartzCom Asia
sales-asia@quartzcom.com

QuartzCom USA
sales-usa@quartzcom.com

www.quartzcom.com

ISO 9001 BUREAU VERITAS Certification