LINEAR SYSTEMS


Twenty-Five Years Of Quality Through Innovation

SST/U401 – SST/U406

LOW NOISE LOW DRIFT MONOLITHIC DUAL N-CHANNEL JFET AMPLIFIER

FEATURES	
LOW DRIFT	$\lvert V_{GS1-2}/T \rvert$ = 10µV/ºC TYP.
LOW NOISE	e_n=6nV/Hz@10Hz TYP.
LOW PINCHOFF	V_P=2.5V MAX.

ABSOLUTE MAXIMUM RATINGS NOTE 1 @ 25 °C (unless otherwise noted)		
Maximum Temperatures		
Storage Temperature		-55 to +150°C
Operating Junction Temperature		-55 to +150°C
Maximum Voltage and Current for Each Transistor NOTE 1		
$-V_{GSS}$	Gate Voltage to Drain or Source	50V
$-V_{DSO}$	Drain to Source Voltage	50V
$-I_{G(f)}$	Gate Forward Current	10mA
Maximum Power Dissipation per side NOTE 2		
Device Dissipation TA = 25°C		300mW



TO-71 Top View

SOIC Top View

MATCHING CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	U401	U402	U403	U404	U405	U406	UNITS	CONDITIONS
$\lvert V_{GS1-2}/T \rvert$ max.	Drift vs. Temperature	10	10	25	25	40	80	µV/ºC	V_{DG} = 10V, I_D = 200µA T_A = -55ºC to +125ºC
$\lvert V_{GS1-2} \rvert$ max.	Offset Voltage	5	10	10	15	20	40	mV	V_{DG} = 10V, I_D = 200µA

ELECTRICAL CHARACTERISTICS TA = 25ºC (unless otherwise noted) NOTE 3


SYMBOL	CHARACTERISTIC	MIN.	TYP.	MAX.	UNITS	CONDITIONS
BV_{GSS}	Breakdown Voltage	-50	-60	--	V	V_{DS}= 0 I_D= 1nA
BV_{G1G2}	Gate-to-Gate Breakdown	±50	--	--	V	I_G= ±1µA I_D= 0, I_S = 0
	TRANSCONDUCTANCE					
G_{fss}	Full Conduction	2000	--	7000	µS	V_{DG}= 10V V_{GS}= 0 f = 1kHz
G_{fs}	Typical Operation	1000	--	2000	µS	V_{DG}= 15V I_D= 200µA f = 1kHz
$\lvert G_{fs1}/G_{fs2} \rvert$	Mismatch	0.97	--	1.0		
I_{DSS}	Saturation Drain Current	0.5	--	10	mA	V_{DG}= 10V V_{GS}= 0
$\frac{I_{DSS1}}{I_{DSS2}}$	Saturation Current Ratio	0.9	0.98	1.0		
	GATE VOLTAGE					
V_{GS}(off) or V_P	Pinchoff Voltage	-0.5	--	-2.5	V	V_{DS}= 15V I_D= 1nA
V_{GS}	Operating Range	--	--	-2.3	V	V_{DS}= 15V I_D= 200µA
	GATE CURRENT					
I_G	Operating	--	-4	-15	pA	V_{DG}= 15V I_D= 200µA
I_G	High Temperature	--	--	-10	nA	T_A=+125ºC
I_{GSS}	Gate Reverse Current	--	--	-100	pA	V_{GS}=-30v, V_{DS}= 0V
I_{G1G2}	Gate to Gate Isolation Current	--	--	±1.0	µA	V_{G1}-V_{G2}= ±50V, I_D= IS= 0

Linear Integrated Systems

• 4042 Clipper Court • Fremont, CA 94538 • Tel: 510 490-9160 • Fax: 510 353-0261

Doc 201123 03/18/2015 Rev#A8 ECN# SST/U401 SST/U406

SYMBOL	CHARACTERISTIC	MIN.	TYP.	MAX.	UNITS	CONDITIONS
	OUTPUT CONDUCTANCE					
G_{OSS}	Full Conduction	--	--	40	µS	V_{DS}= 10V, V_{GS}= 0V, f = 1kHz
G_{OS}	Operating	--	2	2.7	µS	V_{DS}= 15V, I_D= 200µA, f = 1kHz
	COMMON MODE REJECTION					V_{DG1}= 10V
CMRR	-20 log [(V_{GS1}-V_{GS2})/ΔV_{DG1-2}]	95	--	--	dB	V_{DG2}= 20V I_{D1}= I_{D2}=200µA
	NOISE					
NF	Figure	--	--	0.5	dB	V_{DS}= 15V V_{GS}= 0 R_G=10M f= 100Hz NBW= 6Hz
e_n	Voltage	--	6	20	nV/Hz	V_{DS}= 15V I_D= 200µA f= 10Hz NBW= 1Hz
	CAPACITANCE					
C_{ISS}	Input	--	4	8	pF	V_{DS}= 15V I_D= 200µA f= 1MHz
C_{RSS}	Reverse Transfer	--	1.5	3	pF	



Note: All Dimensions in inches

NOTES:

1. These ratings are limiting values above which the serviceability of any semiconductor may be impaired.
2. Derate 2.4mW/ºC when TA is greater than 25ºC
3. All MIN/TYP/MAX limits are absolute numbers. Negative signs indicate electrical polarity only.

Information furnished by Linear Integrated Systems is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.

Linear Integrated Systems (LIS) is a 25-year-old, third-generation precision semiconductor company providing high-quality discrete components. Expertise brought to LIS is based on processes and products developed at Amelco, Union Carbide, Intersil and Micro Power Systems by company President John H. Hall. Hall, a protégé of Silicon Valley legend Dr. Jean Hoerni, was the director of IC Development at Union Carbide, Co-Founder and Vice President of R&D at Intersil, and Founder/President of Micro Power Systems.

Linear Integrated Systems

• 4042 Clipper Court • Fremont, CA 94538 • Tel: 510 490-9160 • Fax: 510 353-0261