



U74ACT02

CMOS IC


QUADRUPLE 2-INPUT POSITIVE-NOR GATES

DESCRIPTION

The UTC **U74ACT02** contains four independent 2-input positive-nor gates. Each Gate Performs the Boolean function $Y = \overline{A + B}$ or $Y = \overline{A} \cdot \overline{B}$

FEATURES

- * Operation Voltage Range: 4.5~5.5V
- * Low Power Dissipation: $I_{CC} = 2\mu A$ (Max.)
- * High Noise Immunity
- * Compatible With TTL Output




TSSOP-14

ORDERING INFORMATION


Ordering Number	Package	Packing
U74ACT02G-P14-R	TSSOP-14	Tape Reel

U74ACT02G-P14-R	
(1) Packing Type	(1) R: Tape Reel
(2) Package Type	(2) P14: TSSOP-14
(3) Green Package	(3) G: Halogen Free and Lead Free

MARKING



■ PIN CONFIGURATION




■ FUNCTION TABLE

INPUT(A)	INPUT(B)	OUTPUT(Y)
H	X	L
X	H	L
L	L	H

H = High voltage level ; L = Low voltage level ; X = Don't care

■ LOGIC DIAGRAM (positive gate)



■ ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	CONDITIONS	RATINGS	UNIT
Supply Voltage	V_{CC}		-0.5 ~ +7.0	V
Input Voltage	V_{IN}		-0.5 ~ + $V_{CC}+0.5$	V
Output Voltage	V_{OUT}		-0.5 ~ + $V_{CC}+0.5$	V
Continuous Output Current	I_{OUT}	$V_{OUT}=0V \sim V_{CC}$	±50	mA
Input Clamp Current	I_{IK}	$V_{IN} < 0$ or $V_{IN} > V_{CC}$	±20	mA
Output Clamp Current	I_{OK}	$V_{OUT} < 0$ or $V_{OUT} > V_{CC}$	±20	mA
Continuous Current Through V_{CC} or GND	I_{CC}		±200	mA
Storage Temperature Range	T_{STG}		-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		4.5		5.5	V
Input Voltage	V_{IN}		0		V_{CC}	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Transition Rise or Fall Rate	$\Delta t/\Delta v$				10	ns/V
Operating Temperature	T_A		-40		+85	°C

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High Level Input Voltage	V_{IH}	$V_{CC}=4.5\sim 5.5V$	2			V
Low Level Input Voltage	V_{IL}	$V_{CC}=4.5\sim 5.5V$			0.8	V
High-Level Output Voltage	V_{OH}	$V_{CC}=4.5V$	$I_{OH}=-24mA$	3.86		V
			$I_{OH}=-50\mu A$	4.4	4.49	V
		$V_{CC}=5.5V$	$I_{OH}=-24mA$	4.86		V
			$I_{OH}=-50\mu A$	5.4	5.49	V
Low-Level Output Voltage	V_{OL}	$V_{CC}=4.5V$	$I_{OL}=24mA$		0.36	V
			$I_{OL}=50\mu A$		0.001	V
		$V_{CC}=5.5V$	$I_{OL}=24mA$		3.6	V
			$I_{OL}=50\mu A$	0.001	0.1	V
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=5.5V, V_{IN}=V_{CC}$ or GND			±0.1	μA
Quiescent Supply Current	I_{CC}	$V_{CC}=5.5V, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0A$			2	μA
Additional Quiescent Supply Current Per Input Pin	ΔI_{CC}	$V_{CC}=5.5V$, One input at 3.4V, Other inputs at V_{CC} or GND		0.6		mA
Input Capacitance	C_I	$V_{CC}=5V, V_{IN}=V_{CC}$ or GND		2.6		pF


■ SWITCHING CHARACTERISTICS ($C_L=50pF, R_L=500\Omega, T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from input (A or B) to output(Y)	t_{PLH} / t_{PHL}	$V_{CC}=5V\pm 0.5V$	1.0	6.5	9.0	ns


■ OPERATING CHARACTERISTICS ($C_L=50pF, f=10MHz, T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	$V_{CC}=5.0V$		40		pF

■ TEST CIRCUIT AND WAVEFORMS



Note : C_L includes probe and jig capacitance.



Notes: 1. C_L includes probe and jig capacitance.

2. All input pulses are supplied by generators having the following characteristics: PRR ≤ 1 MHz, $Z_O = 50\Omega$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.