

U74AHC08

CMOS IC

QUADRUPLE 2-INPUT POSITIVE-AND GATES



SOP-14



TSSOP-14

■ DESCRIPTION

The **U74AHC08** is QUADRUPLE 2-INPUT POSITIVE-AND GATES. Which provides the Function Y=A*B.

■ FEATURES

* Operation voltage range: 2~5.5V
* Max t_{PD} of 7.9 ns at 5 V
* Low power consumption, I_{CC}=2μA(Max)
* ±8mA output drive at 5 V

■ ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74AHC08L-S14-R	U74AHC08G-S14-R	SOP-14	Tape Reel
U74AHC08L-P14-R	U74AHC08G-P14-R	TSSOP-14	Tape Reel


U74AHC08G-S14-R

(1)Packing Type
(2)Package Type
(3)Halogen Free

(1) R: Tape Reel
(2) S14: SOP-14, P14: TSSOP-14
(3) L: Lead Free, G:Halogen Free

Copyright © 2012 Unisonic Technologies Co., Ltd


■ PIN CONFIGURATION



■ FUNCTION TABLE (Each Gate)

INPUT (A)	INPUT (B)	OUTPUT (Y)
L	L	L
L	H	L
H	L	L
H	H	H

■ LOGIC DIAGRAM (Positive Logic)



ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5~7	V
Input Voltage	V_{IN}	-0.5~7	V
Output Voltage	V_{OUT}	-0.5~V_{CC}+0.5	V
Input Clamp Current	I_{IK}	-20	mA
Output Clamp Current	I_{OK}	±20	mA
Output Current	I_{OUT}	±25	mA
V_{CC} or GND Current	I_{CC}	±50	mA
Storage Temperature	T_{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2		5.5	V
Input Voltage	V_{IN}		0		5.5	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Transition Rise or Fall Rate	t_R, t_F	V_{CC}=3.3±0.3V			100	ns/V
		V_{CC}=5.0±0.5V			20	
Ambient Operating Temperature	T_{OPR}		-40		85	°C

■ STATIC CHARACTERISTICS (T_A=25°C)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
High-Level Input Voltage	V_{IH}	V_{CC}=2.0V		1.5			V
		V_{CC}=3.0V		2.1			
		V_{CC}=5.5V		3.85			
Low-Level Input Voltage	V_{IL}	V_{CC}=2.0V				0.5	V
		V_{CC}=3.0V				0.9	
		V_{CC}=5.5V				1.65	
High-Level Output Voltage	V_{OH}	V_{CC}=2.0V	I_{OH}=-50μA	1.9	2.0		V
		V_{CC}=3.0V		2.9	3.0		
		V_{CC}=4.5V		4.4	4.5		
		V_{CC}=3.0V, I_{OH}=-4mA		2.58			
		V_{CC}=4.5V, I_{OH}=-8mA		3.94			
Low-Level Output Voltage	V_{OL}	V_{CC}=2.0V	I_{OL}=50μA			0.1	V
		V_{CC}=3.0V				0.1	
		V_{CC}=4.5V				0.1	
		V_{CC}=3.0V, I_{OL}=4mA				0.36	
		V_{CC}=4.5V, I_{OL}=8mA				0.36	
Input Leakage Current	$I_{I(LEAK)}$	V_{CC}=0~5.5V, V_{IN}=5.5 or GND				±0.1	μA
Quiescent Supply Current	I_Q	V_{CC}=5.5V, V_{IN}=V_{CC} or GND, I_{OUT}=0				2	μA
Input Capacitance	C_{IN}	V_{CC}=5.0V, V_{IN}=V_{CC} or GND			4	10	pF


■ DYNAMIC CHARACTERISTICS (Input: t_R, t_F≤3ns; PRR≤1MHz)

PARAMETER	SYMBOL	V_{CC}(V)	MIN	TYP	MAX	UNIT
Propagation Delay from Input (A and B) to Output(Y)	t_{PLH}	V_{CC}=3.3±0.3V, C_L=15pF		6.2	8.8	ns
	t_{PHL}			6.2	8.8	
	t_{PLH}	V_{CC}=3.3±0.3V, C_L=50pF		8.7	12.3	
	t_{PHL}			8.7	12.3	
Propagation Delay from Input (A and B) to Output(Y)	t_{PLH}	V_{CC}=5.0±0.5V, C_L=15pF		4.3	5.9	ns
	t_{PHL}			4.3	5.9	
	t_{PLH}	V_{CC}=5.0±0.5V, C_L=50pF		5.8	7.9	
	t_{PHL}			5.8	7.9	


■ OPERATING CHARACTERISTICS (V_{CC}=5V; T_A=25°C)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	No load, f=1MHz		18		pF

■ TEST CIRCUIT AND WAVEFORMS



C_L includes probe and jig capacitance.



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.