

U74HC21

CMOS IC

DUAL 4-INPUT AND GATES



SOP-14



TSSOP-14

■ DESCRIPTION

The **U74HC21** contains two independent 4-input AND gates.They perform the Boolean function $Y=A \bullet B \bullet C \bullet D$ or $Y=\overline{\overline{A}+\overline{B}+\overline{C}+\overline{D}}$ in positive logic.

■ FEATURES

* Operation Voltage Range: 2~6V
* Low Quiescent Current: I_{CC}=2μA(Max)
* High Speed: t_{PD}=11ns(Typ)
* Low Input Current: 100nA Max



■ ORDERING INFORMATION

Ordering Number	Package	Packing
U74HC21G-S14-R	SOP-14	Tape Reel
U74HC21G-P14-R	TSSOP-14	Tape Reel

U74HC21G-P14-R
- (1)Packing Type
- (2)Packing Type
- (3)Green Package


(1) R: Tape Reel
(2) S14: SOP-14, P14: TSSOP-14
(3) G: Halogen Free and Lead Free

■ MARKING

SOP-14	TSSOP-14
	

Copyright © 2015 Unisonic Technologies Co., Ltd


■ PIN CONFIGURATION



■ FUNCTION TABLE

INPUT(A)	INPUT(B)	INPUT(C)	INPUT(D)	OUTPUT(Y)
H	H	H	H	H
L	X	X	X	L
X	L	X	X	L
X	X	L	X	L
X	X	X	L	L

■ LOGIC DIAGRAM



■ ABSOLUTE MAXIMUM RATING (T_A = 25°C ,unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5~7	V
Input Clamp Current	I_{IK}	-20	mA
Output Clamp Current	I_{OK}	±20	mA
Output Current	I_{OUT}	±25	mA
V_{CC} or GND Current	I_{CC}	±50	mA
Storage Temperature	T_{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2		6	V
Input Voltage	V_{IN}		0		Vcc	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Transition Rise or Fall Rate	t_R, t_F	V_{CC}=2V			1000	ns
		V_{CC}=4.5V			500	
		V_{CC}=6V			400	
Operating Temperature	T_A		-40		85	°C

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOP-14	θ_{JA}	76	°C/W
	TSSOP-14		113	

■ STATIC CHARACTERISTICS (T_A = 25°C)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-Level Input Voltage	V_{IH}	V_{CC}= 2 V	1.5			V
		V_{CC}= 4.5V	3.15			
		V_{CC}= 6 V	4.2			
Low-Level Input Voltage	V_{IL}	V_{CC}= 2 V			0.5	V
		V_{CC}= 4.5 V			1.35	
		V_{CC}= 6 V			1.8	
High-Level Output Voltage	V_{OH}	V_{CC}= 2V, I_{OH} = 20μA	1.9	1.998		V
		V_{CC}= 4.5V, I_{OH} = 20μA	4.4	4.999		
		V_{CC}= 6V, I_{OH} = 20μA	5.9	5.999		
		V_{CC}= 4.5V, I_{OH} = 4mA	3.98	4.3		
		V_{CC}= 6V, I_{OH} = 5.2mA	5.48	5.8		
Low-Level Output Voltage	V_{OL}	V_{CC}= 2V, I_{OL} = 20μA		0.002	0.1	V
		V_{CC}= 4.5V, I_{OL} = 20μA		0.001	0.1	
		V_{CC}= 6V, I_{OL} = 20μA		0.001	0.1	
		V_{CC}= 4.5V, I_{OL} = 4mA		0.17	0.26	
		V_{CC}= 6V, I_{OL} = 5.2mA		0.15	0.26	
Input Leakage Current	$I_{I(LEAK)}$	V_{CC}= 6V ,V_{IN} = V_{CC} or GND		±0.1	±100	nA
Quiescent Supply Current	I_Q	V_{CC}= 6V, V_{IN} = V_{CC} or GND, I_{OUT} = 0			2	μA
Input Capacitance	C_{IN}	V_{CC}=2V~6V		3	10	pF


■ DYNAMIC CHARACTERISTICS (T_A=25°C, Input: t_R=t_F=6ns, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from Input(A, B, C or D) to Output(Y)	t_{PLH} / t_{PHL}	V_{CC}=2V, C_L=50pF		44	110	ns
		V_{CC}=4.5V, C_L=50pF		14	22	
		V_{CC}=6V, C_L=50pF		11	19	
Output Transition Time	t_T	V_{CC}=2V, C_L=50pF		29	75	ns
		V_{CC}=4.5V, C_L=50pF		10	15	
		V_{CC}=6V, C_L=50pF		8	13	


■ OPERATING CHARACTERISTICS (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	RATINGS	UNIT
Power Dissipation Capacitance	C_{PD}	No Load	25	pF

■ TEST CIRCUIT AND WAVEFORMS



Note : C_L includes probe and jig capacitance.



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.