
U74LVC1G126

CMOS IC

BUS BUFFER/LINE DRIVER; 3-STATE



■ DESCRIPTION

The **U74LVC1G126** is single bus buffer/line driver with 3-state output. The output is disabled When the output enable (OE) is low. When OE is high, true data is will pass A input to the Y output.

This device has power-down protective circuit preventing device from destruction when it is powered down.

■ FEATURES


* Operate From 1.65V to 5.5V
* Inputs Accept Voltages to 5.5V
* High Noise Immunity
* Low Power Dissipation
* Direct Interface With TTL level

■ ORDERING INFORMATION

Ordering Number	Package	Packing
U74LVC1G126-AE5-R	SOT-23-5	Tape Reel
U74LVC1G126-AF5-R	SOT-25	Tape Reel
U74LVC1G126-AL5-R	SOT-353	Tape Reel


U74LVC1G126G-AF5-R (1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) AE5: SOT-23-5, AF5: SOT-25, AL5: SOT-353 (3) G: Halogen Free and Lead Free

■ MARKING



Copyright © 2015Unisonic Technologies Co., Ltd

■ PIN CONFIGURATION




■ FUNCTION TABLE


INPUT(OE)	INPUT(A)	OUTPUT(Y)
H	L	L
H	H	H
L	X	Z

Note: H: HIGH voltage level; L: LOW voltage level; X=don't care; Z=high-impedance OFF-state.

■ LOGIC DIAGRAM (Positive Logic)



Logic Symbol



IEC Logic Symbol

■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		V_{CC}	-0.5 ~ +6.5	V
Input Voltage		V_{IN}	-0.5 ~ +6.5	V
Output Voltage	Enable mode	V_{OUT}	-0.5 ~ V_{CC} + 0.5	V
	Disable mode		-0.5 ~ +6.5	V
	Power-down mode		-0.5 ~ +6.5	V
V_{CC} or GND Current		I_{CC}	±100	mA
Continuous Output Current (V_{OUT}=0 to V_{CC})		I_{OUT}	±50	mA
Input Clamp Current (V_{IN}<0)		I_{IK}	-50	mA
Output Clamp Current (V_{OUT}>V_{CC} or V_{OUT}<0)		I_{OK}	±50	mA
Power Dissipation (T_A=-40°C ~ +125°C)	SOT-23-5	P_D	300	mW
	SOT-25		360	
	SOT-353		250	
Operating Temperature		T_{OPR}	-40 ~ +125	°C
Storage Temperature		T_{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}	Operating	1.65		5.5	V
Input Voltage	V_{IN}		0		5.5	V
Output Voltage	V_{OUT}	V_{CC}=1.65V ~ 5.5V; Enable mode	0		V_{CC}	V
		V_{CC}=1.65V ~ 5.5V; Disable mode	0		5.5	V
		V_{CC}=0V; Power-Down Mode	0		5.5	V
Input Transition Rise or Fall Rate	t_R / t_F	V_{CC}=1.65V ~ 2.7V			20	ns/V
		V_{CC}=2.7V ~ 5.5V			10	ns/V

■ ELECTRICAL CHARACTERISTICS (T_A =25°C , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-Level Input Voltage	V_{IH}	V_{CC}=1.65V ~ 1.95V	0.65×V_{CC}			V
		V_{CC}=2.3V ~ 2.7V	1.7			V
		V_{CC}=2.7V ~ 3.6V	2			V
		V_{CC}=4.5V ~ 5.5V	0.7×V_{CC}			V
Low-Level Input Voltage	V_{IL}	V_{CC}=1.65V ~ 1.95V			0.35×V_{CC}	V
		V_{CC}=2.3V ~ 2.7V			0.7	V
		V_{CC}=2.7V ~ 3.6V			0.8	V
		V_{CC}=4.5V ~ 5.5V			0.3×V_{CC}	V
High-Level Output Voltage	V_{OH}	V_{CC}=1.65 ~ 5.5V, I_{OH}=-100μA	V_{CC}-0.1			V
		V_{CC}=1.65V, I_{OH}=-4mA	1.2			V
		V_{CC}=2.3V, I_{OH}=-8mA	1.9			V
		V_{CC}=2.7V, I_{OH}=-12mA	2.2			V
		V_{CC}=3.0V, I_{OH}=-24mA	2.3			V
		V_{CC}=4.5V, I_{OH}=-32mA	3.8			V
Low-Level Output Voltage	V_{OL}	V_{CC}=1.65 ~ 5.5V, I_{OL}=100μA			0.1	V
		V_{CC}=1.65V, I_{OL}=4mA			0.45	V
		V_{CC}=2.3V, I_{OL}=8mA			0.3	V
		V_{CC}=2.7V, I_{OL}=12mA			0.4	V
		V_{CC}=3.0V, I_{OL}=24mA			0.55	V
		V_{CC}=4.5V, I_{OL}=32mA			0.55	V


■ ELECTRICAL CHARACTERISTICS(Cont.)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Leakage Current	$I_{I(LEAK)}$	V_{CC}=5.5V, V_{IN}=5.5V or GND		±0.1	±5	μA
Power OFF Leakage Current	I_{OFF}	V_{CC}=0V, V_{IN} or V_{OUT}=5.5V		±0.1	±10	μA
3-State Output OFF-State Current	I_{OZ}	V_{CC} =5.5V V_{IN}=V_{IH} or V_{IL}, V_{OUT}=V_{CC} or GND		±0.1	±10	μA
Quiescent Supply Current	I_{CC}	V_{CC}=5.5V, V_{IN}=V_{CC} or GND, I_{OUT}=0		0.1	10	μA
Additional Quiescent Supply Current Per Input Pin	ΔI_{CC}	V_{CC}=2.3 ~ 5.5V, V_{IN}=V_{CC}-0.6V, I_{OUT}=0		5	500	μA

■ SWITCHING CHARACTERISTICS (T_A =25°C , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Propagation Delay From Input A to Output Y	t_{PLH} / t_{PHL}	C_L=30pF	V_{CC}=1.8±0.15V, R_L=1KΩ	1.0	3.0	8.0	ns
			V_{CC}=2.5±0.2V, R_L=500Ω	0.5	2.1	5.5	ns
		C_L=50pF, R_L=500Ω	V_{CC}=2.7V	0.5	2.3	5.5	ns
			V_{CC}=3.3±0.3V	0.5	2.0	4.5	ns
			V_{CC}=5±0.5V	0.5	1.7	4.0	ns
3-State Output Enable Time From Input OE to Output Y	t_{PZH} / t_{PZL}	C_L=30pF	V_{CC}=1.8±0.15V, R_L=1KΩ	1.0	3.2	9.4	ns
			V_{CC}=2.5±0.2V, R_L=500Ω	0.5	2.2	6.6	ns
		C_L=50pF, R_L=500Ω	V_{CC}=2.7V	0.5	2.4	6.6	ns
			V_{CC}=3.3±0.3V	0.5	2.1	5.3	ns
			V_{CC}=5±0.5V	0.5	1.6	5.0	ns
3-State Output Disable Time From Input OE to Output Y	t_{PLZ} / t_{PLH}	C_L=30pF	V_{CC}=1.8±0.15V, R_L=1KΩ	1.0	4.3	9.2	ns
			V_{CC}=2.5±0.2V, R_L=500Ω	0.5	2.7	5.5	ns
		C_L=50pF, R_L=500Ω	V_{CC}=2.7V	0.5	3.4	5.5	ns
			V_{CC}=3.3±0.3V	0.5	3.0	5.5	ns
			V_{CC}=5±0.5V	0.5	2.2	4.2	ns


■ TEST CIRCUIT AND WAVEFORMS




TEST	S
t_{PLH}/t_{PHL}	Open
t_{PHZ}/t_{PZH}	GND
t_{PLZ}/t_{PZL}	V_{LOAD}

TEST CIRCUIT

V_{CC}	INPUTS		V_M	V_{LOAD}	V_Δ	C_L	R_L
	V_{IN}	t_R, t_F					
1.8V±0.15V	V_{CC}	≤2ns	$V_{CC}/2$	$2\times V_{CC}$	0.15V	30pF	1KΩ
2.5V±0.2V	V_{CC}	≤2ns	$V_{CC}/2$	$2\times V_{CC}$	0.15V	30pF	500Ω
2.7V	2.7V	≤2.5ns	1.5V	6V	0.3V	50pF	500Ω
3.3V±0.3V	2.7V	≤2.5ns	1.5V	6V	0.3V	50pF	500Ω
5V±0.5V	V_{CC}	≤2.5ns	$V_{CC}/2$	$2\times V_{CC}$	0.3V	50pF	500Ω



PROPAGATION DELAY TIMES



ENABLE AND DISABLE TIMES

Notes: 1. C_L includes probe and jig capacitance.
2. All input pulses are supplied by generators having the following characteristics: P_{RR} ≤10MHz, Z_O = 50Ω.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.