
UF200G THRU UF208G

TRANSYS ELECTRONICS LIMITED

GLASS PASSIVATED JUNCTION ULTRAFAST SWITCHING RECTIFIER

VOLTAGE - 50 to 800 Volts CURRENT - 2.0 Amperes

DO-15



Dimensions in inches and (millimeters)

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O Utilizing Flame Retardant Epoxy Molding Compound
- Glass passivated junction in DO-15 package
- 2.0 ampere operation at T_A=55 ¢J with no thermal runaway
- Exceeds environmental standards of MIL-S-19500/228
- Ultra Fast switching for high efficiency

MECHANICAL DATA

Case: Molded plastic, DO-15

Terminals: axial leads, solderable per MIL-STD-202, Method 208

Polarity: Band denotes cathode

Mounting Position: Any

Weight: 0.015 ounce, 0.4 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 ¢J ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.


	UF200G	UF201G	UF202G	UF204G	UF206G	UF208G	UNITS
Peak Reverse Voltage, Repetitive; V_{RM}:	50	100	200	400	600	800	V
Maximum RMS Voltage	35	70	140	280	420	560	V
DC Reverse Voltage; V_R	50	100	200	400	600	800	V
Average Forward Current, Io @ T_A=55 ¢J 3/8" lead length, 60 Hz, resistive or inductive load	2.0						A
Peak Forward Surge Current, I_{FM} (surge) 8.3msec. single half sine wave superimposed on rated load(JECEC method)	60						A
Maximum Forward Voltage VF @ 2.0A, 25 ¢J	1.00			1.30	1.70		V
Maximum Reverse Current, @ Rated T_J=25 ¢J	10.0						£gA
Reverse Voltage T_J=100 ¢J	200						£gA
Typical Junction capacitance (Note 1) CJ	35						pF
Typical Junction Resistance (Note 2) R £KJA	45						¢J/W
Reverse Recovery Time I_F=.5A, I_R=1A, I_{rr}=.25A	50	50	50	50	100	100	ns
Operating and Storage Temperature Range	-55 to +150						¢J

NOTES:

1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC
2. Thermal resistance from junction to ambient and from junction to lead length 0.375"(9.5mm) P.C.B. mounted

RATING AND CHARACTERISTIC CURVES

UF200G THRU UF208G



NOTE:1.Rise Time = 7ns max.
Input Impedance = 1 megohm. 22pF
2.Rise Time = 10ns max.
Source Impedance = 50 Ohms




Fig. 1-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




Fig. 2-FORWARD CHARACTERISTICS




Fig. 3-FORWARD CURRENT DERATING CURVE




Fig. 4-TYPICAL JUNCTION CAPACITANCE




Fig. 5-PEAK FORWARD SURGE CURRENT