DATA SHEET

NEC

MOS FIELD EFFECT TRANSISTOR

μPA2714GR

SWITCHING
P-CHANNEL POWER MOS FET

DESCRIPTION

The μPA2714GR is P-Channel MOS Field Effect Transistor designed for power management applications of notebook computers and Li-ion battery protection circuit.


FEATURES

- Low on-state resistance
  $R_{DS(on)1}$ = 20 mΩ MAX. (V_{GS} = –10 V, I_D = –3.5 A)
  $R_{DS(on)2}$ = 30 mΩ MAX. (V_{GS} = –4.5 V, I_D = –3.5 A)
  $R_{DS(on)3}$ = 34 mΩ MAX. (V_{GS} = –4.0 V, I_D = –3.5 A)
- Low C_{iss}: C_{iss} = 1370 pF TYP.
- Small and surface mount package (Power SOP8)

ORDERING INFORMATION

PART NUMBER	PACKAGE
μPA2714GR	Power SOP8


PACKAGE DRAWING (Unit: mm)



ABSOLUTE MAXIMUM RATINGS (T_A = 25°C, All terminals are connected.)

Drain to Source Voltage (V_{GS} = 0 V)	V_{DSS}	–30	V
Gate to Source Voltage (V_{DS} = 0 V)	V_{GSS}	∓20	V
Drain Current (DC)	$I_{D(DC)}$	∓7	A
Drain Current (pulse) Note1	$I_{D(pulse)}$	∓28	A
Total Power Dissipation Note2	P_{T1}	2	W
Total Power Dissipation Note3	P_{T2}	2	W
Channel Temperature	T_{ch}	150	°C
Storage Temperature	T_{stg}	–55 to +150	°C
Single Avalanche Current Note4	I_{AS}	–7	A
Single Avalanche Energy Note4	E_{AS}	4.9	mJ

EQUIVALENT CIRCUIT



Notes 1. PW ≤ 10 μs, Duty Cycle ≤ 1%
2. Mounted on a ceramic substrate of 1200 mm² x 2.2 mm
3. Mounted on a glass epoxy board (1 inch x 1 inch x 0.8 mm) , PW = 10 sec
4. Starting T_{ch} = 25°C, V_{DD} = –15 V, R_G = 25 Ω, L = 100 μH, V_{GS} = –20 → 0 V

Remark Strong electric field, when exposed to this device, can cause destruction of the gate oxide and ultimately degrade the device operation. Steps must be taken to stop generation of static electricity as much as possible, and quickly dissipate it once, when it has occurred.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all products and/or types are available in every country. Please check with NEC Electronics sales representative for availability and additional information.

Document No. G15982EJ2V0DS00 (2nd edition)
Date Published November 2002 NS CP(K)
Printed in Japan


The mark ★ shows major revised points.

© NEC Electronics Corporation 2002


ELECTRICAL CHARACTERISTICS (T_A = 25°C, All terminals are connected.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = –30 V, V_{GS} = 0 V			–1	μA
Gate Leakage Current	I_{GSS}	V_{GS} = ∓20 V, V_{DS} = 0 V			∓100	nA
Gate Cut-off Voltage	$V_{GS(off)}$	V_{DS} = –10 V, I_D = –1 mA	–1.0		–2.5	V
Forward Transfer Admittance	$\|y_{fs}\|$	V_{DS} = –10 V, I_D = –3.5 A	5	11		S
Drain to Source On-state Resistance	$R_{DS(on)1}$	V_{GS} = –10 V, I_D = –3.5 A		16	20	mΩ
	$R_{DS(on)2}$	V_{GS} = –4.5 V, I_D = –3.5 A		22	30	mΩ
	$R_{DS(on)3}$	V_{GS} = –4.0 V, I_D = –3.5 A		25	34	mΩ
Input Capacitance	C_{iss}	V_{DS} = –10 V		1370		pF
Output Capacitance	C_{oss}	V_{GS} = 0 V		390		pF
Reverse Transfer Capacitance	C_{rss}	f = 1 MHz		240		pF
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = –15 V, I_D = –3.5 A		8		ns
Rise Time	t_r	V_{GS} = –10 V		15		ns
Turn-off Delay Time	$t_{d(off)}$	R_G = 10 Ω		76		ns
Fall Time	t_f			42		ns
Total Gate Charge	Q_G	V_{DD} = –24 V		31		nC
Gate to Source Charge	Q_{GS}	V_{GS} = –10 V		4		nC
Gate to Drain Charge	Q_{GD}	I_D = 7 A		9		nC
Body Diode Forward Voltage	$V_{F(S-D)}$	I_F = 7 A, V_{GS} = 0 V		0.82		V
Reverse Recovery Time	t_{rr}	I_F = 7 A, V_{GS} = 0 V		43		ns
Reverse Recovery Charge	Q_{rr}	di/dt = 100 A/μs		27		nC


TEST CIRCUIT 1 AVALANCHE CAPABILITY




TEST CIRCUIT 2 SWITCHING TIME



τ = 1 μs
Duty Cycle ≤ 1%




TEST CIRCUIT 3 GATE CHARGE




TYPICAL CHARACTERISTICS (T_A = 25°C)


DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA




TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




FORWARD BIAS SAFE OPERATING AREA




★ TRANSIENT THERMAL RESISTANCE vs. PULSE WIDTH




DRAIN CURRENT vs.
DRAIN TO SOURCE VOLTAGE




FORWARD TRANSFER CHARACTERISTICS




GATE CUT-OFF VOLTAGE vs.
CHANNEL TEMPERATURE




FORWARD TRANSFER ADMITTANCE vs.
DRAIN CURRENT




DRAIN TO SOURCE ON-STATE RESISTANCE vs.
DRAIN CURRENT




DRAIN TO SOURCE ON-STATE RESISTANCE vs.
GATE TO SOURCE VOLTAGE




DRAIN TO SOURCE ON-STATE RESISTANCE vs. CHANNEL TEMPERATURE




CAPACITANCE vs. DRAIN TO SOURCE VOLTAGE




SWITCHING CHARACTERISTICS




DYNAMIC INPUT/OUTPUT CHARACTERISTICS




SOURCE TO DRAIN DIODE FORWARD VOLTAGE




REVERSE RECOVERY TIME vs. DIODE FORWARD CURRENT



SINGLE AVALANCHE CURRENT vs.
INDUCTIVE LOAD



SINGLE AVALANCHE ENERGY
DERATING FACTOR



[MEMO]

- **The information in this document is current as of November, 2002. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with NEC Electronics sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such NEC Electronics products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

  The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

  "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

  "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

  "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact NEC Electronics sales representative in advance to determine NEC Electronics's willingness to support a given application.

(Note)

(1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.

(2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).