


UVCJ Series
5x7 mm, 3.3 Volt, LVPECL/LVDS, Clock Oscillators



- Integrated phase jitter of less than 1 ps from 12 kHz to 20 MHz
- Ideal for 10 and 40 Gigabit Ethernet and Optical Carrier applications



SUGGESTED SOLDER PAD LAYOUT



PIN 1 ENABLE
Pad1: Enable/Disable
Pad2: N/C
Pad3: Ground
Pad4: Output Q (LVPECL,LVDS,CML)
Pad5: Output $\bar{Q}$ (LVPECL,LVDS,CML)
Pad6: Vcc

PIN 2 ENABLE
Pad1: N/C
Pad2: Enable/Disable
Pad3: Ground
Pad4: Output Q (LVPECL,LVDS,CML)
Pad5: Output $\bar{Q}$ (LVPECL,LVDS,CML)
Pad6: Vcc

RoHS Compliant

Ordering Information

UVCJ 1 8 B L N 00.0000 MHz

Product Series

Temperature Range
1: 0°C to +70°C **2:** -40°C to +85°C
6: -20°C to +70°C **7:** -0°C to +85°C
8: 0°C to +50°C

Stability
3: ±100 ppm **4:** ±50 ppm
6: ±25 ppm **8:** ±20 ppm

Enable/Disable
B: Enable High (pin 1) **G:** Enable High (pin 2)
S: Enable Low (pin 1) **M:** Enable Low (pin 2)
U: No Enable/Disable

Symmetry/Output Logic Type
L: 45/55% LVDS **P:** 45/55% PECL
H: 40/60% LVDS **Q:** 40/60% PECL

Package/Lead Configurations
N: Leadless Ceramic (6 pads)

Frequency (customer specified)


M2013Sxxx - Contact factory for datasheet.

	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Electrical Specifications	Frequency Range	F	0.75		700	MHz	
	Operating Temperature	TA	(See ordering information)				
	Storage Temperature	TS	-55		+125	°C	
	Frequency Stability	ΔF/F	(See ordering information)				See Note 1
	Aging 1st Year Thereafter (per year)		 -3/-5 -1/-2		 +3/+5 +1/-2	 ppm ppm	 <52 MHz/ ≥52 MHz <52 MHz/ ≥52 MHz
	Input Voltage	Vcc	3.135	3.3	3.465	V	
	Input Current	Icc					
	0.75 to 24 MHz				70/30	mA	PECL/LVDS
	24 to 700 MHz				100/60	mA	PECL/LVDS
	Output Type						PECL/LVDS
	Load		50 Ohms to Vcc - 2 VCD 100 Ohm differential load				See Note 2 PECL Waveform LVDS Waveform
	Symmetry (Duty Cycle)		(See ordering information)				@ 50% of waveform
	Output Skew				200	ps	PECL
	Differential Voltage	Vod	250	350	450	mV	LVDS
	Logic "1" Level	Voh	Vcc -1.02			V	LVPECL
	Logic "0" Level	Vol			Vcc -1.63	V	LVPECL
	Rise/Fall Time	Tr/Tf		0.35 0.50	0.55 1.0	ns ns	@ 20/80% LVPECL @ 20/80% LVDS
	Enable Function		80% Vcc min or N/C output active 20% Vcc max: output disables to high-Z				Output Option B
			PECL low, GND, or N/C – output active PECL high 0 output disables to high-Z				Output Option S
	Start up Time				10	ms	
	Phase Jitter (Typical) 0.75 to 49.00 MHz 50.00 to 161.00 MHz 162.00 to 239.00 MHz 240.00 to 499.00 MHz 500.00 to 700.00 MHz	ϕJ		 2.25 0.35 2.85 1.95 1.30		 ps RMS ps RMS ps RMS ps RMS ps RMS	See Note 3 Integrated 12 kHz – 20 MHz Integrated 12 kHz – 20 MHz Integrated 12 kHz – 20 MHz Integrated 12 kHz – 20 MHz Integrated 12 kHz – 20 MHz
Environmental							
	Mechanical Shock	MIL-STD-202, Method 213, C (100 g's)					
	Vibration	MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)					
	Thermal Cycle	MIL-STD-883, Method 1010, B (-55°C to +125°C, 15 min dwell, 10 cycles)					
	Hermeticity	MIL-STD-202, Method 112					
	Solderability	Per EIAJ-STD-002					
	Max Soldering Conditions	See solder profile, Figure 1					

1. Inclusive of initial tolerance, deviation over temperature, shock, vibration, voltage and aging.
2. PECL load - see Load Circuit Diagram #5. LVDS load – see load circuit diagram #9. Consult factory with nonstandard output load requirements.
3. Consult factory for phase jitter at other specific frequencies.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

MtronPTI Lead Free Solder Profile



MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see **www.mtronpti.com** for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI **1-800-762-8800.**